Radiant and hydronic piping systems

Barrier tubing

Wirsbo hePEX™ coils



Wirsbo hePEX[™] features an oxygen barrier that conforms to DIN 4726 for use in closed-loop hydronic piping and radiant heating and cooling applications. The tubing is rated and listed by the Hydrostatic Stress Board of PPI at 200°F at 80psi, 180°F at 100psi and 73.4°F at 160psi. It is compatible with Uponor ProPEX and QS-style fittings and is manufactured in full compliance to ASTM F876 and F877. It is also listed to NSF 61 for potable-water applications.

| Part no. | Part description | Coils/pallet |
|----------|--|--------------|
| A1140313 | 5/16" Wirsbo hePEX, 100-ft. coil | 30 |
| A1180313 | 5/16" Wirsbo hePEX, 250-ft. coil | 40 |
| A1220313 | 5/16" Wirsbo hePEX, 1,000-ft. coil | 12 |
| A1140375 | 3/8" Wirsbo hePEX, 100-ft. coil | 28 |
| A1210375 | 3/8" Wirsbo hePEX, 400-ft. coil | 18 |
| A1220375 | 3/8" Wirsbo hePEX, 1,000-ft. coil | 12 |
| A1140500 | ½" Wirsbo hePEX, 100-ft. coil | 22 |
| A1250500 | 1/2" Wirsbo hePEX, 300-ft. coil | 18 |
| A1260500 | 1/2" Wirsbo hePEX, 500-ft. coil | 12 |
| A1220500 | ½" Wirsbo hePEX, 1,000-ft. coil | 8 |
| A1140625 | 5/8" Wirsbo hePEX, 100-ft. coil | 15 |
| A1250625 | 5%" Wirsbo hePEX, 300-ft. coil | 12 |
| A1210625 | 5%" Wirsbo hePEX, 400-ft. coil | 12 |
| A1220625 | 5%" Wirsbo hePEX, 1,000-ft. coil | 5 |
| A1140750 | ³ / ₄ " Wirsbo hePEX, 100-ft. coil | 22 |
| A1250750 | ³ / ₄ " Wirsbo hePEX, 300-ft. coil | 12 |
| A1240750 | 3/4" Wirsbo hePEX, 500-ft. coil | 8 |
| A1220750 | 3/4" Wirsbo hePEX, 1,000-ft. coil | 3 |
| A1141000 | 1" Wirsbo hePEX, 100-ft. coil | 12 |
| A1251000 | 1" Wirsbo hePEX, 300-ft. coil | 5 |
| A1241000 | 1" Wirsbo hePEX, 500-ft. coil | 6 |
| A1141250 | 11/4" Wirsbo hePEX, 100-ft. coil | 7 |
| A1251250 | 11/4" Wirsbo hePEX, 300-ft. coil | 2 |
| A1141500 | 1½" Wirsbo hePEX, 100-ft. coil | 7 |
| A1251500 | 1½" Wirsbo hePEX, 300-ft. coil | 2 |
| A1142000 | 2" Wirsbo hePEX, 100-ft. coil | 5 |
| A1252000 | 2" Wirsbo hePEX, 300-ft. coil | 2 |
| A1142500 | 2½" Wirsbo hePEX, 100-ft. coil | 1 |
| A1252500 | 2½" Wirsbo hePEX, 300-ft. coil | 1 |
| A1143000 | 3" Wirsbo hePEX, 100-ft. coil | 1 |
| A1253000 | 3" Wirsbo hePEX, 300-ft. coil | 1 |
| A1143500 | 3½" Wirsbo hePEX, 100-ft. coil | 1 |
| A1144000 | 4" Wirsbo hePEX, 100-ft. coil | 1 |

Note: Other non-standard lengths are available on a made-to-order basis. Allow six weeks for delivery. Call Uponor Customer Service at 888.594.7726 for availability and pricing. Wirsbo hePEX 3½" and 4" tubing uses WIPEX™ fittings. See **page 108** for a listing of WIPEX fittings.