



Actuated Valves Product Tandem Actuated Butterfly Valves

Tandem Actuated Butterfly Valves

Custom configured and produced to order, Spears® Tandem Actuated Butterfly Valves are available in multiple configurations to meet variety of operational needs. Tandem Actuated Butterfly Valves utilize a Tee-Style configuration for 3-way or diverting operation where two (2) valves are operated from one (1) actuator.



Multi-Featured Options:

- Tandem 3-Way: two valves operated from one actuator, both closing or both opening at the same time.
- Tandem Diverting: two valves operated from one actuator, one opening while the other closes.
- Variable Valve Orientation Available
- Multi Seat Material Options including EPDM, FKM, Buna-N, and PTFE Sleeved Seats.
- Multi Flanged Connection Options including Standard, Lug-Insert or True-Lug Style Valves
- Multi Actuation Option, including Electric or Pneumatic with a host of Actuation Accessories for each (see Electric or Pneumatic Actuator Accessories for Butterfly Valves)

Pressure Rating @ 73°F (23°C), Water
150 psi for Sizes through 12"
(Larger Sizes Available)

Maximum Service Temperature
PVC = 140°F (60°C)
CPVC = 200°F (93°C)
Temperature/Pressure De-ratings Apply

CONTACT SPEARS® FOR SELECTION ASSISTANCE & MSRP