



Double Containment Product Access Tees & Closure Fittings

Access Tees


DC Access Tee CPVC Sch 80 x CPVC Sch 80 (continued)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
DCAT-C030-C060	3X6	1	4	470	1878.62
DCAT-C040-C080	4X8	1	0	470	4771.17
DCAT-C060-C100	6X10	1	0	470	5102.41
DCAT-C080-C120	8X12	1	0	470	7775.39

DC Access Tee CPVC Sch 80 x PVC Sch 40 Clear

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
DCAT-C005-G020	1/2X2	1	10	470	342.44
DCAT-C007-G030	3/4X3	1	5	470	720.80
DCAT-C010-G030	1X3	1	5	470	728.44
DCAT-C015-G040	1-1/2X4	1	3	470	1204.88
DCAT-C020-G040	2X4	1	6	470	1213.92
DCAT-C030-G060	3X6	1	4	470	1735.86
DCAT-C040-G080	4X8	1	2	470	3101.24

Closure Fittings



A Closure Fitting is a special coupling configuration for joining both Carrier and Containment piping in situations where opposing runs of Carrier and Containment system must meet. Closure Fittings are frequently used at the end of a system where the final Termination Fitting must connect to a fixed point in the system. Spears® offers a complete range of Solvent Cement Closure Fittings that form a permanent solvent cement joint, plus special Union Closure Fittings in limited sizes that provide an easily-installed union to join these opposing Containment piping runs. See Double Containment Design & Installation Guide for proper installation.

Solvent Cement Closure Fittings consist of a male component and a female component. An internal O-ring on each component serves as a "cement-wiper" during installation to assure a proper joint. A "One-step" type cement, such as Spears® CPVC 24 for both PVC & CPVC, should be used to facilitate rapid assembly. See Double Containment Design & Installation Guide for proper installation.

Union Closure Fittings consist of a male component and female component with Union Nut and O-ring seal. Each component is installed on the carrier pipe incorporating a double O-ring seal on the carrier pipe with cemented retainers. Union Closure Fitting allows for easy access to carrier pipe after installation and also provides a small amount of expansion and contraction. See Double Containment Design & Installation Guide and product-enclosed instructions for proper installation.

Closure Fittings

Centralizers are used inside the Containment piping system, but not inside fittings installed on Carrier pipe and must be ordered separately according to same Carrier x Containment size and pipe schedule selected.

DC Solvent Cement Closure Fitting PVC Sch 40

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
DCCF-A030	3	1	10	470	576.84
DCCF-A040	4	1	5	470	591.02
DCCF-A060	6	1	2	470	615.08
DCCF-A080	8	1	0	470	848.44
DCCF-A100	10	1	2	470	935.94
DCCF-A120	12	1	2	470	1478.46

DC Solvent Cement Closure Fitting PVC Sch 80

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
DCCF-B020	2	1	10	470	576.34
DCCF-B030	3	1	10	470	586.20
DCCF-B040	4	1	5	470	604.02
DCCF-B060	6	1	2	470	639.77
DCCF-B080	8	1	3	470	848.18
DCCF-B100	10	1	2	470	1125.61
DCCF-B120	12	1	0	470	1804.39

DC Solvent Cement Closure Fitting CPVC Sch 80

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
DCCF-C020	2	1	10	470	585.08
DCCF-C030	3	1	10	470	609.48
DCCF-C040	4	1	5	470	636.14
DCCF-C060	6	1	2	470	775.38
DCCF-C080	8	1	3	470	1043.08
DCCF-C100	10	1	2	470	1941.80
DCCF-C120	12	1	0	470	3080.82

DC Solvent Cement Closure Fitting PVC Sch 40 Clear

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
DCCF-G030	3	1	10	470	643.66
DCCF-G040	4	1	5	470	668.73
DCCF-G060	6	1	2	470	793.19
DCCF-G080	8	1	6	470	1178.67

DC Union Closure Fittings PVC Clear - EPDM Seals

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
DCUC-030	3	1	0	471	174.95
DCUC-040	4	1	0	471	225.11
DCUC-060	6	1	0	471	281.59

Maximum 100 psi Short Term Hydrostatic Test Only.
50 psi Working Pressure @ 73° F (23° C)

DC Union Closure Fittings PVC Clear - FKM Seals

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
DCUC2-040	4	1	0	471	288.88
DCUC2-060	6	1	0	471	396.73