Spears[®] Sprinkler Head Adapter Removal Kit

Occasionally a Sprinkler Head Adapter may need to be removed for relocation, extension or repair. Kit includes Cutter, Deburring Tool and Wrench. Cutter provides easy cutting of pipe from the inside (using a power drill) to remove adapters without disturbing ceiling or side wall. Deburring Tool allows removal of burrs in cut pipe. Wrench is designed to hold Spears® TorqueSafe™ Head Adapter brass insert from rotating to aid in sprinkler head removal from adapter, if required.

Part Number	Size			Prod Code	MSRP
-------------	------	--	--	--------------	------

Complete Kit Inside Pipe Cutter, Deburring Tool and Wrench True Union Industrial Drain Valve SHRK-005 3/4" & 1" Pipe 660.31 15 299 With Locking Handle Socket x Socket CPVC Gray Valve with CPVC Orange End Connector Inside Pipe Cutter Only GSC-005 3/4" & 1" Pipe 25 0 299 388.02 Not UL Listed **True Union Standard Drain Valves Deburring Tool Only** Socket x Socket **GSB-005** 3/4" & 1" Pipe 447.66 25 0 299 Wrench Only **GSW-005** For 1/2 50 299 161.03 1 Compact 2000 Drain Valve

CPVC Riser Drain Valves For NFPA 13D Installations Only

FlameGuard[®] CPVC Drain & Check Valves For NFPA 13D Applications Only

Application: FlameGuard® CPVC Orange Check Valves and PVC/CPVC True Union Drain Valves are for use in configuring CPVC Fire Sprinkler System connection to water supply (riser/drain assembly) in NFPA 13D installations only. These valves are not UL Listed and NOT for use in any other locations within the fire sprinkler system.

Part Number Size	Std Mstr Prod Pk Ctn Code MSRP
------------------	-----------------------------------



1822-007CFG	3/4	1	18	077	96.40
1822-010CFG	1	1	12	077	114.77
1822-012CFG	1-1/4	1	8	077	182.45
1822-015CFG	1-1/2	1	8	077	192.69
1822-020CFG	2	1	4	077	257.71

PVC Gray Valve with CPVC Orange End Connector

3622-007FG	3/4	1	18	077	54.86		
3622-010FG	1	1	12	077	65.34		
Not UL Listed							



Socket x Socket

6622-007CO	3/4	10	80	077	37.65
6622-010CO	1	10	0	077	47.07
Not UL Listed					

CPVC Swing Check Valves

Socket x Socket

S1520-10CO S1520-12CO S1520-15CO

Τ	1	20	0	077	37.46		
Τ	1-1/4	12	0	077	41.86		
T	1-1/2	12	0	077	47.07		

Made in the U.S.A.

Suitable for Oil-Free air handling to 25 psi, not for distribution of compressed air or gas Effective 02/01/2020 See MSRP-1 Sheet or Check Spears[®] On-line Catalog @ www.spearsmfg.com for Pricing

Page 12



FlameGuard[®] Product CPVC Riser Drain Valves For NFPA 13D Installations Only

CPVC Riser Drain Valves For NFPA 13D Installations

	Only				
Part Number	Size			Prod Code	MSRP
CPVC Swing Check Valves (continued)					
Socket x Socket					
Not UL Listed					

CPVC Special Reinforced Thread Inlet Swing Check Valves



SR Fipt x Socket

Not UL Listed	-		-		
S1520-15FSRSCO	1-1/2	12	0	077	55.57
S1520-12FSRSCO	1-1/4	12	0	077	46.83
S1520-10FSRSCO	1	20	0	077	40.57

General Installation Information: Socket end connections should be installed using Spears[®] FS-5 One-Step Cement for use with Spears[®] CPVC Fire Sprinkler Products. Threaded connections should be made using Spears[®] BLUE 75[™] Thread Sealant tested for compatibility with CPVC materials. PVC True Union Drain Valves are to be installed with system connection to Valve CPVC End Connector. Swing check valves are designed for horizontal installations, but may be installed in up-flow only vertical position. Check valves MUST be installed with the valve's FLOW arrow pointing in the direction of the flow. Do not install valve upside down.