



## Valves Product Lab Ball Valves & Utility Ball Valves

### Lab Ball Valves



Socket/Threaded Valve Only



Valve & Adapters

- Valve & Adapters includes:
- 1 - Threaded 1/4" Valve
  - 2 - O-ring Sealed 1/4" MPT x Mipt Adapters
  - 2 - EPDM or FKM O-rings (AS568-013 size)
  - 1 - End Connector Wrench
  - 2 - O-ring Sealed 1/4" MPT x 3/8" I.D. Tubing Barb Adapters
  - OR -
  - 2 - O-ring Sealed 1/4" MPT x 1/4" I.D. Tubing Barb Adapters
- Pressure Rating @ 73°F (23°C), Water  
1/8" - 3/8" 150 psi
- Maximum Service Temperature  
PVC = 140°F (60°C)  
CPVC = 200°F (93°C)
- Temperature/Pressure De-ratings Apply
- Rated for Vacuum Service

### Lab Valve - PVC

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

#### Valve & Adapters Threaded Ends

1/4X1/4T	1529-002A 31.62	1539-002A 33.05	1	25	218
1/4X3/8T	1529-002 31.62	1539-002 33.05	1	25	218

#### Valve only Threaded Ends

1/4	1521-002 25.26	1531-002 28.14	50	200	218
3/8	1521-003 35.52	1531-003 39.38	50	200	218

#### Valve Only Female x Male Thread Ends

1/8	152FM-001 31.62	153FM-001 33.05	25	200	218
1/4	152FM-002 31.62	153FM-002 33.05	25	200	218

#### Valve only Socket Ends

1/4	1522-002 25.26	---	50	200	218
3/8	1522-003 35.52	---	50	200	218

### Lab Valve - CPVC

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

#### Valve & Adapters Threaded Ends

1/4X1/4T	1529-002CA 37.95	1539-002CA 38.69	1	25	219
1/4X3/8T	1529-002C 37.95	1539-002C 38.69	1	25	219

#### Valve only Threaded Ends

1/4	1521-002C 30.38	1531-002C 33.41	50	200	219
3/8	1521-003C 42.61	1531-003C 39.94	50	200	219

#### Valve Only Female x Male Thread Ends

1/8	152FM-001C 37.95	---	25	200	219
1/4	152FM-002C 37.95	---	25	200	219

#### Valve only Socket Ends

1/4	1522-002C 30.38	1532-002C 36.16	50	200	219
3/8	1522-003C 42.61	1532-003C 47.31	50	200	219

### Utility Ball Valves



- Pressure Rating @ 73°F (23°C), Water  
1/2" - 6" 150 psi
- Maximum Service Temperature  
PVC = 140°F (60°C)  
CPVC = 200°F (93°C)
- Temperature/Pressure De-ratings Apply
- All Valves Assembled with Silicone-Free, Water Soluble Lubricant
- Note: Standard 6" Valve uses Lever-Style Handle for proper leverage.

### PVC w/EPDM O-ring Seal

Size	Threaded Ends	Socket Ends	Std Pk	Mstr Pk	Prod Code
------	---------------	-------------	--------	---------	-----------

#### PVC White

1/2	2621-005 11.51	2622-005 11.51	50	0	215
3/4	2621-007 13.66	2622-007 13.66	25	0	215
1	2621-010 18.57	2622-010 18.57	25	0	215
1-1/4	2621-012 24.59	2622-012 24.59	20	0	215
1-1/2	2621-015 37.53	2622-015 37.53	20	0	215
2	2621-020 47.43	2622-020 47.43	8	0	215
2-1/2	2621-025 81.20	2622-025 81.20	6	0	214
3	2621-030 145.63	2622-030 145.63	1	4	214