

Valves Product
Single Entry Ball Valves & Compact 2000 Ball Valves



Single Entry Ball Valves

PVC White (continued)

Size	Buna-N	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	--------	------	-----	--------	---------	-----------

Socket Ends

4	2412-040W 538.33	2422-040W 593.09	2432-040W 644.73	1	0	240
---	---------------------	---------------------	---------------------	---	---	-----

PVC Gray

Size	Buna-N	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	--------	------	-----	--------	---------	-----------

Threaded Ends

1/2	2411-005G 25.64	2421-005G 28.42	2431-005G 31.62	10	120	240
3/4	2411-007G 32.29	2421-007G 35.93	2431-007G 39.88	10	80	240
1	2411-010G 37.99	2421-010G 42.17	2431-010G 46.88	10	0	240
1-1/4	2411-012G 52.77	2421-012G 58.66	2431-012G 65.09	6	0	240
1-1/2	2411-015G 66.44	2421-015G 77.82	2431-015G 86.53	5	0	240
2	2411-020G 76.92	2421-020G 85.47	2431-020G 94.93	5	0	240
3	2411-030G 268.09	2421-030G 332.49	2431-030G 383.43	1	0	240
4	2411-040G 566.64	2421-040G 624.34	2431-040G 678.64	1	0	240

Socket Ends

1/2	2412-005G 25.64	2422-005G 28.42	2432-005G 31.62	10	120	240
3/4	2412-007G 32.29	2422-007G 35.93	2432-007G 39.88	10	80	240
1	2412-010G 37.99	2422-010G 42.17	2432-010G 46.88	10	0	240
1-1/4	2412-012G 52.77	2422-012G 58.66	2432-012G 65.09	5	0	240
1-1/2	2412-015G 66.51	2422-015G 77.82	2432-015G 86.53	5	0	240
2	2412-020G 76.92	2422-020G 85.47	2432-020G 94.93	5	0	240
3	2412-030G 268.09	2422-030G 332.49	2432-030G 383.43	1	0	240
4	2412-040G 566.64	2422-040G 624.34	2432-040G 678.64	1	0	240

Compact 2000 Ball Valves



Pressure Rating @ 73°F (23°C), Water
 1/2" - 2" 235 psi
 Flanged 150 psi

Maximum Service Temperature
 PVC = 140°F (60°C)
 CPVC = 200°F (93°C)
 Temperature/Pressure De-ratings Apply

All Valves Assembled with Silicone-Free, Water Soluble Lubricants.
 Rated for Vacuum Service

Compact 2000 Ball Valves are a Maintenance-Free, Sealed Unit
 (non-repairable).

See Ball Valve Accessories & Repair Kits Section for Additional Options
 and Features.

PVC 2000 Compact Ball Valve

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Socket Ends

1/2	6622-005 25.98	6632-005 29.25	10	120	210
3/4	6622-007 35.45	6632-007 36.31	10	80	210
1	6622-010 38.72	6632-010 43.41	10	0	210
1-1/4	6622-012 58.24	6632-012 67.29	6	0	210
1-1/2	6622-015 69.35	6632-015 77.14	5	0	210
2	6622-020 92.60	6632-020 104.03	8	0	210

Threaded Ends

1/2	6621-005 25.98	6631-005 29.25	10	120	210
3/4	6621-007 35.45	6631-007 36.11	10	80	210
1	6621-010 38.72	6631-010 43.41	10	0	210
1-1/4	6621-012 63.75	6631-012 67.29	6	0	210
1-1/2	6621-015 69.35	6631-015 77.14	5	0	210
2	6621-020 92.60	6631-020 104.03	8	0	210

Flanged Ends

1/2	6623-005 54.74	6633-005 57.52	10	0	210
3/4	6623-007 61.82	6633-007 63.98	10	120	210
1	6623-010 80.55	6633-010 84.87	10	0	210
1-1/4	6623-012 100.59	6633-012 107.92	10	0	210



Valves Product

Compact 2000 Ball Valves & Compact Ball Valves (Regular Style)

Compact 2000 Ball Valves

PVC 2000 Compact Ball Valve (continued)

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Flanged Ends

1-1/2	6623-015 121.69	6633-015 132.27	1	4	210
2	6623-020 162.39	6633-020 169.52	1	0	210

CPVC 2000 Compact Ball Valve

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Socket Ends

1/2	6622-005C 30.60	6632-005C 34.06	10	120	212
3/4	6622-007C 40.37	6632-007C 45.36	10	80	212
1	6622-010C 50.45	6632-010C 56.73	10	0	212
1-1/4	6622-012C 82.57	6632-012C 102.04	6	0	212
1-1/2	6622-015C 102.13	6632-015C 113.46	5	0	212
2	6622-020C 133.80	6632-020C 150.31	8	0	212

Threaded Ends

1/2	6621-005C 30.60	6631-005C 34.06	10	120	212
3/4	6621-007C 40.37	6631-007C 45.36	10	80	212
1	6621-010C 50.45	6631-010C 56.73	10	0	212
1-1/4	6621-012C 82.57	6631-012C 102.04	6	0	212
1-1/2	6621-015C 102.13	6631-015C 113.46	5	0	212
2	6621-020C 133.80	6631-020C 150.31	8	0	212

Flanged Ends

1/2	6623-005C 83.75	6633-005C 86.34	1	0	212
3/4	6623-007C 98.99	6633-007C 103.36	1	0	212
1	6623-010C 130.27	6633-010C 137.96	1	8	212
1-1/4	6623-012C 163.85	6633-012C 172.65	1	0	212
1-1/2	6623-015C 207.03	6633-015C 219.43	1	4	212
2	6623-020C 288.46	6633-020C 296.98	1	0	212

Compact Ball Valves (Regular Style)



Pressure Rating @ 73°F (23°C), Water
 1/2" - 2" 235 psi
 3" - 6" 150 psi
 Flanged 150 psi

Maximum Service Temperature
 PVC = 140°F (60°C)
 CPVC = 200°F (93°C)

Temperature/Pressure De-ratings Apply
 Rated for Vacuum Service

Socket/Threaded Style

All Valves Assembled with Silicone-Free, Water Soluble Lubricants.

See Ball Valve Accessories & Repair Kits Section
 for Additional Options and Features

Note: Standard 6" Valve uses Lever-Style Handle for proper leverage.

T-Handle option is more compact but will increase difficulty of operation.

PVC

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Socket Ends

1/2	2122-005 27.34	2132-005 30.79	10	80	210
3/4	2122-007 37.32	2132-007 38.22	10	0	210
1	2122-010 40.73	2132-010 45.72	10	0	210
1-1/4	2122-012 73.03	2132-012 81.19	6	0	210
1-1/2	2122-015 90.43	2132-015 94.48	5	0	210
2	2122-020 97.46	2132-020 109.51	6	0	210
3	2122-030 316.77	2132-030 355.87	1	4	211
4	2122-040 487.35	2132-040 701.51	1	0	211
6 (Lever Handle)	2122-060 632.91	2132-060 911.04	1	0	211
6 (Tee Handle)	21226-060 632.91	21326-060 911.04	1	0	211

Threaded Ends

1/2	2121-005 27.34	2131-005 30.79	10	80	210
3/4	2121-007 37.32	2131-007 38.22	10	0	210