



Valves Product

True Union Ball Valves (Regular Style) & Single Entry Ball Valves

True Union Ball Valves (Regular Style)

CPVC (continued)

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Socket Venturied Ends

6 VENTURIED	2322-060C 2345.45	2332-060C 2433.56	1	0	233
-------------	----------------------	----------------------	---	---	-----

Threaded Ends

2-1/2	2321-025C 665.45	2331-025C 739.36	1	0	232
3	2321-030C 778.08	2331-030C 864.56	1	0	232
4	2321-040C 1409.89	2331-040C 1566.56	1	0	232

Flanged Ends

1/2	2323-005C 157.43	2333-005C 160.83	6	0	232
3/4	2323-007C 193.00	2333-007C 201.04	5	0	232
1	2323-010C 220.98	2333-010C 234.56	5	0	232
1-1/4	2323-012C 330.13	2333-012C 341.72	2	0	232
1-1/2	2323-015C 363.16	2333-015C 375.20	3	0	232
2	2323-020C 505.33	2333-020C 601.83	2	0	232
2-1/2	2323-025C 896.00	2333-025C 1075.48	1	0	232
3	2323-030C 1310.35	2333-030C 1340.21	1	0	232
4	2323-040C 2298.12	2333-040C 2390.03	1	0	232

Flanged Venturied Ends

6 VENTURIED	2323-060C 3562.18	2333-060C 3685.63	1	0	233
-------------	----------------------	----------------------	---	---	-----

Single Entry Ball Valves



PVC White – Socket/Threaded Style PVC Gray – Socket/Threaded Style

Pressure Rating @ 73°F (23°C), Water
 1/2" - 2" 235 psi
 3" - 4" 150 psi

Maximum Service Temperature
 PVC = 140°F (60°C)

Temperature/Pressure De-ratings Apply

Rated for Vacuum Service

All Valves Assembled with Silicone-Free, Water Soluble Lubricant. See Ball Valve Accessories & Repair Kits Section for Additional Options and Features

PVC White

Size	Buna-N	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	--------	------	-----	--------	---------	-----------

Threaded Ends

1/2	2411-005W 23.35	2421-005W 25.89	2431-005W 28.80	10	120	240
3/4	2411-007W 31.62	2421-007W 32.60	2431-007W 36.22	10	80	240
1	2411-010W 34.52	2421-010W 38.33	2431-010W 42.62	10	0	240
1-1/4	2411-012W 47.99	2421-012W 53.36	2431-012W 59.27	6	0	240
1-1/2	2411-015W 62.20	2421-015W 72.22	2431-015W 78.31	5	0	240
2	2411-020W 70.02	2421-020W 77.73	2431-020W 86.39	5	0	240
3	2411-030W 254.66	2421-030W 315.93	2431-030W 364.24	1	0	240
4	2411-040W 538.33	2421-040W 593.09	2431-040W 644.73	1	0	240

Socket Ends

1/2	2412-005W 23.35	2422-005W 25.89	2432-005W 28.80	10	120	240
3/4	2412-007W 31.62	2422-007W 32.60	2432-007W 36.22	10	80	240
1	2412-010W 34.52	2422-010W 38.33	2432-010W 42.62	10	0	240
1-1/4	2412-012W 47.99	2422-012W 53.36	2432-012W 59.27	6	0	240
1-1/2	2412-015W 62.20	2422-015W 72.22	2432-015W 78.32	5	0	240
2	2412-020W 70.02	2422-020W 77.73	2432-020W 86.39	5	0	240
3	2412-030W 254.66	2422-030W 315.93	2432-030W 364.24	1	0	240

Valves Product
Single Entry Ball Valves & Compact 2000 Ball Valves



Single Entry Ball Valves

PVC White (continued)

Size	Buna-N	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	--------	------	-----	--------	---------	-----------

Socket Ends

4	2412-040W 538.33	2422-040W 593.09	2432-040W 644.73	1	0	240
---	---------------------	---------------------	---------------------	---	---	-----

PVC Gray

Size	Buna-N	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	--------	------	-----	--------	---------	-----------

Threaded Ends

1/2	2411-005G 25.64	2421-005G 28.42	2431-005G 31.62	10	120	240
3/4	2411-007G 32.29	2421-007G 35.93	2431-007G 39.88	10	80	240
1	2411-010G 37.99	2421-010G 42.17	2431-010G 46.88	10	0	240
1-1/4	2411-012G 52.77	2421-012G 58.66	2431-012G 65.09	6	0	240
1-1/2	2411-015G 66.44	2421-015G 77.82	2431-015G 86.53	5	0	240
2	2411-020G 76.92	2421-020G 85.47	2431-020G 94.93	5	0	240
3	2411-030G 268.09	2421-030G 332.49	2431-030G 383.43	1	0	240
4	2411-040G 566.64	2421-040G 624.34	2431-040G 678.64	1	0	240

Socket Ends

1/2	2412-005G 25.64	2422-005G 28.42	2432-005G 31.62	10	120	240
3/4	2412-007G 32.29	2422-007G 35.93	2432-007G 39.88	10	80	240
1	2412-010G 37.99	2422-010G 42.17	2432-010G 46.88	10	0	240
1-1/4	2412-012G 52.77	2422-012G 58.66	2432-012G 65.09	5	0	240
1-1/2	2412-015G 66.51	2422-015G 77.82	2432-015G 86.53	5	0	240
2	2412-020G 76.92	2422-020G 85.47	2432-020G 94.93	5	0	240
3	2412-030G 268.09	2422-030G 332.49	2432-030G 383.43	1	0	240
4	2412-040G 566.64	2422-040G 624.34	2432-040G 678.64	1	0	240

Compact 2000 Ball Valves



Pressure Rating @ 73°F (23°C), Water
 1/2" - 2" 235 psi
 Flanged 150 psi

Maximum Service Temperature
 PVC = 140°F (60°C)
 CPVC = 200°F (93°C)
 Temperature/Pressure De-ratings Apply

All Valves Assembled with Silicone-Free, Water Soluble Lubricants.
 Rated for Vacuum Service

Compact 2000 Ball Valves are a Maintenance-Free, Sealed Unit
 (non-repairable).

See Ball Valve Accessories & Repair Kits Section for Additional Options
 and Features.

PVC 2000 Compact Ball Valve

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	------	-----	--------	---------	-----------

Socket Ends

1/2	6622-005 25.98	6632-005 29.25	10	120	210
3/4	6622-007 35.45	6632-007 36.31	10	80	210
1	6622-010 38.72	6632-010 43.41	10	0	210
1-1/4	6622-012 58.24	6632-012 67.29	6	0	210
1-1/2	6622-015 69.35	6632-015 77.14	5	0	210
2	6622-020 92.60	6632-020 104.03	8	0	210

Threaded Ends

1/2	6621-005 25.98	6631-005 29.25	10	120	210
3/4	6621-007 35.45	6631-007 36.11	10	80	210
1	6621-010 38.72	6631-010 43.41	10	0	210
1-1/4	6621-012 63.75	6631-012 67.29	6	0	210
1-1/2	6621-015 69.35	6631-015 77.14	5	0	210
2	6621-020 92.60	6631-020 104.03	8	0	210

Flanged Ends

1/2	6623-005 54.74	6633-005 57.52	10	0	210
3/4	6623-007 61.82	6633-007 63.98	10	120	210
1	6623-010 80.55	6633-010 84.87	10	0	210
1-1/4	6623-012 100.59	6633-012 107.92	10	0	210