



Schedule 80 CPVC Product

Tank Adapters

Tank Adapters

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Tank Adapters, CPVC New Style Standard with Neoprene Gaskets

Socket x Socket

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8170-002C	1/4	25	150	101	59.34
8170-003C	3/8	25	150	101	59.34
8170-005C	1/2	25	0	101	59.34
8170-007C	3/4	25	0	101	70.59
8170-010C	1	25	0	101	79.23
8170-012C	1-1/4	20	0	101	101.05
8170-015C	1-1/2	20	0	101	110.04
8170-020C	2	15	0	101	155.34
8170-025C	2-1/2	4	0	101	228.29
8170-030C	3	4	0	101	271.75
8170-040C	4	2	0	101	452.87
8170-060C	6	1	0	101	1245.43
8170-080C	8	1	0	101	2767.42



Tank Adapters, CPVC New Style Standard with EPDM Gaskets

Socket x Socket

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8170E-002C	1/4	25	150	101	67.49
8170E-003C	3/8	25	150	101	67.49
8170E-005C	1/2	25	0	101	67.49
8170E-007C	3/4	25	0	101	75.75
8170E-010C	1	25	0	101	87.96
8170E-012C	1-1/4	20	0	101	111.31
8170E-015C	1-1/2	20	0	101	116.79
8170E-020C	2	15	0	101	168.38
8170E-025C	2-1/2	4	0	101	239.16
8170E-030C	3	4	0	101	284.75
8170E-040C	4	2	0	101	472.65
8170E-060C	6	1	0	101	1297.32
8170E-080C	8	1	0	101	2848.33



Tank Adapters, CPVC New Style Standard with FKM Gaskets

Socket x Socket

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8170V-002C	1/4	25	150	101	88.48
8170V-003C	3/8	25	150	101	88.48
8170V-005C	1/2	25	0	101	88.48
8170V-007C	3/4	25	0	101	101.80
8170V-010C	1	25	0	101	117.84
8170V-012C	1-1/4	20	0	101	144.79
8170V-015C	1-1/2	20	0	101	150.94
8170V-020C	2	15	0	101	228.51
8170V-025C	2-1/2	4	0	101	328.89



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Tank Adapters, CPVC New Style Standard with FKM Gaskets

(continued)

Socket x Socket

8170V-030C	3	4	0	101	391.56
8170V-040C	4	2	0	101	867.27
8170V-060C	6	1	0	101	2179.57
8170V-080C	8	1	0	101	5098.57

Tank Adapters, CPVC New Style Standard with Neoprene Gaskets

Socket x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171-002C	1/4	25	150	101	59.34
8171-003C	3/8	25	200	101	59.34
8171-005C	1/2	25	0	101	59.34
8171-007C	3/4	25	0	101	70.59
8171-010C	1	25	0	101	79.23
8171-012C	1-1/4	20	0	101	101.05
8171-015C	1-1/2	20	0	101	110.04
8171-020C	2	15	0	101	155.34
8171-025C	2-1/2	4	0	101	228.29
8171-030C	3	4	0	101	271.75
8171-040C	4	2	0	101	452.87
8171-060C	6	1	0	101	1245.43



Tank Adapters, CPVC New Style Standard with EPDM Gaskets

Socket x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171E-002C	1/4	25	150	101	67.49
8171E-003C	3/8	25	200	101	67.49
8171E-005C	1/2	25	0	101	67.49
8171E-007C	3/4	25	0	101	75.75
8171E-010C	1	25	0	101	87.96
8171E-012C	1-1/4	20	0	101	111.31
8171E-015C	1-1/2	20	0	101	116.79
8171E-020C	2	15	0	101	168.38
8171E-025C	2-1/2	4	0	101	239.16
8171E-030C	3	4	0	101	284.75
8171E-040C	4	2	0	101	472.65
8171E-060C	6	1	0	101	1297.31



Tank Adapters, CPVC New Style Standard with FKM Gaskets

Socket x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171V-002C	1/4	25	150	101	88.48
8171V-003C	3/8	25	200	101	88.48
8171V-005C	1/2	25	0	101	88.48
8171V-007C	3/4	25	0	101	101.80
8171V-010C	1	25	0	101	117.84
8171V-012C	1-1/4	20	0	101	144.79



Tank Adapters



Tank Adapters

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Tank Adapters, CPVC New Style Standard with FKM Gaskets

(continued)

Socket x Fipt

8171V-015C	1-1/2	20	0	101	150.94
8171V-020C	2	15	0	101	228.51
8171V-025C	2-1/2	4	0	101	328.94
8171V-030C	3	4	0	101	391.56
8171V-040C	4	2	0	101	867.27
8171V-060C	6	1	0	101	2179.57

Tank Adapters, CPVC New Style Special Reinforced (SR) Threaded with Neoprene Gaskets

Socket x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171-002CSR	1/4	25	150	101	61.14
8171-003CSR	3/8	25	200	101	61.14
8171-005CSR	1/2	25	0	101	61.14
8171-007CSR	3/4	25	0	101	73.18
8171-010CSR	1	25	0	101	82.78
8171-012CSR	1-1/4	20	0	101	106.78
8171-015CSR	1-1/2	20	0	101	119.87
8171-020CSR	2	15	0	101	165.77
8171-025CSR	2-1/2	4	0	101	252.17
8171-030CSR	3	4	0	101	300.14
8171-040CSR	4	2	0	101	482.36
8171-060CSR	6	1	0	101	1273.96

Tank Adapters, CPVC New Style Special Reinforced (SR) Threaded with EPDM Gaskets

Socket x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171E-002CSR	1/4	25	150	101	69.29
8171E-003CSR	3/8	25	200	101	69.29
8171E-005CSR	1/2	25	0	101	69.29
8171E-007CSR	3/4	25	0	101	78.32
8171E-010CSR	1	25	0	101	93.64
8171E-012CSR	1-1/4	20	0	101	117.03
8171E-015CSR	1-1/2	20	0	101	126.61
8171E-020CSR	2	15	0	101	178.99
8171E-025CSR	2-1/2	4	0	101	263.03
8171E-030CSR	3	4	0	101	313.13
8171E-040CSR	4	2	0	101	502.06
8171E-060CSR	6	2	0	101	1325.87

Tank Adapters, CPVC New Style Special Reinforced (SR) Threaded with FKM Gaskets

Socket x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171V-002CSR	1/4	25	150	101	90.28
8171V-003CSR	3/8	25	200	101	90.28

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Tank Adapters, CPVC New Style Special Reinforced (SR)

Threaded with FKM Gaskets (continued)

Socket x SR Fipt - Stainless Steel Collar

8171V-005CSR	1/2	25	0	101	90.28
8171V-007CSR	3/4	25	0	101	104.37
8171V-010CSR	1	25	0	101	121.41
8171V-012CSR	1-1/4	20	0	101	150.51
8171V-015CSR	1-1/2	20	0	101	160.72
8171V-020CSR	2	15	0	101	239.33
8171V-025CSR	2-1/2	4	0	101	352.67
8171V-030CSR	3	4	0	101	419.95
8171V-040CSR	4	2	0	101	896.68
8171V-060CSR	6	2	0	101	2213.88

Tank Adapters, CPVC New Style Standard with Neoprene Gaskets

Fipt x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172-002C	1/4	25	150	101	79.23
8172-003C	3/8	25	200	101	79.23
8172-005C	1/2	25	0	101	79.23
8172-007C	3/4	25	0	101	91.48
8172-010C	1	25	0	101	100.07
8172-012C	1-1/4	20	0	101	141.28
8172-015C	1-1/2	20	0	101	154.43
8172-020C	2	15	0	101	192.47
8172-025C	2-1/2	4	0	101	270.86
8172-030C	3	4	0	101	322.44
8172-040C	4	2	0	101	509.46
8172-060C	6	1	0	101	1415.25

Tank Adapters, CPVC New Style Standard with EPDM Gaskets

Fipt x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172E-002C	1/4	25	150	101	82.35
8172E-003C	3/8	25	200	101	82.35
8172E-005C	1/2	25	0	101	82.35
8172E-007C	3/4	25	0	101	97.08
8172E-010C	1	25	0	101	104.61
8172E-012C	1-1/4	20	0	101	146.97
8172E-015C	1-1/2	20	0	101	167.73
8172E-020C	2	15	0	101	207.29
8172E-025C	2-1/2	4	0	101	304.75
8172E-030C	3	4	0	101	362.83
8172E-040C	4	2	0	101	604.08
8172E-060C	6	1	0	101	1436.63



Tank Adapters

Tank Adapters

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Tank Adapters, CPVC New Style Standard with FKM Gaskets

Fipt x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172V-002C	1/4	25	150	101	127.42
8172V-003C	3/8	25	200	101	127.42
8172V-005C	1/2	25	0	101	127.42
8172V-007C	3/4	25	0	101	143.63
8172V-010C	1	25	0	101	165.28
8172V-012C	1-1/4	20	0	101	202.75
8172V-015C	1-1/2	20	0	101	209.78
8172V-020C	2	15	0	101	326.80
8172V-025C	2-1/2	4	0	101	463.76
8172V-030C	3	4	0	101	552.04
8172V-040C	4	2	0	101	1451.74
8172V-060C	6	1	0	101	2660.84



Tank Adapters, CPVC New Style Special Reinforced (SR) Threaded with Neoprene Gaskets

Fipt x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172-002CSR	1/4	25	150	101	80.99
8172-003CSR	3/8	25	200	101	80.99
8172-005CSR	1/2	25	0	101	80.99
8172-007CSR	3/4	25	0	101	94.05
8172-010CSR	1	25	0	101	103.63
8172-012CSR	1-1/4	20	0	101	147.01
8172-015CSR	1-1/2	20	0	101	164.24
8172-020CSR	2	15	0	101	203.07
8172-025CSR	2-1/2	4	0	101	294.72
8172-030CSR	3	4	0	101	350.86
8172-040CSR	4	2	0	101	538.89
8172-060CSR	6	2	0	101	1443.78



Tank Adapters, CPVC New Style Special Reinforced (SR) Threaded with EPDM Gaskets

Fipt x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172E-002CSR	1/4	25	150	101	84.17
8172E-003CSR	3/8	25	200	101	84.17
8172E-005CSR	1/2	25	0	101	84.17
8172E-007CSR	3/4	25	0	101	99.65
8172E-010CSR	1	25	0	101	108.19
8172E-012CSR	1-1/4	20	0	101	152.71
8172E-015CSR	1-1/2	20	0	101	177.53
8172E-020CSR	2	15	0	101	217.89
8172E-025CSR	2-1/2	4	0	101	328.71
8172E-030CSR	3	4	0	101	391.33
8172E-040CSR	4	2	0	101	633.51



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Tank Adapters, CPVC New Style Special Reinforced (SR) Threaded with EPDM Gaskets (continued)

Fipt x SR Fipt - Stainless Steel Collar

8172E-060CSR	6	1	0	101	1465.14
--------------	---	---	---	-----	---------

Tank Adapters, CPVC New Style Special Reinforced (SR) Threaded with FKM Gaskets

Fipt x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172V-002CSR	1/4	25	150	101	129.23
8172V-003CSR	3/8	25	200	101	129.23
8172V-005CSR	1/2	25	0	101	129.23
8172V-007CSR	3/4	25	0	101	146.20
8172V-010CSR	1	25	0	101	168.85
8172V-012CSR	1-1/4	20	0	101	208.47
8172V-015CSR	1-1/2	20	0	101	219.56
8172V-020CSR	2	15	0	101	337.44
8172V-025CSR	2-1/2	4	0	101	487.58
8172V-030CSR	3	4	0	101	580.45
8172V-040CSR	4	2	0	101	1481.17
8172V-060CSR	6	2	0	101	2689.40



Tank Adapter, CPVC Self Aligning with Neoprene Gasket

Fipt

75 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172SA-010C	1	5	0	101	259.43
8172SA-020C	2	4	0	101	391.56
8172SA-030C	3	2	0	101	610.13



Tank Adapter, CPVC Self Aligning with EPDM Gasket

Fipt

75 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172ESA-010C	1	5	0	101	272.75
8172ESA-020C	2	4	0	101	413.05
8172ESA-030C	3	2	0	101	642.44



Tank Adapter, CPVC Self Aligning with FKM Gasket

Fipt

75 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172VSA-010C	1	5	0	101	539.07
8172VSA-020C	2	4	0	101	815.97
8172VSA-030C	3	2	0	101	1267.79



Tank Adapters



Tank Adapters

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Tank Adapter, CPVC Old Style with Neoprene Gasket

Socket x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

871-005C	1/2	25	0	101	59.34
871-007C	3/4	25	0	101	70.59
871-010C	1	25	0	101	79.23
871-012C	1-1/4	20	0	101	101.05
871-015C	1-1/2	20	0	101	110.04
871-020C	2	15	0	101	155.34
871-030C	3	4	0	101	271.75
871-040C	4	2	0	101	452.87



Tank Adapter, CPVC Old Style with Neoprene Gasket

Fipt x Fipt

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

872-005C	1/2	25	0	101	79.23
872-007C	3/4	25	0	101	91.48
872-010C	1	25	0	101	100.07
872-012C	1-1/4	20	0	101	141.28
872-015C	1-1/2	20	0	101	154.43
872-020C	2	15	0	101	192.47
872-030C	3	4	0	101	322.44
872-040C	4	2	0	101	509.46



Tank Adapter Gasket Only - Neoprene (New Style)

3N-002	1/4	100	0	299	3.33
3N-003	3/8	50	0	299	3.33
3N-005	1/2	10	0	299	3.33
3N-007	3/4	10	0	299	3.57
3N-010	1	10	0	299	3.79
3N-012	1-1/4	10	0	299	5.24
3N-015	1-1/2	10	0	299	6.15
3N-020	2	10	0	299	8.05
3N-025	2-1/2	10	0	299	8.40
3N-030	3	10	0	299	8.78
3N-040	4	50	0	299	24.24
2N-060	6	10	0	299	30.29
3N-080	8	10	0	299	138.91



Tank Adapter Gasket Only - EPDM (New Style)

3E-002	1/4	10	0	299	2.06
3E-003	3/8	10	0	299	2.36



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Tank Adapter Gasket Only - EPDM (New Style) (continued)

3E-005	1/2	10	0	299	3.16
3E-007	3/4	10	0	299	3.34
3E-010	1	10	0	299	4.82
3E-012	1-1/4	10	0	299	10.14
3E-015	1-1/2	10	0	299	10.41
3E-020	2	10	0	299	11.93
3E-025	2-1/2	10	0	299	16.88
3E-030	3	10	0	299	18.16
3E-040	4	10	0	299	27.35
2E-060	6	10	0	299	49.39
3E-080	8	10	0	299	130.55



Tank Adapter Gasket Only - FKM (New Style)

3V-002	1/4	10	0	299	12.61
3V-003	3/8	10	0	299	16.03
3V-005	1/2	10	0	299	20.40
3V-007	3/4	10	0	299	22.61
3V-010	1	10	0	299	24.69
3V-012	1-1/4	10	0	299	46.22
3V-015	1-1/2	10	0	299	49.60
3V-020	2	10	0	299	63.92
3V-025	2-1/2	10	0	299	77.88
3V-030	3	10	0	299	140.46
3V-040	4	10	0	299	174.93
2V-060	6	10	0	299	617.48
3V-080	8	10	0	299	993.78




Tank Adapter Gasket Only - Neoprene (Old Style)

2N-005	1/2	10	0	299	3.33
2N-007	3/4	10	0	299	3.57
2N-010	1	10	0	299	3.79
2N-015	1-1/4 OR 1-1/2	10	0	299	6.15
2N-020	2	10	0	299	8.05
2N-030	3	10	0	299	8.78
2N-040	4	10	0	299	24.24



Tank Adapter Gasket Only - EPDM (Old Style)

2E-005	1/2	10	0	299	3.86
2E-007	3/4	10	0	299	3.99
2E-010	1	10	0	299	6.93
2E-015	1-1/4 OR 1-1/2	10	0	299	10.41
2E-020	2	10	0	299	11.93
2E-030	3	10	0	299	18.16
2E-040	4	10	0	299	27.35





Schedule 80 CPVC Product
Tank Adapters & Pipe Flanges

Tank Adapters

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Tank Adapter Wrench Sets (New Style)

Body Wrench & Nut Wrench



TAW-002	1/4	1	25	299	26.87
TAW-003	3/8	1	25	299	26.87
TAW-005	1/2	1	25	299	26.87
TAW-007	3/4	1	25	299	27.40
TAW-010	1	1	25	299	28.49
TAW-012	1-1/4	1	20	299	32.15
TAW-015	1-1/2	1	20	299	34.86
TAW-020	2	1	10	299	39.72
TAW-025	2-1/2	1	10	299	43.94
TAW-030	3	1	10	299	48.43
TAW-040	4	1	10	299	51.87

Tank Adapter Individual Body Wrench (New Style)



TAW1-002	1/4	500	0	299	15.08
TAW1-003	3/8	400	0	299	15.08
TAW1-005	1/2	250	0	299	15.08
TAW1-007	3/4	220	0	299	15.37
TAW1-010	1	200	0	299	16.00
TAW1-012	1-1/4	300	0	299	18.13
TAW1-015	1-1/2	150	0	299	19.52
TAW1-020	2	100	0	299	21.19
TAW1-025	2-1/2	80	0	299	22.14
TAW1-030	3	74	0	299	27.76
TAW1-040	4	35	0	299	28.56

Tank Adapter Individual Nut Wrench (New Style)



TAW2-002	1/4	300	0	299	15.08
TAW2-003	3/8	250	0	299	15.08
TAW2-005	1/2	200	0	299	15.08
TAW2-007	3/4	160	0	299	15.37
TAW2-010	1	110	0	299	16.00
TAW2-012	1-1/4	200	0	299	18.13
TAW2-015	1-1/2	120	0	299	19.52
TAW2-020	2	100	0	299	21.19
TAW2-025	2-1/2	50	0	299	22.14
TAW2-030	3	40	0	299	27.76
TAW2-040	4	35	0	299	28.56

Pipe Flanges

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Flange One Piece

Socket



150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

851-005C	1/2	25	0	090	32.99
851-007C	3/4	25	0	090	33.75
851-010C	1	15	0	090	36.85
851-012C	1-1/4	15	0	090	44.99
851-015C	1-1/2	20	0	090	49.93
851-020C	2	10	0	090	60.44
851-025C	2-1/2	10	0	090	125.24
851-030C	3	10	0	090	130.96
851-040C	4	5	0	090	176.94
851-050C	5	5	0	090	324.26
851-060C	6	5	0	090	301.42
851-080C	8	2	0	090	905.88
851-100C	10	2	0	091	1129.03
851-100CF	10	1	2	097	1956.58
851-120C	12	2	0	091	1585.91
851-120CF	12	1	0	097	2935.83

Flange One Piece

Fipt



150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

852-005C	1/2	25	0	090	46.13
852-007C	3/4	25	0	090	55.93
852-010C	1	15	0	090	61.03
852-012C	1-1/4	15	0	090	84.69
852-015C	1-1/2	20	0	090	89.66
852-020C	2	10	0	090	91.31
852-025C	2-1/2	10	0	090	148.21
852-030C	3	10	0	090	147.06
852-040C	4	5	0	090	228.62
852-060CF	6	1	8	097	341.57
852-080CF	8	1	2	097	846.09

Flange - Special Reinforced One Piece Threaded

SR Fipt - Stainless Steel Collar



150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

852-005CSR	1/2	25	0	096	25.35
852-007CSR	3/4	25	0	096	30.76
852-010CSR	1	15	0	096	33.65
852-012CSR	1-1/4	15	0	096	46.57
852-015CSR	1-1/2	15	0	096	49.38
852-020CSR	2	10	0	096	50.57
852-025CSR	2-1/2	10	0	096	81.36
852-030CSR	3	10	0	096	80.73