

Valves Product

Industrial Swing Check Valves & Industrial Swing Check Valve Accessory and Repair Kits & Utility Swing Check Valves



Industrial Swing Check Valves

Industrial Swing Check Valve With Counter Balance

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
<b>PP</b>					
3/4	4423CB-007P 885.22	4433CB-007P 983.55	1	12	113
1	4423CB-010P 1058.97	4433CB-010P 1154.15	1	4	113
1-1/4	4423CB-012P 1080.58	4433CB-012P 1662.79	1	0	113
1-1/2	4423CB-015P 1527.39	4433CB-015P 2050.93	1	0	113
2	4423CB-020P 1645.41	4433CB-020P 1848.75	1	0	113
2-1/2	4423CB-025P 2540.24	4433CB-025P 3120.49	1	0	112
3	4423CB-030P 3090.74	4433CB-030P 3866.98	1	0	112
4	4423CB-040P 3539.35	4433CB-040P 3888.24	1	0	112
6	4423CB-060P 6585.04	4433CB-060P 8450.29	1	0	112
8	4423CB-080P 12021.60	4433CB-080P 13145.62	1	0	112

Industrial Swing Check Valve Accessory and Repair Kits

Repair Kits include:

- 1-Bonnet O-ring
- 1-Disc O-ring
- 1-Seat O-ring

- 1-Plug O-ring
- 1-Arm Plug O-ring

Industrial Swing Check Valve Repair Kits

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
3/4	SK-ERK-007 32.27	SK-VRK-007 39.36	1	10	299
1	SK-ERK-010 42.16	SK-VRK-010 51.41	1	10	299
1-1/2 & 1-1/4	SK-ERK-015 100.81	SK-VRK-015 127.49	1	10	299
2	SK-ERK-020 108.22	SK-VRK-020 131.96	1	10	299
2-1/2	SK-ERK-025 114.45	SK-VRK-025 146.48	1	10	299
3	SK-ERK-030 129.76	SK-VRK-030 158.35	1	10	299
4	SK-ERK-040 141.59	SK-VRK-040 172.64	1	10	299
6	SK-ERK-060 281.40	SK-VRK-060 332.19	1	10	299
8	SK-ERK-080 354.07	SK-VRK-080 429.54	1	10	299

Utility Swing Check Valves



Pressure Rating @ 73°F (23°C),  
Water

1/2" - 4" Full Flow (open) 150 psi  
Back Pressure (closed) 75 psi  
6" - 8" Full Flow (open) 100 psi  
Back Pressure (closed) 50 psi

Maximum Service Temperature  
140°F (60°C)

Temperature/Pressure De-ratings  
Apply  
EPDM Seat

General Installation Information: Swing check valves are designed for horizontal installations, but may be installed in an up-flow only vertical position. Check valves MUST be installed with the valve's FLOW arrow pointing in the direction of the flow. Do not install valve upside down. Flow velocity should not exceed 5 ft./sec. Minimum opening pressure less than 0.5 psi.

PVC White Swing Check

Size	Socket	Thread	SR Threaded	Std Pk	Mstr Pk	Prod Code
1/2	S1520-05 20.47	S1520-05F 20.47	S1520-05FSR 23.88	35	0	026
3/4	S1520-07 21.14	S1520-07F 21.14	S1520-07FSR 25.99	35	0	026
1	S1520-10 22.02	S1520-10F 22.02	S1520-10FSR 28.79	20	0	026
1-1/4	S1520-12 22.87	S1520-12F 22.87	S1520-12FSR 33.74	12	0	026
1-1/2	S1520-15 24.24	S1520-15F 24.24	S1520-15FSR 42.79	12	0	026
2	S1520-20 37.63	S1520-20F 37.63	S1520-20FSR 57.77	15	0	026
2-1/2	S1520-25 62.59	S1520-25F 62.59	S1520-25FSR 82.74	5	0	026
3	S1520-30 69.56	S1520-30F 69.56	S1520-30FSR 123.38	4	0	026
4	S1520-40 98.48	S1520-40F 98.48	S1520-40FSR 154.25	2	0	026
6	S1520-60 206.95	S1520-60F 206.95	S1520-60FSR 272.97	1	0	026
8	S1520-80 384.44	---	---	1	0	026

PVC Clear Swing Check

Size	Socket	Thread	SR Threaded	Std Pk	Mstr Pk	Prod Code
1/2	S1520C05 27.84	S1520C05F 27.84	S1520C05FSR 31.24	35	0	026
3/4	S1520C07 28.40	S1520C07F 28.40	S1520C07FSR 33.29	35	0	026
1	S1520C10 28.94	S1520C10F 28.94	S1520C10FSR 35.72	20	0	026
1-1/4	S1520C12 30.38	S1520C12F 30.38	S1520C12FSR 41.22	12	0	026
1-1/2	S1520C15 33.02	S1520C15F 33.02	S1520C15FSR 51.60	12	0	026
2	S1520C20 47.55	S1520C20F 47.55	S1520C20FSR 67.66	15	0	026



**Valves Product**  
**Utility Swing Check Valves & True Union Utility Swing Check Valves & Compression Utility Swing Check Valves**

**Utility Swing Check Valves**

**PVC Clear Swing Check (continued)**

Size	Socket	Thread	SR Threaded	Std Pk	Mstr Pk	Prod Code
2-1/2	S1520C25 79.24	S1520C25F 79.24	S1520C25FSR 110.46	5	0	026
3	S1520C30 88.04	S1520C30F 88.04	S1520C30FSR 141.85	4	0	026
4	S1520C40 118.53	S1520C40F 118.53	S1520C40FSR 174.25	2	0	026
6	S1520C60 244.97	S1520C60F 244.97	S1520C60FSR 310.99	1	0	026
8	S1520C80 409.19	---	---	1	0	026

**True Union Utility Swing Check Valves**



Pressure Rating @ 73°F (23°C),  
 Water  
 Full Flow (open) 150 psi  
 Back Pressure (closed) 75 psi

Maximum Service Temperature  
 140°F (60°C)

Temperature/Pressure De-ratings Apply  
 EPDM Seat

**General Installation Information:** Swing check valves are designed for horizontal installations, but may be installed in an up-flow only vertical position. Check valves MUST be installed with the valve's FLOW arrow pointing in the direction of the flow. Do not install valve upside down. Flow velocity should not exceed 5 ft./sec. Minimum opening pressure less than 0.5 psi.

**PVC White True Union Swing Check**

Size	Socket	Threaded	SR Thread	Std Pk	Mstr Pk	Prod Code
1/2	S1720-05 23.29	S1720-05F 23.29	S1720-05FSR 26.67	35	0	026
3/4	S1720-07 24.00	S1720-07F 24.00	S1720-07FSR 28.89	30	0	026
1	S1720-10 25.01	S1720-10F 25.01	S1720-10FSR 31.78	18	0	026
1-1/4	S1720-12 26.33	S1720-12F 26.33	S1720-12FSR 37.17	12	0	026
1-1/2	S1720-15 28.94	S1720-15F 28.94	S1720-15FSR 47.53	10	0	026
2	S1720-20 43.46	S1720-20F 43.46	S1720-20FSR 63.53	10	0	026
2-1/2	S1720-25 72.48	S1720-25F 72.48	S1720-25FSR 103.66	2	0	026
3	S1720-30 92.56	S1720-30F 92.56	S1720-30FSR 146.39	2	0	026
4	S1720-40 124.93	S1720-40F 124.93	S1720-40FSR 180.14	1	0	026

**PVC Clear True Union Swing Check**

Size	Socket	Threaded	SR Thread	Std Pk	Mstr Pk	Prod Code
1/2	S1720C05 30.16	S1720C05F 30.16	S1720C05FSR 33.55	35	0	026
3/4	S1720C07 30.66	S1720C07F 30.66	S1720C07FSR 35.55	30	0	026
1	S1720C10 33.51	S1720C10F 33.51	S1720C10FSR 40.27	18	0	026
1-1/4	S1720C12 35.29	S1720C12F 35.29	S1720C12FSR 46.13	12	0	026
1-1/2	S1720C15 37.85	S1720C15F 37.85	S1720C15FSR 56.43	10	0	026
2	S1720C20 53.24	S1720C20F 53.24	S1720C20FSR 73.40	10	0	026
2-1/2	S1720C25 87.44	S1720C25F 87.44	S1720C25FSR 118.65	2	0	026
3	S1720C30 100.63	S1720C30F 100.63	S1720C30FSR 154.45	2	0	026
4	S1720C40 134.17	S1720C40F 134.17	S1720C40FSR 189.86	1	0	026

**Compression Utility Swing Check Valves**



Pressure Rating @ 73°F (23°C), Water  
 Full Flow (open) 150 psi  
 Back Pressure (closed) 75 psi

Maximum Service Temperature  
 140°F (60°C)

Temperature/Pressure De-ratings Apply

- Standard Swing Check Assembly Maintains a Positive Seal
- Convenient Compression Ends for Quick Connections
- Engineered for Maximum Flow, Quick Response & Positive Shutoff
- Excellent for Pool & Spa, OEM and General Purpose Applications
- Compact, Space-Saving Design
- Replaceable PVC White or Clear Sealed Unit
- High Grade EPDM Seat
- Suitable for Horizontal or Vertical Up-flow Installations
- Pressure Rated to 150 psi @ 73°F Full Flow (open), 75 psi Back Pressure (closed)
- Maximum Service Temperature 140°F (temperature/pressure de-ratings apply)

**General Installation Information:** Swing check valves are designed for horizontal installations, but may be installed in up-flow only vertical position. Check valves MUST be installed with the valve's FLOW arrow pointing in the direction of the flow. Do not install valve upside down. Flow velocity should not exceed 5 ft./sec. Minimum opening pressure less than 0.5 psi.

**PVC White Compression End Swing Check**

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
<b>Compression End</b>					
S1500-05	1/2	20	0	026	27.22
S1500-07	3/4	35	0	026	28.64
S1500-10	1	20	0	026	29.85