

Valves Product

Industrial Swing Check Valves & Industrial Swing Check Valve Accessory and Repair Kits & Utility Swing Check Valves



Industrial Swing Check Valves

Industrial Swing Check Valve With Counter Balance

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
PP					
3/4	4423CB-007P 885.22	4433CB-007P 983.55	1	12	113
1	4423CB-010P 1058.97	4433CB-010P 1154.15	1	4	113
1-1/4	4423CB-012P 1080.58	4433CB-012P 1662.79	1	0	113
1-1/2	4423CB-015P 1527.39	4433CB-015P 2050.93	1	0	113
2	4423CB-020P 1645.41	4433CB-020P 1848.75	1	0	113
2-1/2	4423CB-025P 2540.24	4433CB-025P 3120.49	1	0	112
3	4423CB-030P 3090.74	4433CB-030P 3866.98	1	0	112
4	4423CB-040P 3539.35	4433CB-040P 3888.24	1	0	112
6	4423CB-060P 6585.04	4433CB-060P 8450.29	1	0	112
8	4423CB-080P 12021.60	4433CB-080P 13145.62	1	0	112

Industrial Swing Check Valve Accessory and Repair Kits

Repair Kits include:

- 1-Bonnet O-ring
- 1-Disc O-ring
- 1-Seat O-ring

- 1-Plug O-ring
- 1-Arm Plug O-ring

Industrial Swing Check Valve Repair Kits

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
3/4	SK-ERK-007 32.27	SK-VRK-007 39.36	1	10	299
1	SK-ERK-010 42.16	SK-VRK-010 51.41	1	10	299
1-1/2 & 1-1/4	SK-ERK-015 100.81	SK-VRK-015 127.49	1	10	299
2	SK-ERK-020 108.22	SK-VRK-020 131.96	1	10	299
2-1/2	SK-ERK-025 114.45	SK-VRK-025 146.48	1	10	299
3	SK-ERK-030 129.76	SK-VRK-030 158.35	1	10	299
4	SK-ERK-040 141.59	SK-VRK-040 172.64	1	10	299
6	SK-ERK-060 281.40	SK-VRK-060 332.19	1	10	299
8	SK-ERK-080 354.07	SK-VRK-080 429.54	1	10	299

Utility Swing Check Valves



Pressure Rating @ 73°F (23°C),
Water

1/2" - 4" Full Flow (open) 150 psi
Back Pressure (closed) 75 psi
6" - 8" Full Flow (open) 100 psi
Back Pressure (closed) 50 psi

Maximum Service Temperature
140°F (60°C)

Temperature/Pressure De-ratings
Apply
EPDM Seat

General Installation Information: Swing check valves are designed for horizontal installations, but may be installed in an up-flow only vertical position. Check valves MUST be installed with the valve's FLOW arrow pointing in the direction of the flow. Do not install valve upside down. Flow velocity should not exceed 5 ft./sec. Minimum opening pressure less than 0.5 psi.

PVC White Swing Check

Size	Socket	Thread	SR Threaded	Std Pk	Mstr Pk	Prod Code
1/2	S1520-05 20.47	S1520-05F 20.47	S1520-05FSR 23.88	35	0	026
3/4	S1520-07 21.14	S1520-07F 21.14	S1520-07FSR 25.99	35	0	026
1	S1520-10 22.02	S1520-10F 22.02	S1520-10FSR 28.79	20	0	026
1-1/4	S1520-12 22.87	S1520-12F 22.87	S1520-12FSR 33.74	12	0	026
1-1/2	S1520-15 24.24	S1520-15F 24.24	S1520-15FSR 42.79	12	0	026
2	S1520-20 37.63	S1520-20F 37.63	S1520-20FSR 57.77	15	0	026
2-1/2	S1520-25 62.59	S1520-25F 62.59	S1520-25FSR 82.74	5	0	026
3	S1520-30 69.56	S1520-30F 69.56	S1520-30FSR 123.38	4	0	026
4	S1520-40 98.48	S1520-40F 98.48	S1520-40FSR 154.25	2	0	026
6	S1520-60 206.95	S1520-60F 206.95	S1520-60FSR 272.97	1	0	026
8	S1520-80 384.44	---	---	1	0	026

PVC Clear Swing Check

Size	Socket	Thread	SR Threaded	Std Pk	Mstr Pk	Prod Code
1/2	S1520C05 27.84	S1520C05F 27.84	S1520C05FSR 31.24	35	0	026
3/4	S1520C07 28.40	S1520C07F 28.40	S1520C07FSR 33.29	35	0	026
1	S1520C10 28.94	S1520C10F 28.94	S1520C10FSR 35.72	20	0	026
1-1/4	S1520C12 30.38	S1520C12F 30.38	S1520C12FSR 41.22	12	0	026
1-1/2	S1520C15 33.02	S1520C15F 33.02	S1520C15FSR 51.60	12	0	026
2	S1520C20 47.55	S1520C20F 47.55	S1520C20FSR 67.66	15	0	026