

Valves Product Globe Valves



Pressure Rating @ 73°F (23°C), Water
150 psi

Maximum Service Temperature
PVC = 140°F (60°C)
CPVC = 200°F (93°C)

Temperature/Pressure De-ratings Apply

All Valves Assembled with Silicone-Free,
Water Soluble Lubricant
Suitable for Vacuum Service

Internal Repair Kit includes 1-Bonnet O-ring along with a factory assembled (required) internal component replacement unit consisting of Bonnet assembled with Stem/O-rings, Seat & Seal Carrier components. Install in valve using existing valve Bolts/Nuts/Washers, and Handle/Nut.

PVC Internal Repair Kit

Size	Buna-N	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
2-1/2	GL-BRK-025 248.43	GL-ERK-025 600.87	GL-VRK-025 668.33	1	0	299
3	GL-BRK-030 276.86	GL-ERK-030 665.76	GL-VRK-030 742.07	1	0	299
4	GL-BRK-040 324.84	GL-ERK-040 780.73	GL-VRK-040 858.38	1	0	299
6	GL-BRK-060 707.78	GL-ERK-060 1199.71	GL-VRK-060 1224.24	1	0	299

CPVC Internal Repair Kits

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
2-1/2	GL-ERK-025C 846.12	GL-VRK-025C 940.15	1	0	299
3	GL-ERK-030C 967.93	GL-VRK-030C 1062.92	1	0	299
4	GL-ERK-040C 1097.53	GL-VRK-040C 1207.85	1	0	299
6	GL-ERK-060C 1567.59	GL-VRK-060C 1724.97	1	0	299

PVC Flanged Ends

Size	Buna-N	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
2-1/2	6013-025 746.79	6023-025 790.33	6033-025 851.41	1	0	620
3	6013-030 856.05	6023-030 893.97	6033-030 994.87	1	0	620
4	6013-040 971.18	6023-040 1161.00	6033-040 1275.72	1	0	620
6	6013-060 1493.61	6023-060 1785.99	6033-060 1821.59	1	0	620

CPVC Flanged Ends

Size	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
2-1/2	6023-025C 1198.27	6033-025C 1258.48	1	0	622
3	6023-030C 1257.89	6033-030C 1398.36	1	0	622
4	6023-040C 1633.72	6033-040C 1795.92	1	0	622
6	6023-060C 2543.77	6033-060C 2565.27	1	0	622