



Valves Product Gate Valves

Gate Valves



1/2" - 2"
Socket/Threaded Style

2-1/2" - 3" Socket Style

4" Socket Style

Pressure Rating @ 73°F
(23°C), Water
1/2" - 2" 200 psi
2-1/2" - 3" 150 psi
4" 235 psi
Flanged 150 psi

Maximum Service
Temperature
PVC = 140°F (60°C)
CPVC = 200°F (93°C)
Temperature/Pressure
De-ratings Apply

CPVC Gate-Wedge on
CPVC Valve
All Valves Assembled with
Silicone-Free,
Water Soluble Lubricant
See Gate Valve
Accessories & Repair Kits
Section for Additional
Options and Features

PVC

Size	Buna-N	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	--------	------	-----	--------	---------	-----------

Threaded Ends

1/2	2011-005 29.69	2021-005 32.60	2031-005 35.91	12	0	200
3/4	2011-007 36.33	2021-007 39.97	2031-007 42.07	12	0	200
1	2011-010 43.04	2021-010 47.40	2031-010 52.20	12	0	200
1-1/4	2011-012 59.53	2021-012 65.51	2031-012 72.01	6	0	200
1-1/2	2011-015 75.96	2021-015 84.39	2031-015 91.88	6	0	200
2	2011-020 97.54	2021-020 107.39	2031-020 118.06	6	0	200
2-1/2	2011-025 539.32	2021-025 593.23	2031-025 652.59	1	0	201

SR Threaded Ends

3	2011-030SR 539.32	2021-030SR 593.23	2031-030SR 652.59	1	0	201
4	2011-040SR 1058.36	2021-040SR 1175.97	2031-040SR 1293.52	1	0	201

Socket Ends

1/2	2012-005 29.69	2022-005 32.60	2032-005 35.91	12	0	200
3/4	2012-007 36.33	2022-007 39.97	2032-007 42.07	12	0	200
1	2012-010 43.04	2022-010 47.40	2032-010 52.20	12	0	200

PVC (continued)

Size	Buna-N	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	--------	------	-----	--------	---------	-----------

Socket Ends

1-1/4	2012-012 59.53	2022-012 65.51	2032-012 72.01	6	0	200
1-1/2	2012-015 75.96	2022-015 84.39	2032-015 91.88	6	0	200
2	2012-020 97.54	2022-020 107.39	2032-020 118.06	6	0	200
2-1/2	2012-025 539.32	2022-025 593.23	2032-025 652.59	1	0	201
3	2012-030 539.32	2022-030 593.23	2032-030 652.59	1	0	201
4	2012-040 1058.36	2022-040 1175.97	2032-040 1293.52	1	0	201

Flanged Ends

1/2	2013-005 143.80	2023-005 163.07	2033-005 186.89	4	0	200
3/4	2013-007 161.81	2023-007 183.11	2033-007 208.92	4	0	200
1	2013-010 177.68	2023-010 200.71	2033-010 230.52	4	0	200
1-1/4	2013-012 200.14	2023-012 229.77	2033-012 272.69	3	0	200
1-1/2	2013-015 233.60	2023-015 266.65	2033-015 313.27	3	0	200
2	2013-020 300.68	2023-020 315.93	2033-020 338.20	2	0	200
2-1/2	2013-025 674.12	2023-025 902.59	2033-025 992.83	1	0	201
3	2013-030 674.12	2023-030 902.59	2033-030 992.83	1	0	201
4	2013-040 1326.92	2023-040 1474.43	2033-040 1621.87	1	0	201

CPVC

Size	Buna-N	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	--------	------	-----	--------	---------	-----------

Threaded Ends

1/2	2011-005C 86.93	2021-005C 96.55	2031-005C 106.24	12	0	202
3/4	2011-007C 93.99	2021-007C 104.41	2031-007C 114.86	12	0	202
1	2011-010C 103.03	2021-010C 114.49	2031-010C 125.89	12	0	202
1-1/4	2011-012C 180.97	2021-012C 201.08	2031-012C 221.20	6	0	202
1-1/2	2011-015C 197.81	2021-015C 220.40	2031-015C 242.44	6	0	202
2	2011-020C 228.84	2021-020C 254.22	2031-020C 279.64	6	0	202
2-1/2	2011-025C 852.09	2021-025C 919.51	2031-025C 998.46	1	0	203

SR Threaded Ends

3	2011-030CSR 1144.09	2021-030CSR 1270.87	2031-030CSR 1412.08	1	0	203
4	2011-040CSR 2059.34	2021-040CSR 2288.12	2031-040CSR 2542.35	1	0	203

Socket Ends

1/2	2012-005C 86.93	2022-005C 96.55	2032-005C 106.24	12	0	202
3/4	2012-007C 93.99	2022-007C 104.41	2032-007C 114.86	12	0	202

Valves Product
Gate Valves & Plug Gate Valves



Gate Valves

CPVC (continued)

Size	Buna-N	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
------	--------	------	-----	--------	---------	-----------

Socket Ends

1	2012-010C 103.03	2022-010C 114.49	2032-010C 125.89	12	0	202
1-1/4	2012-012C 180.97	2022-012C 201.08	2032-012C 221.20	6	0	202
1-1/2	2012-015C 197.81	2022-015C 220.40	2032-015C 242.44	6	0	202
2	2012-020C 228.84	2022-020C 254.22	2032-020C 279.64	6	0	202
2-1/2	2012-025C 852.09	2022-025C 919.51	2032-025C 998.46	1	0	203
3	2012-030C 1144.09	2022-030C 1270.87	2032-030C 1412.08	1	0	203
4	2012-040C 2059.34	2022-040C 2288.12	2032-040C 2542.35	1	0	203

Flanged Ends

1/2	2013-005C 389.48	2023-005C 432.69	2033-005C 475.93	4	0	202
3/4	2013-007C 421.07	2023-007C 467.80	2033-007C 514.60	4	0	202
1	2013-010C 461.45	2023-010C 512.83	2033-010C 564.08	4	0	202
1-1/4	2013-012C 624.13	2023-012C 693.76	2033-012C 763.14	3	0	202
1-1/2	2013-015C 681.68	2023-015C 760.39	2033-015C 836.33	3	0	202
2	2013-020C 789.40	2023-020C 877.08	2033-020C 964.82	2	0	202
2-1/2	2013-025C 1031.38	2023-025C 1362.96	2033-025C 1529.00	1	0	203
3	2013-030C 1430.08	2023-030C 1588.99	2033-030C 1765.56	1	0	203
4	2013-040C 2574.16	2023-040C 2860.18	2033-040C 3177.99	1	0	203

Plug Gate Valves



Pressure Rating @ 73°F (23°C), Water
1/2" - 2" 235 psi
Flanged 150 psi

Maximum Service Temperature
PVC = 140°F (60°C)
CPVC = 200°F (93°C)

Temperature/Pressure De-ratings Apply

Plug-Style PE Wedge on All Valves
Rated for Vacuum Service

All Valves Assembled with Silicone-Free,
Water Soluble Lubricants

PVC Socket Ends

Size	Buna-N	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
1/2	5212-005 29.69	5222-005 32.60	5232-005 35.91	12	0	200
3/4	5212-007 36.33	5222-007 39.97	5232-007 42.07	12	0	200
1	5212-010 43.04	5222-010 47.40	5232-010 52.20	12	0	200
1-1/4	5212-012 59.53	5222-012 65.51	5232-012 72.01	6	0	200
1-1/2	5212-015 75.96	5222-015 84.39	5232-015 91.88	6	0	200
2	5212-020 97.54	5222-020 107.39	5232-020 118.06	6	0	200

PVC SR Threaded Ends

Size	Buna-N	EPDM	FKM	Std Pk	Mstr Pk	Prod Code
1/2	5211-005SR 33.05	5221-005SR 35.98	5231-005SR 39.22	12	0	200
3/4	5211-007SR 41.17	5221-007SR 44.82	5231-007SR 46.93	12	0	200
1	5211-010SR 49.73	5221-010SR 54.09	5231-010SR 58.86	12	0	200