



Valves Product
Utility Swing Check Valves & True Union Utility Swing Check Valves & Compression Utility Swing Check Valves

Utility Swing Check Valves

PVC Clear Swing Check (continued)

Size	Socket	Thread	SR Threaded	Std Pk	Mstr Pk	Prod Code
2-1/2	S1520C25 79.24	S1520C25F 79.24	S1520C25FSR 110.46	5	0	026
3	S1520C30 88.04	S1520C30F 88.04	S1520C30FSR 141.85	4	0	026
4	S1520C40 118.53	S1520C40F 118.53	S1520C40FSR 174.25	2	0	026
6	S1520C60 244.97	S1520C60F 244.97	S1520C60FSR 310.99	1	0	026
8	S1520C80 409.19	---	---	1	0	026

True Union Utility Swing Check Valves



Pressure Rating @ 73°F (23°C),
 Water
 Full Flow (open) 150 psi
 Back Pressure (closed) 75 psi

Maximum Service Temperature
 140°F (60°C)

Temperature/Pressure De-ratings Apply
 EPDM Seat

General Installation Information: Swing check valves are designed for horizontal installations, but may be installed in an up-flow only vertical position. Check valves MUST be installed with the valve's FLOW arrow pointing in the direction of the flow. Do not install valve upside down. Flow velocity should not exceed 5 ft./sec. Minimum opening pressure less than 0.5 psi.

PVC White True Union Swing Check

Size	Socket	Threaded	SR Thread	Std Pk	Mstr Pk	Prod Code
1/2	S1720-05 23.29	S1720-05F 23.29	S1720-05FSR 26.67	35	0	026
3/4	S1720-07 24.00	S1720-07F 24.00	S1720-07FSR 28.89	30	0	026
1	S1720-10 25.01	S1720-10F 25.01	S1720-10FSR 31.78	18	0	026
1-1/4	S1720-12 26.33	S1720-12F 26.33	S1720-12FSR 37.17	12	0	026
1-1/2	S1720-15 28.94	S1720-15F 28.94	S1720-15FSR 47.53	10	0	026
2	S1720-20 43.46	S1720-20F 43.46	S1720-20FSR 63.53	10	0	026
2-1/2	S1720-25 72.48	S1720-25F 72.48	S1720-25FSR 103.66	2	0	026
3	S1720-30 92.56	S1720-30F 92.56	S1720-30FSR 146.39	2	0	026
4	S1720-40 124.93	S1720-40F 124.93	S1720-40FSR 180.14	1	0	026

PVC Clear True Union Swing Check

Size	Socket	Threaded	SR Thread	Std Pk	Mstr Pk	Prod Code
1/2	S1720C05 30.16	S1720C05F 30.16	S1720C05FSR 33.55	35	0	026
3/4	S1720C07 30.66	S1720C07F 30.66	S1720C07FSR 35.55	30	0	026
1	S1720C10 33.51	S1720C10F 33.51	S1720C10FSR 40.27	18	0	026
1-1/4	S1720C12 35.29	S1720C12F 35.29	S1720C12FSR 46.13	12	0	026
1-1/2	S1720C15 37.85	S1720C15F 37.85	S1720C15FSR 56.43	10	0	026
2	S1720C20 53.24	S1720C20F 53.24	S1720C20FSR 73.40	10	0	026
2-1/2	S1720C25 87.44	S1720C25F 87.44	S1720C25FSR 118.65	2	0	026
3	S1720C30 100.63	S1720C30F 100.63	S1720C30FSR 154.45	2	0	026
4	S1720C40 134.17	S1720C40F 134.17	S1720C40FSR 189.86	1	0	026

Compression Utility Swing Check Valves



Pressure Rating @ 73°F (23°C), Water
 Full Flow (open) 150 psi
 Back Pressure (closed) 75 psi

Maximum Service Temperature
 140°F (60°C)

Temperature/Pressure De-ratings Apply

- Standard Swing Check Assembly Maintains a Positive Seal
- Convenient Compression Ends for Quick Connections
- Engineered for Maximum Flow, Quick Response & Positive Shutoff
- Excellent for Pool & Spa, OEM and General Purpose Applications
- Compact, Space-Saving Design
- Replaceable PVC White or Clear Sealed Unit
- High Grade EPDM Seat
- Suitable for Horizontal or Vertical Up-flow Installations
- Pressure Rated to 150 psi @ 73°F Full Flow (open), 75 psi Back Pressure (closed)
- Maximum Service Temperature 140°F (temperature/pressure de-ratings apply)

General Installation Information: Swing check valves are designed for horizontal installations, but may be installed in up-flow only vertical position. Check valves MUST be installed with the valve's FLOW arrow pointing in the direction of the flow. Do not install valve upside down. Flow velocity should not exceed 5 ft./sec. Minimum opening pressure less than 0.5 psi.

PVC White Compression End Swing Check

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
Compression End					
S1500-05	1/2	20	0	026	27.22
S1500-07	3/4	35	0	026	28.64
S1500-10	1	20	0	026	29.85



Compression Utility Swing Check Valves

PVC White Compression End Swing Check (continued)

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
Compression End					
S1500-12	1-1/4	12	0	026	35.04
S1500-15	1-1/2	12	0	026	39.11
S1500-20	2	10	0	026	61.67
S1500-25	2-1/2	5	0	026	103.02
S1500-30	3	4	0	026	133.73
S1500-40	4	2	0	026	205.45

PVC Clear Compression End Swing Check

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
Compression End					
S1500C05	1/2	35	0	026	29.93
S1500C07	3/4	35	0	026	32.21
S1500C10	1	20	0	026	32.87
S1500C12	1-1/4	12	0	026	36.91
S1500C15	1-1/2	12	0	026	41.60
S1500C20	2	10	0	026	62.09
S1500C25	2-1/2	5	0	026	104.17
S1500C30	3	4	0	026	152.15
S1500C40	4	2	0	026	209.63

Compression Coupling Nut Wrenches

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
CCW-005	1/2	1	50	299	14.65
CCW-007	3/4	1	50	299	14.91
CCW-010	1	1	50	299	15.54
CCW-012	1-1/4	1	50	299	17.57
CCW-015	1-1/2	1	50	299	18.96
CCW-020 ¹	2	1	50	299	21.19
CCW-030 ²	3	1	25	299	26.06

¹ CCW-20 - Wrench also fits 2-1/2" Coupling Body

² CCW-30 - Wrench also fits 4" Coupling Body

Compression Coupling Nut Wrench Sets

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
CCW-000	Set	1	25	299	122.38

Complete Set of Wrenches, Sizes 1/2" - 3"

Utility Spring Check Valves

(Spring Assisted Swing Check)



Pressure Rating @ 73°F (23°C), Water
 Full Flow (open) 150 psi
 Back Pressure (closed) 75 psi

Maximum Service Temperature
 140°F (60°C)

Temperature/Pressure De-ratings Apply
 EPDM Seat

Stainless Steel Spring Assisted
 (non-adjustable)

General Installation Information: Spring check valves are designed for horizontal installations, but may be installed in an up-flow only vertical position. Check valves MUST be installed with the valve's FLOW arrow pointing in the direction of the flow. Do not install valve upside down. Flow velocity should not exceed 5 ft./sec. Minimum opening pressure less than 0.5 psi.

PVC White Spring Check (Spring Assisted Swing Check)

Size	Socket	Thread	SR Thread	Std Pk	Mstr Pk	Prod Code
1/2	S1580-05 40.33	S1580-05F 40.33	S1580-05FSR 43.73	20	0	026
3/4	S1580-07 45.64	S1580-07F 45.64	S1580-07FSR 50.49	20	0	026
1	S1580-10 47.55	S1580-10F 47.55	S1580-10FSR 54.29	20	0	026
1-1/4	S1580-12 49.49	S1580-12F 49.49	S1580-12FSR 60.37	12	0	026
1-1/2	S1580-15 52.69	S1580-15F 52.69	S1580-15FSR 71.22	12	0	026
2	S1580-20 55.23	S1580-20F 55.23	S1580-20FSR 75.37	15	0	026
2-1/2	S1580-25 98.03	S1580-25F 98.03	S1580-25FSR 129.25	5	0	026
3	S1580-30 102.24	S1580-30F 102.24	S1580-30FSR 156.06	4	0	026
4	S1580-40 145.11	S1580-40F 145.11	S1580-40FSR 200.86	2	0	026

PVC Clear Spring Check (Spring Assisted Swing Check)

Size	Socket	Thread	SR Thread	Std Pk	Mstr Pk	Prod Code
1/2	S1580C05 41.54	S1580C05F 41.54	S1580C05FSR 45.00	20	0	026
3/4	S1580C07 47.03	S1580C07F 47.03	S1580C07FSR 51.95	20	0	026
1	S1580C10 49.03	S1580C10F 49.03	S1580C10FSR 55.78	20	0	026
1-1/4	S1580C12 51.04	S1580C12F 51.04	S1580C12FSR 61.88	12	0	026
1-1/2	S1580C15 54.08	S1580C15F 54.08	S1580C15FSR 72.67	12	0	026
2	S1580C20 56.14	S1580C20F 56.14	S1580C20FSR 76.25	15	0	026