

**FP-3523**



**FP-3523 - Steering Wheel Control** "C" clamp adjustable control, black vinyl dipped with stainless steel fasteners. Steering wheel can be positioned for personal ease of operation or to accommodate low overhead doors for clearance when monitor is mounted on an apparatus. Outside diameter is 13" (330mm).

**FP-3525**



**FP-3525 - Mini Stream Shaper** lightweight aluminum or brass body with hard anodized finish and replaceable Delrin "Honeycomb" grid straightens steam minimizing water turbulence, resulting in improved, effective distance and overall reach. 1-1/2" (38mm) (3515) or 2-1/2" (64mm) (3525) NH female inlet x 2-1/2" (64mm) NH outlet.

**FP-3526 - Pressure Gauge** is stainless steel and liquid filled with a protective cover. 0-300# mounted on monitors at the base of the nozzle so that operator can insure proper pressure ranges for maximum, effective operation of both straight bore and combination fog/straight stream nozzles.

**FP-3526**



**FP-3527 - Drain Outlet** brass construction 1/4" (6mm) NPT male base with drain cock. Idea for pressure relief when used with automatic nozzle or in cold climates where water removal is necessary.

**FP-3527**



**FP-3528 - Butterfly Valve** 2-1/2" (64mm), 3" (76mm) or 4" (102mm) with aluminum bronzed wafer mounted in a neoprene seat. Cast steel body and handle with locking plate.

**FP-3529 - Hydrant Mount** 2-1/2" (64mm) or 3" (76mm) NPT male discharge thread with 2-1/2" (64mm) N.H. swivel inlet. "C" clamp hydrant bracket support arms are designed to fit on virtually any hydrant style. Red epoxy finish.

**FP-3530 - Hydrant Mount** with 2-1/2" (64mm) or 3" (76mm) 150# ASA raised face flange discharge with 2-1/2" (64mm) NH female swivel inlet. Flange outlet ideal to mount flange base monitor on butterfly valve.

**FPHM-2 - Hydrant Mount** only with two leg 2-1/2" (64mm) swivel inlet, 2-1/2" (64mm) flange or NPT outlet.



**FP-3528**

# ACCESSORIES/OPTIONS

**FPHM-2M - Hydrant Mount** only with two leg 2-1/2" (64mm) swivel inlet, complete with monitor.

**FP-3542 - Field Service Repair Kits** consist of replacement "O" rings, stainless steel ball-bearings and zerk fittings. Specify monitor style number when ordering. Nozzle and ball valve kits contain replacement ball and seats complete with all "O" ring gaskets

**FP-3543 - Special Threads** other than National Hose or National Pipe thread.

**FP-3544 - Nuts, Bolts and Gasket Package** for mounting monitors onto an existing flange mount.

**FP-3545 - Companion Flange** 2-1/2" (64mm), 3" (76mm) or 4" (102mm) with NPT female thread on the I.D. to mount onto a NPT male thread discharge pipe. Ideal for use with a butterfly valve between flange and monitor base. Red epoxy finish to match monitor.

**FP-3550 - Parallel Control Handles** c/p with black vinyl handle grip.

**FPHB-4 - Hydrant Base** for monitors. 6" (152mm) flanged inlet with 4" (102mm) flanged outlet for mounting monitor. Base has four 2-1/2" (64mm) outlets for extending water lines in high risk areas. Can be either flat or raised face flange. Carbon steel body with red epoxy finish, with cast brass 2-1/2" (64mm) NH discharge outlets. Optional caps with chains.

**FPGV - Gate Valve** made of cast brass with crank type handle. 2-1/2" (64mm) swivel inlet and 2-1/2" (64mm) male outlet with a red finish.



FP-3542

FP-3544



FP-3545



FPGV



FP-3550