

175 PSI WWP Bronze Angle Valves

Fire Protection Valve • Threaded Ends • Rubber Disc • Screw Over Bonnet

175 PSI/12.1 Bar Non-Shock Cold Water


UL LISTED*

MATERIAL LIST

PART	SPECIFICATION
1. Handwheel	Aluminum
2. Handwheel Screw	Carbon Steel (½" & ¾") Stainless Steel (1")
3. Stem	Bronze ASTM B584 Alloy C84400
4. Packing Nut	Bronze ASTM B584 Alloy C83600 or ASTM B16
5. Packing	Graphite Impregnated (Non Asbestos)
6. Bonnet	Bronze ASTM B584 Alloy C84400
7. Body	Bronze ASTM B584 Alloy C84400
8. Seat Disc	Nitrile Rubber
9. Seat Screw	Stainless Steel
10. Pack Washer	Sheet Brass



KT-67-UL
Threaded



DIMENSIONS—WEIGHTS—QUANTITIES


Dimensions											
Size		A		B		C		Weight		Box	Master
In.	mm.	In.	mm.	In.	mm.	In.	mm.	Lbs.	Kg.	Qty.	Ctn. Qty.
½	15	.94	24	3.25	83	1.06	27	.62	.28	10	60
¾	20	1.02	26	3.12	79	1.20	30	.70	.32	10	60
1	25	1.80	46	4.50	114	1.62	41	1.57	.71	5	25

* UL Listed for Trim and Drain Use, (Subject 258).

NOTE: See T-301-W for 1¼" -2" sizes.



WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.



KT-67-U
NPT x NPT

Visit our website for the most current information.