



Transition Fittings Product
CPVC Gray Special Reinforced (SR) Fittings & CPVC Gray Brass Thread Fittings

CPVC Gray Special Reinforced (SR) Fittings

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Tank Adapters, CPVC New Style Special Reinforced (SR)

Threaded with FKM Gaskets (continued)

Socket x SR Fipt - Stainless Steel Collar

8171V-015CSR	1-1/2	20	0	101	160.72
8171V-020CSR	2	15	0	101	239.33
8171V-025CSR	2-1/2	4	0	101	352.67
8171V-030CSR	3	4	0	101	419.95
8171V-040CSR	4	2	0	101	896.68
8171V-060CSR	6	2	0	101	2213.88

Tank Adapters, CPVC New Style Special Reinforced (SR) Threaded with Neoprene Gaskets

Fipt x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172-002CSR	1/4	25	150	101	80.99
8172-003CSR	3/8	25	200	101	80.99
8172-005CSR	1/2	25	0	101	80.99
8172-007CSR	3/4	25	0	101	94.05
8172-010CSR	1	25	0	101	103.63
8172-012CSR	1-1/4	20	0	101	147.01
8172-015CSR	1-1/2	20	0	101	164.24
8172-020CSR	2	15	0	101	203.07
8172-025CSR	2-1/2	4	0	101	294.72
8172-030CSR	3	4	0	101	350.86
8172-040CSR	4	2	0	101	538.89
8172-060CSR	6	2	0	101	1443.78

Tank Adapters, CPVC New Style Special Reinforced (SR) Threaded with EPDM Gaskets

Fipt x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172E-002CSR	1/4	25	150	101	84.17
8172E-003CSR	3/8	25	200	101	84.17
8172E-005CSR	1/2	25	0	101	84.17
8172E-007CSR	3/4	25	0	101	99.65
8172E-010CSR	1	25	0	101	108.19
8172E-012CSR	1-1/4	20	0	101	152.71
8172E-015CSR	1-1/2	20	0	101	177.53
8172E-020CSR	2	15	0	101	217.89
8172E-025CSR	2-1/2	4	0	101	328.71
8172E-030CSR	3	4	0	101	391.33
8172E-040CSR	4	2	0	101	633.51
8172E-060CSR	6	1	0	101	1465.14

Tank Adapters, CPVC New Style Special Reinforced (SR) Threaded with FKM Gaskets

Fipt x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172V-002CSR	1/4	25	150	101	129.23
8172V-003CSR	3/8	25	200	101	129.23

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Tank Adapters, CPVC New Style Special Reinforced (SR)

Threaded with FKM Gaskets (continued)

Fipt x SR Fipt - Stainless Steel Collar

8172V-005CSR	1/2	25	0	101	129.23
8172V-007CSR	3/4	25	0	101	146.20
8172V-010CSR	1	25	0	101	168.85
8172V-012CSR	1-1/4	20	0	101	208.47
8172V-015CSR	1-1/2	20	0	101	219.56
8172V-020CSR	2	15	0	101	337.44
8172V-025CSR	2-1/2	4	0	101	487.58
8172V-030CSR	3	4	0	101	580.45
8172V-040CSR	4	2	0	101	1481.17
8172V-060CSR	6	2	0	101	2689.40

Elastomer Expansion Joint - CPVC

CPVC with EPDM Bellows SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

EJ21-007CSR	3/4	10	0	085	255.64
EJ21-010CSR	1	10	0	085	293.98
EJ21-012CSR	1-1/4	15	0	085	324.86
EJ21-015CSR	1-1/2	10	0	085	414.08
EJ21-020CSR	2	8	0	085	547.34
EJ21-025CSR	2-1/2	4	0	085	760.14
EJ21-030CSR	3	2	0	085	1012.39

CPVC Gray Brass Thread Fittings

Tee - Brass Transition

Socket x Socket x Fipt With Brass Thread Insert

802-005CBR	1/2	20	140	096	71.66
802-007CBR	3/4	20	80	096	143.34

Not intended to convey or dispense water for human consumption through drinking or cooking

Tee - Brass Transition Reducing

Socket x Socket x Fipt With Brass Thread Insert

802-101CBR	3/4X1/2	50	0	096	88.84
------------	---------	----	---	-----	-------

Not intended to convey or dispense water for human consumption through drinking or cooking

90° Ell - Brass Transition

Socket x Fipt With Brass Thread Insert

807-005CBR	1/2	20	240	096	63.01
807-007CBR	3/4	20	160	096	110.02

Not intended to convey or dispense water for human consumption through drinking or cooking