



Transition Fittings Product PVC Gray Brass Thread Fittings & CPVC Gray Special Reinforced (SR) Fittings

PVC Gray Brass Thread Fittings

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union - Socket/Brass Fipt/EPDM

Socket x Fipt with Brass Thread Insert & EPDM O-ring Seal



235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

899-007BR	3/4	10	60	086	58.88
899-010BR	1	10	0	086	79.40
899-012BR	1-1/4	5	20	086	133.54
899-015BR	1-1/2	5	0	086	176.76
899-020BR	2	5	0	086	235.59

Not intended to convey or dispense water for human consumption through drinking or cooking

CPVC Gray Special Reinforced (SR) Fittings

Tee - Special Reinforced

Socket x Socket x SR Fipt - Stainless Steel Collar



802-005CSR	1/2	50	0	096	24.16
802-007CSR	3/4	15	120	096	35.29
802-010CSR	1	15	0	096	44.40
802-012CSR	1-1/4	15	0	096	51.52
802-015CSR	1-1/2	10	0	096	51.52
802-020CSR	2	10	0	096	84.21
802-030CSR	3	5	0	096	121.27
802-040CSR	4	5	0	096	228.46

Tee - Special Reinforced

SR Fipt x SR Fipt x SR Fipt - Stainless Steel Collar



805-002CSR	1/4	25	150	096	21.62
805-003CSR	3/8	25	150	096	21.62
805-005CSR	1/2	25	150	096	28.91
805-007CSR	3/4	25	100	096	33.12
805-010CSR	1	15	0	096	49.46
805-015CSR	1-1/2	10	0	096	52.52
805-020CSR	2	10	0	096	62.54

Tee - Special Reinforced Reducing

Socket x Socket x SR Fipt - Stainless Steel Collar



802-072CSR	1/2X1/4	25	200	096	24.16
802-098CSR	3/4X1/4	25	100	096	32.27
802-101CSR	3/4X1/2	50	0	096	32.27
802-128CSR ¹	1X1/4	15	0	096	49.85
802-130CSR	1X1/2	50	0	096	19.73
802-131CSR	1X3/4	15	0	096	49.85
802-164CSR ¹	1-1/4X1/4	5	0	096	66.28
802-166CSR	1-1/4X1/2	15	0	096	52.51

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Tee - Special Reinforced Reducing (continued)

Socket x Socket x SR Fipt - Stainless Steel Collar

802-168CSR	1-1/4X1	10	0	096	53.59
802-207CSR ¹	1-1/2X1/4	15	0	096	94.92
802-211CSR	1-1/2X1	10	0	096	62.92
802-212CSR	1-1/2X1-1/4	10	0	096	62.92
802-245CSR ¹	2X1/4	10	0	096	109.02
802-247CSR	2X1/2	10	0	096	98.14
802-248CSR	2X3/4	10	0	096	109.02
802-287CSR	2-1/2X1/2	10	0	096	74.97
802-331CSR ¹	3X1/4	5	0	096	208.25
802-413CSR ¹	4X1/4	5	0	096	225.98

¹ Sized with Bushing

Tee - Special Reinforced Reducing

Socket x SR Fipt - Stainless Steel Collar x Socket



(See also Gauge & Instrument Fittings for additional configurations)

803-095CSR	3/4X1/2X3/4	15	0	096	19.88
------------	-------------	----	---	-----	-------

90° Ell - Special Reinforced

Socket x SR Fipt - Stainless Steel Collar



807-005CSR	1/2	20	240	096	11.73
807-007CSR	3/4	75	0	096	13.77
807-010CSR	1	50	0	096	16.59
807-012CSR	1-1/4	25	0	096	34.25
807-015CSR	1-1/2	10	0	096	41.17
807-020CSR	2	10	0	096	51.51

90° Ell - Special Reinforced

SR Fipt x SR Fipt - Stainless Steel Collar



808-003CSR	3/8	25	150	096	7.08
808-005CSR	1/2	20	120	096	7.08
808-007CSR	3/4	20	160	096	10.37
808-010CSR	1	50	0	096	13.29
808-012CSR	1-1/4	25	0	096	25.59
808-015CSR	1-1/2	10	0	096	30.13
808-020CSR	2	10	0	096	40.36

90° Ell - Special Reinforced Reducing

Socket x SR Fipt - Stainless Steel Collar



807-101CSR	3/4X1/2	50	0	096	14.94
807-130CSR	1X1/2	50	0	096	16.12

Transition Fittings Product
CPVC Gray Special Reinforced (SR) Fittings



CPVC Gray Special Reinforced (SR) Fittings

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

45° Ell - Special Reinforced

SR Fipt x SR Fipt - Stainless Steel Collar

819-007CSR	3/4	25	300	096	16.19
------------	-----	----	-----	-----	-------



Coupling - Special Reinforced

SR Fipt x SR Fipt - Stainless Steel Collar

830-005CSR	1/2	25	150	096	11.43
830-007CSR	3/4	25	150	096	18.46
830-010CSR	1	25	200	096	20.98
830-012CSR	1-1/4	10	120	096	22.29
830-015CSR	1-1/2	10	80	096	23.88
830-020CSR	2	10	0	096	28.23



Coupling - Special Reinforced Reducer

SR Fipt x SR Fipt - Stainless Steel Collar

830-101CSR	3/4X1/2	50	200	096	20.47
830-130CSR	1X1/2	50	0	096	24.73
830-131CSR	1X3/4	25	200	096	24.73
830-168CSR	1-1/4X1	25	0	096	33.63
830-210CSR	1-1/2X3/4	25	0	096	48.08
830-211CSR	1-1/2X1	10	80	096	48.08
830-212CSR	1-1/2X1-1/4	10	80	096	48.08
830-249CSR	2X1	25	0	096	118.37
830-251CSR	2X1-1/2	15	0	096	118.37



Female Adapter - Special Reinforced

Socket x SR Fipt - Stainless Steel Collar

835-002CSR	1/4	25	450	096	16.03
835-003CSR	3/8	25	300	096	16.03
835-005CSR	1/2	25	150	096	6.89
835-007CSR	3/4	25	150	096	7.44
835-010CSR	1	25	200	096	16.98
835-012CSR	1-1/4	10	60	096	17.42
835-015CSR	1-1/2	10	80	096	20.21
835-020CSR	2	10	0	096	28.72
835-025CSR	2-1/2	5	0	096	66.77
835-030CSR	3	15	0	096	137.20
835-040CSR	4	5	0	096	228.35
835-060CSR	6	6	0	096	356.72



Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Female Adapter - Encapsulated Special Reinforced

Socket x ESR Fipt

835-002CESR	1/4	25	450	096	20.35
835-003CESR	3/8	25	300	096	20.35
835-005CESR	1/2	25	300	096	10.56
835-007CESR	3/4	25	300	096	11.15
835-010CESR	1	25	200	096	24.57
835-012CESR	1-1/4	10	80	096	25.14
835-015CESR	1-1/2	10	80	096	32.57
835-020CESR	2	10	0	096	50.60



Female Spigot Adapter - Special Reinforced

Spigot x SR Fipt - Stainless Steel Collar

878-005CSR	1/2	50	600	096	7.34
878-007CSR	3/4	25	300	096	7.75
878-010CSR	1	50	0	096	17.43
878-012CSR	1-1/4	25	0	096	18.02
878-015CSR	1-1/2	25	0	096	20.92
878-020CSR	2	15	0	096	38.11
878-030CSR	3	5	0	096	138.93
878-040CSR	4	5	0	096	233.21



Female Adapter - Special Reinforced Reducing

Socket x SR Fipt - Stainless Steel Collar

835-074CSR	1/2X3/4	50	400	096	7.44
835-101CSR	3/4X1/2	50	400	096	7.44
835-102CSR	3/4X1	50	0	096	16.98
835-130CSR	1X1/2	50	0	096	16.98
835-131CSR	1X3/4	25	200	096	16.98



Female Spigot Adapter - Encapsulated Special Reinforced

Spigot x ESR Fipt

878-005CESR	1/2	50	600	096	10.87
878-007CESR	3/4	25	300	096	11.57
878-010CESR	1	50	0	096	24.80
878-012CESR	1-1/4	25	0	096	25.47
878-015CESR	1-1/2	25	0	096	33.21
878-020CESR	2	15	0	096	51.34



Female Spigot Adapter - Special Reinforced Reducing

Spigot x SR Fipt - Stainless Steel Collar

878-072CSR	1/2X1/4	25	450	096	21.04
878-098CSR	3/4X1/4	50	300	096	24.49
878-128CSR	1X1/4	50	400	096	27.42





Transition Fittings Product CPVC Gray Special Reinforced (SR) Fittings

CPVC Gray Special Reinforced (SR) Fittings

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Male Adapter - Internal Reinforced



R Mipt x Socket - Stainless Steel Sleeve

NSF® Certified Lead Free

836-005CR	1/2	25	150	096	10.58
836-007CR	3/4	25	300	096	12.13
836-010CR	1	10	120	096	14.38
836-012CR	1-1/4	10	60	096	29.44
836-015CR	1-1/2	10	120	096	39.72
836-020CR	2	10	0	096	53.73

Reducer Bushing - Special Reinforced Reducing Flush Style



Mipt x SR Fipt - Stainless Steel Collar

839-209CSR	1-1/2X1/2	25	300	096	27.14
839-210CSR	1-1/2X3/4	25	300	096	27.14
839-247CSR	2X1/2	10	60	096	29.99
839-248CSR	2X3/4	10	60	096	29.99
839-249CSR	2X1	10	120	096	29.99
839-420CSR	4X2	6	0	096	166.56

Reducer Bushing - Special Reinforced



Spigot x SR Fipt - Stainless Steel Collar

838-128CSR	1X1/4	25	150	096	15.64
838-207CSR	1-1/2X1/4	25	200	096	26.45
838-209CSR	1-1/2X1/2	10	120	096	27.57
838-210CSR	1-1/2X3/4	10	120	096	27.57
838-247CSR	2X1/2	10	80	096	37.88
838-248CSR	2X3/4	10	80	096	37.88
838-249CSR	2X1	10	120	096	37.88
838-334CSR	3X3/4	10	0	096	160.44
838-335CSR	3X1	10	0	096	160.44
838-336CSR	3X1-1/4	10	0	096	160.44
838-337CSR	3X1-1/2	10	0	096	160.44
838-528CSR	6X2	5	0	096	551.59
838-530CSR	6X3	5	0	096	551.59

Cap - Special Reinforced



SR Fipt - Stainless Steel Collar

848-002CSR	1/4	25	500	096	8.66
848-003CSR	3/8	25	450	096	8.66
848-007CSR	3/4	25	300	096	13.51
848-030CSR	3	5	0	096	150.76

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union 2000 - Socket/Special Reinforced Fipt/EPDM



Socket x SR Fipt w/EPDM O-ring Seal - Stainless Steel Collar

1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8099-005CSR	1/2	20	120	096	19.41
8099-007CSR	3/4	20	160	096	34.47
8099-010CSR	1	15	90	096	47.73
8099-012CSR	1-1/4	10	0	096	90.41
8099-015CSR	1-1/2	10	0	096	98.34
8099-020CSR	2	5	0	096	103.55
8099-025CSR	2-1/2	5	0	096	177.60
8099-030CSR	3	5	0	096	288.46
8099-040CSR	4	4	0	096	338.77
8099-060CSR	6	1	0	096	752.84

Union 2000 - Special Reinforced



Soc x SR Fipt with FKM O-ring Seal - Stainless Steel Collar

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8059-005CSR	1/2	25	200	096	19.80
8059-007CSR	3/4	20	160	096	34.94
8059-010CSR	1	15	90	096	48.13
8059-012CSR	1-1/4	10	0	096	91.76
8059-015CSR	1-1/2	10	0	096	99.75
8059-020CSR	2	5	0	096	103.84
8059-030CSR	3	5	0	096	292.13
8059-040CSR	4	4	0	096	340.82

Union 2000 - Special Reinforced Fipt/FKM



SR Fipt x SR Fipt w/FKM O-ring Seal - Stainless Steel Collar

1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8058-005CSR	1/2	20	120	096	20.33
8058-007CSR	3/4	20	80	096	35.42
8058-010CSR	1	15	90	096	48.68
8058-012CSR	1-1/4	10	0	096	91.76
8058-015CSR	1-1/2	10	0	096	100.14
8058-020CSR	2	5	0	096	105.51
8058-030CSR	3	5	0	096	298.15
8058-040CSR	4	4	0	096	349.29
8058-060CSR	6	1	0	096	786.65

Union 2000 - Special Reinforced Fipt/EPDM



SR Fipt x SR Fipt w/EPDM O-ring Seal - Stainless Steel Collar

1/2" - 4" 235 psi; 6" 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8098-005CSR	1/2	20	160	096	19.64
-------------	-----	----	-----	-----	-------

Transition Fittings Product
CPVC Gray Special Reinforced (SR) Fittings



CPVC Gray Special Reinforced (SR) Fittings

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Union 2000 - Special Reinforced Fipt/EPDM (continued)

SR Fipt x SR Fipt w/EPDM O-ring Seal - Stainless Steel Collar

8098-007CSR	3/4	20	80	096	35.09
8098-010CSR	1	15	90	096	48.13
8098-012CSR	1-1/4	10	0	096	90.87
8098-015CSR	1-1/2	10	0	096	99.36
8098-020CSR	2	5	0	096	104.46
8098-025CSR	2-1/2	5	0	096	180.55
8098-030CSR	3	5	0	096	293.54
8098-040CSR	4	4	0	096	339.82
8098-060CSR	6	1	0	096	755.17

Union (Old Style) - Socket/Special Reinforced Fipt/EPDM

Socket x SR Fipt w/EPDM O-ring Seal -Stainless Steel Collar

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

899-002CSR	1/4	25	150	096	30.96
899-003CSR	3/8	25	100	096	30.96
899-005CSR	1/2	10	60	096	19.41
899-007CSR	3/4	10	40	096	34.47
899-010CSR	1	10	40	096	47.73
899-012CSR	1-1/4	5	20	096	90.41
899-015CSR	1-1/2	5	0	096	98.34
899-020CSR	2	5	0	096	103.55
899-030CSR	3	5	0	096	288.46
899-040CSR	4	4	0	096	338.77

Union (Old Style) - Socket/Special Reinforced Fipt/FKM

Socket x SR Fipt w/FKM O-ring Seal - Stainless Steel Collar

235 psi Maximum Internal Pressure Rating @ 73°F (23°C)

859-002CSR	1/4	25	150	096	31.17
859-003CSR	3/8	25	100	096	31.17
859-005CSR	1/2	10	60	096	19.80
859-007CSR	3/4	10	60	096	34.94
859-010CSR	1	10	40	096	48.13
859-012CSR	1-1/4	5	20	096	91.76
859-015CSR	1-1/2	5	0	096	99.75
859-020CSR	2	5	0	096	103.84
859-030CSR	3	5	0	096	292.13
859-040CSR	4	4	0	096	340.82

Flange - Special Reinforced One Piece Threaded

SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

852-005CSR	1/2	25	0	096	25.35
852-007CSR	3/4	25	0	096	30.76
852-010CSR	1	15	0	096	33.65
852-012CSR	1-1/4	15	0	096	46.57

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Flange - Special Reinforced One Piece Threaded (continued)

SR Fipt - Stainless Steel Collar

852-015CSR	1-1/2	15	0	096	49.38
852-020CSR	2	10	0	096	50.57
852-025CSR	2-1/2	10	0	096	81.36
852-030CSR	3	10	0	096	80.73
852-040CSR	4	5	0	096	151.29

Tank Adapters, CPVC New Style Special Reinforced (SR) Threaded with Neoprene Gaskets



Socket x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171-002CSR	1/4	25	150	101	61.14
8171-003CSR	3/8	25	200	101	61.14
8171-005CSR	1/2	25	0	101	61.14
8171-007CSR	3/4	25	0	101	73.18
8171-010CSR	1	25	0	101	82.78
8171-012CSR	1-1/4	20	0	101	106.78
8171-015CSR	1-1/2	20	0	101	119.87
8171-020CSR	2	15	0	101	165.77
8171-025CSR	2-1/2	4	0	101	252.17
8171-030CSR	3	4	0	101	300.14
8171-040CSR	4	2	0	101	482.36
8171-060CSR	6	1	0	101	1273.96

Tank Adapters, CPVC New Style Special Reinforced (SR) Threaded with EPDM Gaskets



Socket x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171E-002CSR	1/4	25	150	101	69.29
8171E-003CSR	3/8	25	200	101	69.29
8171E-005CSR	1/2	25	0	101	69.29
8171E-007CSR	3/4	25	0	101	78.32
8171E-010CSR	1	25	0	101	93.64
8171E-012CSR	1-1/4	20	0	101	117.03
8171E-015CSR	1-1/2	20	0	101	126.61
8171E-020CSR	2	15	0	101	178.99
8171E-025CSR	2-1/2	4	0	101	263.03
8171E-030CSR	3	4	0	101	313.13
8171E-040CSR	4	2	0	101	502.06
8171E-060CSR	6	2	0	101	1325.87

Tank Adapters, CPVC New Style Special Reinforced (SR) Threaded with FKM Gaskets



Socket x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8171V-002CSR	1/4	25	150	101	90.28
8171V-003CSR	3/8	25	200	101	90.28
8171V-005CSR	1/2	25	0	101	90.28
8171V-007CSR	3/4	25	0	101	104.37
8171V-010CSR	1	25	0	101	121.41
8171V-012CSR	1-1/4	20	0	101	150.51



Transition Fittings Product
CPVC Gray Special Reinforced (SR) Fittings & CPVC Gray Brass Thread Fittings

CPVC Gray Special Reinforced (SR) Fittings

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Tank Adapters, CPVC New Style Special Reinforced (SR)

Threaded with FKM Gaskets (continued)

Socket x SR Fipt - Stainless Steel Collar

8171V-015CSR	1-1/2	20	0	101	160.72
8171V-020CSR	2	15	0	101	239.33
8171V-025CSR	2-1/2	4	0	101	352.67
8171V-030CSR	3	4	0	101	419.95
8171V-040CSR	4	2	0	101	896.68
8171V-060CSR	6	2	0	101	2213.88

Tank Adapters, CPVC New Style Special Reinforced (SR) Threaded with Neoprene Gaskets

Fipt x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172-002CSR	1/4	25	150	101	80.99
8172-003CSR	3/8	25	200	101	80.99
8172-005CSR	1/2	25	0	101	80.99
8172-007CSR	3/4	25	0	101	94.05
8172-010CSR	1	25	0	101	103.63
8172-012CSR	1-1/4	20	0	101	147.01
8172-015CSR	1-1/2	20	0	101	164.24
8172-020CSR	2	15	0	101	203.07
8172-025CSR	2-1/2	4	0	101	294.72
8172-030CSR	3	4	0	101	350.86
8172-040CSR	4	2	0	101	538.89
8172-060CSR	6	2	0	101	1443.78

Tank Adapters, CPVC New Style Special Reinforced (SR) Threaded with EPDM Gaskets

Fipt x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172E-002CSR	1/4	25	150	101	84.17
8172E-003CSR	3/8	25	200	101	84.17
8172E-005CSR	1/2	25	0	101	84.17
8172E-007CSR	3/4	25	0	101	99.65
8172E-010CSR	1	25	0	101	108.19
8172E-012CSR	1-1/4	20	0	101	152.71
8172E-015CSR	1-1/2	20	0	101	177.53
8172E-020CSR	2	15	0	101	217.89
8172E-025CSR	2-1/2	4	0	101	328.71
8172E-030CSR	3	4	0	101	391.33
8172E-040CSR	4	2	0	101	633.51
8172E-060CSR	6	1	0	101	1465.14

Tank Adapters, CPVC New Style Special Reinforced (SR) Threaded with FKM Gaskets

Fipt x SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

8172V-002CSR	1/4	25	150	101	129.23
8172V-003CSR	3/8	25	200	101	129.23

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Tank Adapters, CPVC New Style Special Reinforced (SR)

Threaded with FKM Gaskets (continued)

Fipt x SR Fipt - Stainless Steel Collar

8172V-005CSR	1/2	25	0	101	129.23
8172V-007CSR	3/4	25	0	101	146.20
8172V-010CSR	1	25	0	101	168.85
8172V-012CSR	1-1/4	20	0	101	208.47
8172V-015CSR	1-1/2	20	0	101	219.56
8172V-020CSR	2	15	0	101	337.44
8172V-025CSR	2-1/2	4	0	101	487.58
8172V-030CSR	3	4	0	101	580.45
8172V-040CSR	4	2	0	101	1481.17
8172V-060CSR	6	2	0	101	2689.40

Elastomer Expansion Joint - CPVC

CPVC with EPDM Bellows SR Fipt - Stainless Steel Collar

150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

EJ21-007CSR	3/4	10	0	085	255.64
EJ21-010CSR	1	10	0	085	293.98
EJ21-012CSR	1-1/4	15	0	085	324.86
EJ21-015CSR	1-1/2	10	0	085	414.08
EJ21-020CSR	2	8	0	085	547.34
EJ21-025CSR	2-1/2	4	0	085	760.14
EJ21-030CSR	3	2	0	085	1012.39

CPVC Gray Brass Thread Fittings

Tee - Brass Transition

Socket x Socket x Fipt With Brass Thread Insert

802-005CBR	1/2	20	140	096	71.66
802-007CBR	3/4	20	80	096	143.34

Not intended to convey or dispense water for human consumption through drinking or cooking

Tee - Brass Transition Reducing

Socket x Socket x Fipt With Brass Thread Insert

802-101CBR	3/4X1/2	50	0	096	88.84
------------	---------	----	---	-----	-------

Not intended to convey or dispense water for human consumption through drinking or cooking

90° Ell - Brass Transition

Socket x Fipt With Brass Thread Insert

807-005CBR	1/2	20	240	096	63.01
807-007CBR	3/4	20	160	096	110.02

Not intended to convey or dispense water for human consumption through drinking or cooking