





# Selection Chart

## PRESS TOOLS

Inline RP 241 page 10.5	Jaws	Pressing Rings	Power	Copper/SS Capacity	PEX Capacity	Steel Capacity	Weight (lb.)	Rotating Barrel	Characteristics
	Compact Series Jaws: • ProPress® (copper & stainless) • PureFlow™ (PEX) • ASTM F1807 (PEX) • MegaPress® (steel)	Compact Series Press Rings (see chart below)	12V Advanced Lithium 2.5 Battery	½ - 1 ¼"	¾ - 1 ½"	½ - ¾"	5.2 with battery	180°	The inline form of the tool allows access to tighter spaces, enabling press connections in hard-to-reach areas. The tool comes standard with two 12V Advanced Lithium 2.5 batteries that can produce over 140 presses per charge for jobsite efficiency.
<b>Compact RP 240</b> page 10.6	<b>Characteristics</b>								
	Compact Series Jaws: • ProPress® (copper & stainless) • PureFlow™ (PEX) • ASTM F1807 (PEX) • MegaPress® (steel)	Compact Series Press Rings (see chart below)	12V Advanced Lithium 2.5 Battery	½ - 1 ¼"	¾ - 1 ½"	½ - ¾"	5.2 with battery	180°	For ½" to 1 ¼" copper and stainless steel, and ¾" to 1 ½" PEX fittings, the RP 240 is the right choice for contractors who prefer a pistol grip style tool. Also features a 180° rotating barrel to reach into tight spaces.
<b>RP 340</b> page 10.12	<b>Characteristics</b>								
	Series Jaws: • ProPress® (copper & stainless) • PureFlow™ (PEX) • MegaPress® (Black Iron Pipe) • Press Snap Soil Pipe Cutter	Standard Series Press Rings: (see chart below)	18V Advanced Lithium 2 Battery	½ - 4"	½ - 2"	½ - 2" (2 ½ - 4" with Press Booster)	8.3 with battery	180°	The RP 340 press tool has a 4" capacity and weighs only 8.3 pounds. It features a 180° rotating swivel barrel, perfect for getting at hard-to-reach connections. An available 18V Advanced Lithium 4 battery helps the RP 340 achieve more than 400 presses per charge, and it has a service interval of 42,000 cycles. An optional AC power adapter can further maximize uptime job site to job site.
<b>PEX-One™</b> page 10.13	<b>Characteristics</b>								
	• ASTM F1807 (PEX) • PureFlow™ (PEX)	–	12V Advanced Lithium 2.5 Battery	–	½ - 1"	–	5.5 with battery	–	The RIDGID PEX-One™ 12V Battery PEX Tool is designed to be lightweight, low-profile and to press multiple size connections, up to one inch, with a single tool. The first in its class, RIDGID PEX-One™ gives you the one-handed capability you need for easy and accurate press connections in all those tight spaces.

## PRESS JAWS & RINGS

Compact Series Press Jaws for use with 100B, RP 240 or RP 241								
Compact Series Jaws	¾"	1"	1 ¼"	1 ½"	2"	2 ½"	3"	4"
ProPress (copper & stainless)	–	16958	–	16963	16978	31228	–	–
Pureflow (PEX)	17003	17008	19813	17013	17018	22683	22688	–
ASTM F 1807 (PEX)	–	22958	–	22968	22973	22978	–	–
MegaPress	–	48433	–	48438	–	–	–	–

Standard Series Press Jaws for use with CT400, 320-E, RP 330-B, RP 330-C & RP 340								
Standard Series Jaws	½"	¾"	1"	1 ¼"	1 ½"	2"	2 ½"	3"
ProPress (copper & stainless)	76652	–	76657	76662	76667	76672	76677	–
Pureflow (PEX)	22653	22658	22663	22668	22673	22678	35343	–
MegaPress	37958	–	37963	37968	–	–	–	–

Large Diameter Press Rings for use with CT400, 320-E, RP 330-B, RP 330-C & RP 340					
Pressing Rings	Standard Series Actuator Jaw	2 ½"	3"	4"	2 ½"-4" Ring Kit with Case
ProPress XL-C (copper and stainless steel fittings)	V2 Actuator 21878	20543	20548	20553	20483

MEGAPRESS - SMALL DIAMETER PRESS RINGS FOR USE WITH CT400, 320-E, RP 330-B, RP 330-C & RP 340			
Actuator Jaw	1 ¼"	1 ½"	2"
V2: 21878	37973	37978	37983

Small Diameter Press Rings for use with CT400, 320-E, RP 330-B, RP 330-C, RP 340, 100B, RP 200-B & RP 210-B							
Actuator Jaw	½"	¾"	1"	1 ¼"	1 ½"	2"	For Use With
V1 28033	27998	28003	28008	28013	–	–	RP 340 RP 330-B RP 330-C 320E CT400
V2 21878	–	–	–	–	28018	28023	RP 340 RP 330-B RP 330-C 320E CT400
C1 26163	27998	28003	28008	28013	–	–	100B RP 200-B RP 210-B

ProPress® is a registered trademark of Viega. PureFlow™ is a trademark of Viega. MegaPress® is a registered trademark of Viega.