Drum Machines



K-6200 DRUM MACHINE

- 3" to 6" (75 to 150 mm) Drain/Sewer Lines Up to 200' (61 m)
- K-6200 machines offer superior maneuverability and a small footprint allows easy access to tight work areas. It comes equipped with either Inner Core cable or Integral Wound cable. Recommend 5/8" (16 mm) cable for 3" (75 mm) to 6" (150 mm) drain lines up to 200' (61 m).
- Cable Control System causes the drum to stop spinning when the blade becomes lodged in a blockage, limits potential for cable to flip-over in the drum and helps indicate to operator when blockages are encountered.
- Direct Drive Design 4/10 HP universal motor and gearbox bear down as torque builds. Audible
 warnings let operator know when blockage is encountered. Drum requires no adjustments to stay
 aligned and tight on drive shaft.
- Easy Maintenance Construction Separate drum and machine in seconds. Inner drum and guide tube remove easily to maintain or replace cable.
- **Designed Durable and Stable** Low center of gravity frame design and custom kickstand keep machine firmly anchored during operation. Rugged, corrosion-resistant polyethylene drum is rust and dent proof. Double tubular frame is lightweight and designed for extra strength.
- AUTOFEED[®] Control and Standard Accessories Powerful feed mechanism is built to last and is easily maintained. AUTOFEED control, toolbox and selection of cutters included in all models.

SPECIFICATIONS

- Line Capacity 3"- 6" (75-150 mm) Lines, up to 200' (61 m)
- Drum Capacity 100' (30.5 m) of 5/8" (16 mm) cable
- Weight (Machine & 100' (30.5 m) of Cable) 180 lbs. (81.6 kg)
- Size Length 29 1/2" (75 cm, Height 43 1/2" (110 cm) (max.), Width 18 3/4", (47 cm)

MOTOR

- Type 115V/60 Hz, 5.6 Amp, Reversible, Universal AC Motor
- Rating 4/10 HP, 285 RPM
- Machine Options

| Catalog No. | Model No. | Description | Weight | |
|-------------|------------------|---|--------|------|
| Galalog NO. | | | lb. | kg |
| 93557 | | Machine, Standard Accessories and $\mathbf{5/8''} \times 100' \ (16 \ \text{mm} \times 30.5 \ \text{m}) \ \text{HD}$ Solid Core Cable | 180 | 81.8 |
| 95732 | K-6200 with C-24 | Machine, Standard Accessories and $\mathbf{5/s^{\prime\prime}}$ x 100' (16 mm x 30.5 m) Inner Core Cable | 100 | |
| 95737 | K-6200 | Machine with 5/8" (16 mm) Pigtail & Standard Accessories | 98 | 44.5 |

Standard Equipment

| Catalog No. Model No. | Description | 93557 K-6200 w/C24 HD Cable | 95732 K-6200 w/C-24 | 95737 K-6200 |
|--------------------------|--------------------------------------|--------------------------------|------------------------|-----------------|
| 58192 | 5/8" (16 mm) x 100' HC Cable (30.5m) | I | | |
| 59360 | Tool Box | I | I | I |
| 70032 | RIDGID PVC Drain Cleaning Gloves | I | I | I |
| 92495 | Spade Cutter, 1 3/4" (45 mm) | I | I | I |
| 92510 | Double Cutter, 2" (50 mm) | I | I | I |
| 92520 | Double Cutter, 3" (75 mm) | I | I | I |
| 92525 | Double Cutter, 4" (110 mm) | I | I | I |
| 92555 | 5⁄8" (16 mm) x 2' (50 mm) Leader | I | I | I |

