



GENERAL PURPOSE GAUGES

Series P-915 Low Cost Metric Utility Gauges

DESCRIPTION


U.S. Gauge P-915 utility gauges provide economical, reliable service in a wide variety of applications including pumps, compressors, and other equipment.

Series P-915 utility gauges come in English and metric ranges with accuracy of either $\pm 3-2-3\%$ or $\pm 1.6\%$ full scale. Gauges are available in 40mm, 50mm, and 63mm ABS cases with a choice of English or metric connections in center-back and lower mount configurations.

SPECIFICATIONS

- SIZES:** 40mm, 50mm, and 63mm
- RANGES:** 0-30 through 0-4000 psi
- ACCURACY:** $\pm 3-2-3\%$ (Grade B) or $\pm 1.6\%$ of span
- BOURDON TUBE:** Phosphor bronze
- WINDOW:** Polystyrene (polycarbonate optional)
- MOVEMENT:** Brass
- DIAL:** ABS, white background with black numbering
- POINTER:** ABS, black
- CASE:** ABS, black
- CONNECTION:** Brass, center-back or lower mount; 1/8-27 NPT: for 40mm and 50mm; 1/4-18 NPT: for 50mm and 63mm
G1/8B, G1/4B, R1/8, R1/4

Other sizes, ranges, and mounting configurations are available for OEM quantities



Dimensions – P-915							
Dial Sizes	Model	Unit	ØA	B	C	D	E
40mm	LM	inches	1.63	.92	.36	–	.80
		mm	41.4	23.4	9.1	–	20.3
	CBM	inches	1.63	1.06	.79	.55	.80
		mm	41.4	26.9	20.1	14.0	20.3
50mm	LM	inches	1.91	1.06	.38	–	.97
		mm	48.5	26.9	9.7	–	24.6
	CBM	inches	1.91	1.06	.95	.55	.92
		mm	48.5	26.9	24.1	14.0	23.4
63mm	LM	inches	2.43	1.10	.39	–	.97
		mm	61.7	27.9	9.9	–	24.6
	CBM	inches	2.43	1.10	1.19	.55	.92
		mm	61.7	27.9	30.2	14.0	23.4