Sectional Machines



K-1500G SECTIONAL MACHINE

- 2" to 10" (50 to 250 mm) Drain/Sewer Lines
- A gasoline engine makes the Model K-1500G well-suited for cleaning lines in remote locations where electrical power is unavailable. Cuts through roots fast.
- Unique, easy-to-use, instant-acting cable clutch maximizes operator control. Pull down on the handle and the cable spins at 600 RPM. Release handle, cable stops instantly.
- Comes equipped to use 1 ¼" (32 mm) cable to clean 3" (75 mm) to 10" (250 mm) lines through 300' (92 m).
- 6 HP gasoline engine drives cable via four-speed transmission. Allows the operator to vary the cable spinning speed to fit the application. Forward speeds of 333, 425 and 500 RPM, and a reverse speed of 250 RPM.
- Low-profile, four-wheel cart easily rolls to the job. Guards against machine upset and possible fuel spillage.
- Includes A-1 RIDGID® drain cleaning mitt and operator's manual.

MACHINE DIMENSIONS

- Width Wheel to Wheel 26" (66 cm)
- Length Including Kickstand 28" (71 cm)
- Ground to Top of Handle 38" (97 cm)
- Back of Handle to Front 49" (124 cm)
- Ground to Top of Housing Shell 27" (60 cm)

Catalog No.	Model No.	Description	Weight	
			lb	kg
44587	K-1500G	Machine Only with A-1 RIDGID Drain Cleaning Mitt, A-12 Coupling Pin Key and A-34-10 Rear Guide Hose, A-369-X 1 1/4" (32 mm) Jaw Set	190	86.4
48462		Machine with Standard Equipment, includes: — Ten Sections Of C-14 Cable, Total 150' (45.7 m) — Three A-8 Cable Carriers — A-1 Left-Hand RIDGID Drain Cleaning Mitt — A-12 Coupling Pin Key — A-34-12 Rear Guide Hose — A-2864 Hex Key — A-3516 Hex Key — A-3 Tool Box — T-2 Heavy-Duty Straight Auger — T-4 Heavy-Duty Funnel Auger — T-6 Retrieving Auger — T-8 Grease Cutter — T-13 Sawtooth Cutter — T-50 Sharktooth Cutter	350	159.0



A-17 Manhole Guide PipeAdjusts 7' to 12', supports cables, locks into place quickly.



Model K-1500G with C-14 shown above.