

H1990M

# HEPA-AIRE® NEGATIVE AIR MACHINE

## Lightweight and Compact

### Powerful and Portable

The H1990M model has a 6" narrower cabinet than the H2KM model, with the same motor and blower and virtually identical leak-proof rivet construction and controls.

### FEATURES & BENEFITS

- The sturdy and compact H1990M weighs in at just 125 pounds, including filters
- Its narrow cabinet design allows the H1990M to fit in tight places
- True 99.97%-certified HEPA filter retains its original 99.97%+ efficiency, even after many hours of operation
- Swing out hinged door secured with cam latches for easy filter replacement
- 20 Gauge galvanized steel cabinet with watertight pop rivet construction includes an attached outlet exhaust collar for 12" flex duct connection
- Optional plastic inlet manifold available for inlet duct attachment (P/N: H1980P)
- The H1990M has been independently tested and certified in accordance with applicable UL and CSA safety requirements

### TECHNICAL SPECIFICATIONS

DESCRIPTION	UNIT	H1990M
Net Weight	lbs. (kg)	125 (56.7)
Dimensions (L x W x H)	in. (cm)	35.125 x 19.125 x 30.25 (89.212 x 48.578 x 76.835)
Electrical Rating	V, Hz, A	120 VAC, 60 Hz, 15 A
Airflow, max. with clean filters	CFM	1600 on High, 1050 on Low
Normal Operating Amps	amps	9 or less
Motor		1 HP, auto reset, 60 Hz, single phase
Sound Level @ 5 Feet	dB(A)	73-83 on high speed
HEPA Filter Efficiency	-	99.97% @ 0.3 microns
Cabinet Material	-	20 gauge stainless steel
Prefilter Access	-	Swing out hinged access door
First Stage Prefilter	1 ea.	H1901, polypad
Second Stage Prefilter	1 ea.	H1902, 2" deep pleated particulate
Optional Second Stage Prefilter	1 ea.	VL2002, 2" deep high capacity carbon
HEPA Filter	1 ea.	H1910M

Specifications and details are subject to change without prior notice.

Note: Airflow ratings estimates are based on factory and independent testing @ 120 VAC with an air straightener and a traverse of readings taken with a computing vane-anemometer. Actual results may vary for various reasons, including motor and blower and HEPA filter tolerances. Factors such as filter loading, reduced voltage to the motor, and inlet and outlet ducting will reduce airflow. Use these ratings as a general guideline only.



#### THE H1990M IS BEST SUITED FOR:



CRITICAL ENVIRONMENT PROTECTION



ABATEMENT & REMEDIATION

**ABATEMENT**  
TECHNOLOGIES®  
LEADERS IN CLEAN AIR

1 800 634 9091  
**ABATEMENT.COM**  
IAQINFO@ABATEMENT.COM