

Interchangeable Crimp Heads

Each Interchangeable Head is compatible with the exclusive QuickChange System™ and offers 360 degree head rotation for increased maneuverability into tight spaces.



4PIN™ DIELESS CRIMP HEAD

The 4PIN Dieless Crimp Head is classified to UL 1976 for copper connectors and wire from #8AWG to 750 kcmil (MCM) and aluminum connectors and wire from #8AWG to 500 kcmil (MCM).

- Eliminate the risk of losing dies or crimping with mismatched dies.

Catalog No.	Model No.	Description	Weight	
			lb.	kg
52283	4P-6	4PIN Dieless Crimp Head Only	5.8	2.6

*For the most up to date RIDGID Crimp Die/Electrical Connector Compatibility Charts, go to www.RIDGID.com/CrimpDies.

NEW



UC 60 BG
BG and D3 Grooves



UC 60 O
O and D3 Grooves

UC-60 CRIMP HEADS

- Copper Taps: #10 Solid – 2/0 Stranded
- AL and ACSR Taps: #14 Solid – 4/0 ACSR
- Stirrups: #6 – 4/0 ACSR
- Tension Splices: #10 Stranded – 4/0 ACSR
- Lugs & Splices: #8-350 MCM AL, 500 MCM CU
- Services Entrances: #10 Stranded – 4/0 ACSR

Catalog No.	Model No.	Description	Weight	
			lb.	kg
56793	UC-60 BG	D3/W-Die Crimp Head	4.85	2.20
56798	UC-60 O	D3/W-Die Crimp Head	4.85	2.20

LR-60B LATCHING ROUND CRIMP HEAD

- Slim, compact head design allows tool access to tight spaces.
- Quick release latching system for maximum efficiency.
- Crimp dies quickly snap into head – no push button or adapters to change dies
- Classified to UL 1976 for copper connectors and wire from #8AWG to 600 kcmil (MCM) and aluminum connectors and wire from #8AWG to 350 kcmil (MCM).
- Compatible with 6 Ton dies from RIDGID and other manufacturers*. See page 12.8 for 6 Ton RIDGID Dies.
- LR60B designed for 6 Ton U Dies ONLY. See page 12.8 for dies.



Catalog No.	Model No.	Description	Weight	
			lb.	kg
47753	LR-60B	Latching Round Crimp Head Only	5.3	2.4

*For the most up to date RIDGID Crimp Die/Electrical Connector Compatibility Charts, go to www.RIDGID.com/CrimpDies.