Inline & Sidewall Exhaust Fans





UL/cUL 705 Power Ventilators
E40001 - BCF with TEFC motors
E40001 - BDF with TEFC motors
US LISTED

Model BCF is AMCA Licensed for Air Performance Model BDF is AMCA Licensed for Sound and Air Performance



Model BCF and BDF Belt Drive


Centrifugal duct fans are designed for clean air inline exhaust or supply applications.

Quick Build Performance

BCF capacities range from 200 to 6,000 cfm and 1.5 in. wg of static pressure. BDF capacities range from 300 to 15,000 cfm and 3 in. wg of static pressure.

| Standard Construction | BCF | BDF |
|--|-----|-----|
| Housing - galvanized steel | | |
| Housing - low profile | | |
| Housing - square | | |
| Drive frame secured to housing | | |
| Wheel - forward-curved, galvanized steel | | |
| Motor and scroll - mounted to drive frame | | |
| Access door - bolted, removable (BCF-108/208 and larger, all BDF) | | |
| Access door - hinged (BCF-106, 107, 206 and 207) | | |
| Corrosion-resistant fasteners | | |
| NEMA-1 disconnect switch | | |
| Ball bearing motor - 1/4 hp and larger | | |
| Double-studded vibration isolators | | |
| Flanges - inlet and outlet | | |
| Adjustable motor pulley | | |
| Options and Accessories | BCF | BDF |
| Damper | | |
| Isolators | | |
| Insulation | | |
| Filter box* - filters are throwaway (pleated) or permanent (aluminum mesh) | | |
| Mixing box | | |
| NEMA rated disconnect switch | | |
| Dual drives | | |
| Multiple discharge positions* | | |
| Decorative or protective powder coating | | |
| UL/cUL Listed Power Ventilators | | |


*see page 31 for additional information



Dimensions for BCF Top horizontal discharge

| Model Size | А | В | С | Е | F |
|---------------|----|-------|----|----|----|
| 106 | 20 | 231/4 | 11 | 12 | 6 |
| 107 | 23 | 29 | 13 | 15 | 8 |
| 108 | 26 | 32 | 16 | 18 | 10 |
| 110 | 32 | 36 | 19 | 24 | 12 |
| 112 | 36 | 42 | 23 | 28 | 14 |
| 206 | 34 | 231/4 | 11 | 26 | 6 |
| 207 | 38 | 29 | 13 | 30 | 8 |
| 208 | 44 | 32 | 16 | 36 | 10 |
| 210 | 48 | 36 | 19 | 40 | 12 |
| 212 | 58 | 42 | 23 | 50 | 14 |

All dimensions are in inches.



Dimensions for BDF Bottom horizontal discharge

| Model Size | Α | В | С | Damper Outlet Opening (W x H) | Inlet Opening (D x E) |
|---------------|-------|--------|-------|--|--|
| 80 | 231/4 | 18½ | 151/8 | 9¾ x 8¾ | 15 ³ / ₁₆ x 12 ¹¹ / ₁₆ |
| 90 | 241/4 | 211/4 | 18¾ | 12½ x 10½ | 18½ x 15½ |
| 100 | 261/4 | 223/4 | 203/4 | 13¾ x 11¾ | 19¾ x 17⅓ |
| 120 | 33 | 271/4 | 223/4 | 16 x 13% | 24½ x 19½ |
| 150 | 34¾ | 32 1/8 | 27¾ | 19½ x 16½ | 285/8 x 237/8 |
| 180 | 401/4 | 41¾ | 31¾ | 22½ x 18½ | 37½ x 27% |
| 200 | 501/4 | 491/4 | 39¾ | 23½ x 25¼ | 45½ x 36 |

All dimensions are in inches.

