

A&D® HC-i Series



Specifications

Internal Resolution:

HC-3 Ki, 6 Ki, 30 Ki: 1/600,000
 HC-15 Ki: 1/750,000

Display:

Seven segment liquid crystal display (LCD)
 Character height: pcs 18.6 mm
 Unit weight: 11.4 mm

Power Source (included):

AC adapter or SLA battery option
 Operating time approximately 80 hours without interface

Memory Items:

99 weight registers

Weight Sensor:

Load cell

Operating Temperature:

14° F to 104° F (-10° C to 40° C)

Dimensions:

Overall (L x W x H): 12.4 x 13 x 5 in (315 x 331 x 126 mm)

Warranty:

Two-year limited warranty

Standard Features

- Sealed removable display unit
- Automatic Counting Accuracy Improvement (ACAI)
- Audible Weighing Assist beeping function (AWA)
- Display function - Hi/OK/Lo
- Accumulation function
- Full-digital calibration function
- Auto power-off function

Options:

- Rechargeable battery
- RS-232C

Part Number/Price

Part #	Model #	Description	Pan Size	Price
112837	HC-3Ki	6 lb x 0.001 lb (3 x 0.0005 kg)	11.8 x 8.3 in (300 x 211 mm)	\$700.00
112838	HC-6Ki	15 lb x 0.002 lb (6 x 0.001 kg)	11.8 x 8.3 in (300 x 211 mm)	\$700.00
112839	HC15Ki	30 lb x 0.005 lb (15 x 0.002 kg)	11.8 x 8.3 in (300 x 211 mm)	\$700.00
112840	HC-30Ki	60 lb x 0.01 lb (30 x 0.005 kg)	11.8 x 8.3 in (300 x 211 mm)	\$700.00

Options/Accessories

Part #	Model #	Description	Price
112841	HC-03i	RS-232C for HC-i	\$77.00
112842	HC-06i	Rechargeable battery pack	\$43.00
97766	TB-163C	AC adapter, 120 V, standard with unit	\$43.00