

Standard Features

Capacity: 3kg-15kg Readability: 0.5g-2g

- IPX8 protection rating
- Front and rear dual display, 0.8 in (20.5 mm)
- Removable stainless steel platform cover
- Fast 0.5 second stabilization time
- SmarText™ interface
- Knife-proof keypad
- · AC adapter and battery included





APPROVALS



Specifications

	V22XWE3T	V22XWE6T	V22XWE15T	
Part#	102771	102772	102773	
List Price	\$518.00	\$518.00	\$518.00	
Capacity	3 kg	6 kg	15 kg	
Resolution	0.5 g	1 g	2 g	
Weigh Units	Kilograms, Pounds, Grams, Ounces, Pound and Ounce			
Operating Modes	Weigh, Checkweigh			
Construction	Stainless steel housing and platform			
Protection Rating	IPX8			
Safe Overload	150% of capacity			
Stabilization Time	<1 second			
Operating Temperature	14° F to 104° F (-10° C to 40° C)			
Pan Size	7.5x 9.5 in (242 x 190 mm)			
Dimensions	(W x D x H) 10.1 x 11.3 x 4.9 in (256 x 288 x 124 mm)			
Weight (Approx.)	8.6 lb (3.9 kg)			
Calibration	Digital external calibration			
Power	Universal AC adapter, 12VDC 0.7A internal rechargeable lead acid battery			
Battery Life	50 hours with 1 hour recharge time			
Warranty	One-year Limited Warranty			
Return Policy	OHAUS Standard Policy - restock fee may apply			

[^]Weighing Chamber

Part Number/Price

Part#	Model#	Description	Price
102771	V22XWE3T	3 kg x 0.5 g	\$518.00
102772	V22XWE6T	6 kg x 1 g	\$518.00
102773	V22XWE15T	15kg x 2g	\$518.00

Options/Accessories

Part#	Model#	Description	Price
33451	3369-10	Polypropylene Maxi-Scoop™ 10 dia x 2.5 in deep (25.4 dia x 6.4 cm deep) with pouring spout, weight 145 g	\$37.00
97250	80250400	Stainless steel scoop 11.9 x 7.4 x 1.7 in (30 x 18.7 x 4.3 cm)	\$62.00
100292	80250954	Stainless steel scoop 17.2 x 11 x 3.4 in (44 x 28 x 8.5 cm)	\$82.00
156237	46001812	Universal AC adapter	\$53.00
156235	46001780	Universal plug set	\$17.00