

**Specifications**

**Cable Fittings:**

(5) nylon 0.187 in-0.312 in (4.7 mm-7.9 mm) cable strain reliefs

**Connectors:**

Electrovert 0.197 in (5.0 mm) miniature two piece connectors. Maximum wire size # 14 AWG; connectors are removable for easy wiring.

**Trimming:**

Individual cell trim, signal trim

**Potentiometers:**

100,000 ohm, 25-turn cermet

**Enclosure:**


Stainless steel NEMA Type 4X, 40 PSI washdown

**Circuit Board:**

6.5 in x 1.5 in (165.1 mm x 38.1 mm) with anti-fungal coating

**Operating Temperature:**

0°F to 122°F (-18°C to 50°C)



**Standard Features**

- Stainless steel, NEMA Type 4X enclosure
- Strain relief cable fittings
- Removable connectors for easy wiring
- Number of cells: Two or four single cells (even number of cells only)
- Any unused channels require modification

**Applications**

- Truck and floor scales
- Limited space installations

**Part Number/Price**

Part #	Description	Price
21165	EL504 signal trim junction box	\$350.00
21296	Board only	\$255.00
165274	Enclosure only	\$150.00

*Note: Do not mix junction box models or use other brands of junction boxes with Rice Lake junction boxes. There is a risk of system instability.*

