

Specifications

Load Cell, NTEP Certified:

IP69K stainless steel and hermetically sealed

Output Impedance:

350 Ω

Maximum Overload:

180 to 200% depending on capacity

Overload Protection:

Five-point, independently adjusted

Cable Length:

34 in or 10 ft

Compensated Temperature Range:

14° F to 104° F (-10° C to 40° C)

Warranty:

Three-year limited warranty (includes water ingress)

Approvals:

NTEP CC 95-072, Class III 5,000 d

Measurement Canada AM-5082, Class III 5,000

Load cell is FM approved





Standard Features

- 304 stainless steel construction
- Five-point overload protection
- Specially designed adjustable support feet provide exceptional traction and will not scratch surfaces
- IP69K, stainless steel hermetically sealed load cell

APPROVALS



Measurement
Canada
Approved



Drawing Dimensions

| 10 in x 10 in | | | |
|---------------|----------------------|----|----------------------|
| A | 4.25 in (107.95 mm) | C | 10 in (254 mm) |
| B | 10 in (254 mm) | C1 | 10.25 in (260.35 mm) |
| B1 | 10.25 in (260.35 mm) | | |
| 12 in x 12 in | | | |
| A | 4.25 in (107.95 mm) | C | 12.0 in (304.8 mm) |
| B | 12.0 in (304.8 mm) | C1 | 12.25 (311.15 mm) |
| B1 | 12.25 (311.15 mm) | | |

Part Number/Price

| Part # | Platform Capacity | Dimensions | Est. Weight | Price |
|--------------------|-------------------------------|-------------------|-------------|------------|
| 10 ft Cable | 34 in Cable | | | |
| 112600 | 106143 5 lb (2.5 kg) | 10 x 10 x 4.25 in | 14 lb | \$1,005.00 |
| 112602 | 106144 10 lb (5 kg) | 10 x 10 x 4.25 in | 14 lb | \$1,005.00 |
| 112604 | 106145 25 lb (12.5 kg) | 10 x 10 x 4.25 in | 14 lb | \$1,005.00 |
| 112606 | 106146 25 lb (12.5 kg) | 12 x 12 x 4.25 in | 17 lb | \$1,085.00 |
| 112608 | 106147 50 lb (25 kg) | 12 x 12 x 4.25 in | 17 lb | \$1,085.00 |
| 112610 | 106148 100 lb (50 kg) | 12 x 12 x 4.25 in | 17 lb | \$1,085.00 |

Options/Accessories

| Part # | Description | Price |
|-----------------|---|--------------------------------|
| N/A | Ball transfer and roller conveyor top | See end of section for details |
| 112044 | 12 in column for IQ plus® 210, CW-90, CW-90X, 480/482 Legend Series, 680 Synergy Series | \$135.00 |
| 112045** | 18 in column for IQ plus® 210, CW-90, CW-90X, 480/482 Legend Series, 680 Synergy Series | \$180.00 |
| 196363 | 12 in column for 882IS/882IS Plus with battery | \$200.00 |
| 196364 | 18 in column for 882IS/882IS Plus with battery | \$245.00 |
| 197482 | 12 in column for 882IS/882IS Plus with power supply (Note: Power supply does not mount to column) | \$135.00 |
| 197484 | 18 in column for 882IS/882IS Plus with power supply (Note: Power supply does not mount to column) | \$180.00 |

** Not recommended for use with scale bases smaller than 12 x 12 in