

Specifications

Capacity:

IGX 150 lb/60 kg x .05 lb/0.02 kg
 IGX 300 lb/150 kg x .1 lb/0.05 kg
 IGB 150 lb/60 kg x 0.05 lb/0.02 kg
 IGB 300 lb/150 kg x 0.1 lb/0.05 kg

Accuracy:

Configurable 1/3,000**, 1/6,000, 1/7,500
 **Legal for Trade setting

Display:

IGX: vacuum fluorescent display (VFD), 25 mm
 IGB: liquid crystal display (LCD), 29 mm

Display Items:

Weight: five-digits, center of zero, tare, checkweighing: over "H," under "L"

Electrical Power:

IGX: 120 V
 IGB: D size batteries or optional AC adapter (batteries not included) 500 hour battery life

Operating Temperature:

23° F to 109° F (-5° C to 40° C)

Warranty:

One-year limited warranty

Approvals:

NTEP CC 05-020, Class III, 3,000 d



Standard Features

- Ability to toggle between lb and kg
- Stainless steel cover with die-cast base
- Checkweighing function
- Configurable display resolution: 1/3,000, 1/6,000, 1/7,500 (NOTE: Legal for Trade setting is 1/3,000)
- 10 PLUs for storing tare, upper limit, lower limit

IGX:

- Display, VFD
- Power, 120 VAC
- Internal buzzer

IGB:

- Display, LCD
- Power, two D-size batteries or optional AC adapter
- Selectable automatic power-off function
- Batteries not included

APPROVALS



Part Number/Price

Part #	Capacity	Platform Dimensions	Est. Weight	Price
IGX				
84989	150 lb (60 kg) x 0.05 lb (0.02 kg)	15.75 x 21.65 x 5.43 in	43 lb	\$895.00
84990	300 lb (150 kg) x 0.1 lb (0.05 kg)	15.75 x 21.65 x 5.43 in	43 lb	\$895.00
IGB				
84991	150 lb (60 kg) x 0.05 lb (0.02 kg)	15.75 x 21.65 x 5.43 in	41 lb	\$795.00
84992	300 lb (150 kg) x 0.1 lb (0.05 kg)	15.75 x 21.65 x 5.43 in	41 lb	\$795.00

Options/Accessories

Part #	Description	Price
75473	AC adapter (IGB only)	\$25.00
86545	Additional operating manual (IGX/IGB)	\$25.00

Drawing Dimensions

A	15.75 in (400 mm)	E	29.06 in (738 mm)
B	21.65 in (550 mm)	F	22.00 in (560 mm)
C	9.84 in (250 mm)	G	33.70 in (856 mm)
D	5.43 in (138 mm)		

