

**Interchangeable Products**

AVERY-WEIGHTRONIX®  
MK29.....

**Specifications**

- Full Scale Output:**  
2.0 mV/V
- Output Resistance:**  
350 (± 3) ohm
- Input Resistance:**  
385 (± 15) ohm
- Material/Finish:**  
Stainless steel
- Temperature:**  
Compensated range  
14°F to 104°F (-10°C to 40°C)  
Operating range  
0°F to 150°F (-18°C to 65°C)
- Seal Type:**  
Environmentally sealed, IP66
- Safe Overload:**  
200% full scale, at center loading point
- Rated Excitation:**  
5- 10 VDC (15 V maximum)
- Total Error:**  
0.02% full scale
- Insulation Resistance:**  
2,000 megohms
- Deflection at Capacity:**  
7.5 kg-100 kg=0.015 in (0.4 mm)
- Cable Length:**  
1.5 m, 3 m, 25 ft
- Cable Diameter:**  
0.200 PVC jacket
- Cable Color Code:**  
Green +Excitation  
Black -Excitation  
Red +Signal  
White -Signal  
Blue +Sense  
Brown -Sense
- Platform Size:**  
15.75 in x 15.75 in
- Warranty:**  
One-year limited warranty
- Approvals:**  
cFMus  
NTEP

**APPROVALS**



**Dimensions**

Picture is a representation of actual product

Rated Capacity	A	B	C	F	G	I	J
<b>kg/mm</b>							
7.5-100	35.0	25.0	15.0	106.0	30.0	14.5	135.0
<b>lb/in</b>							
16.6-220.5	1.378	0.98	0.591	4.173	1.18	0.571	5.31

**Order Information**

Load Rating	Part#	Est. Weight	Price
<b>1.5 m Cable</b>			
7.5 kg	53485	2 lb	\$255.00
10 kg	112374	2 lb	\$255.00
15 kg	53486	2 lb	\$255.00
30 kg	53487	2 lb	\$255.00
50 kg	53488	2 lb	\$255.00
100 kg*	53490	2 lb	\$255.00
<b>3 m Cable</b>			
7.5 kg	111381	2 lb	\$265.00
10 kg	112365	2 lb	\$265.00
15 kg	114132	2 lb	\$265.00
30 kg	114133	2 lb	\$265.00
<b>25 ft Cable Trimmed Outputs</b>			
15 kg	124512	2 lb	\$315.00
30 kg	124513	2 lb	\$315.00

\*Non-NTEP Certified

