

Available in configurations with three or four mounting assemblies. Picture is a representation of actual product.

The ITCM Series utilizes several Rice Lake Weighing Systems components to provide an unmatched level of performance in tank and hopper weighing applications and mechanical scale conversions. The ITCM HE incorporates clevis and unique rod-end ball joint assemblies to reduce the overall length to less than half of the traditional tension cell mounts, while providing correct load alignment. In addition, the load cell is completely electrically isolated from stray currents, which are a major cause of load cell failure. To complete the design, a grounding strap connects the two clevis assemblies to further provide safety to your load cells.



Module with RL20001 HE s-beam load cell. Important: Read "Load Cell Mounting Hardware Safety Guidelines"

Complete Kit Includes

- Three or four ITCM assemblies with RL20001HE stainless steel, welded seal
- · NTEP Certified s-beam load cells
- One JB4SS NEMA Type 4X stainless steel signal trim junction box
- 25 ft of our hostile environment EL147HE SURVIVOR® load cell cable

Standard Features

- · Capacities (per module): 500-5,000 lb (226.8-2,268.0 kg)
- · Clevis mounts with nylon insulating washers
- PTFE-lined rod-end ball joints
- · Load cell is completely isolated from stray currents
- Grounding strap provides alternative path to ground
- Complete package for ease of installation
- · Provides correct load-cell loading even in difficult installations
- Lower overall height compared to other isolated tension assemblies

Applications

- Suspended hoppers and tanks
- · Mechanical scale conversions
- Use as a single module or in multiples

Load Cell Certifications






Stainless Steel, Welded Seal, NTEP Certified Isolated Tension Cell Modules

Load Rating Dimensions - Inches (mm)*

Load Cell Capacity	Α	В	C	D
lb/in				
			1/2-13 UNC	
500	2.68	2.68	5/8-11 UNC	9.50 (ref)
			3/4-10 UNC	
750	2.68	2.68	1/2-13 UNC	9.50 (ref)
750			5/8-11 UNC 3/4-10 UNC	
			1/2-13 UNC	
1,000	2.68	2.68	5/8-11 UNC	9.50 (ref)
1,000			3/4-10 UNC	
			1/2-13 UNC	
1,500	2.68	2.68	5/8-11 UNC	9.50 (ref)
,			3/4-10 UNC	
			1/2-13 UNC	
2,000	2.68	2.68	5/8-11 UNC	9.50 (ref)
			3/4-10 UNC	
2,500	2.68	2.68	5/8-11 UNC	9.50 (ref)
			3/4-10 UNC	``´
3,000	3.37	3.37	3/4-10 UNC	10.00 (ref)
5,000	3.37	3.37	3/4-10 UNC	12.62 (ref)
kg/mm				
			1/2-13 UNC	
226.8	68.1	68.1	5/8-11 UNC	241.3
			3/4-10 UNC	
040.0	00.1	CO 1	1/2-13 UNC 5/8-11 UNC	241.3
340.2	68.1	68.1	3/4-10 UNC	241.3
			1/2-13UNC	
453.6	68.1	68.1	5/8-11 UNC	241.3
400.0	00.1	00.1	3/4-10 UNC	241.0
			1/2-13 UNC	
680.4	68.1	68.1	5/8-11 UNC	241.3
			3/4-10 UNC	
			1/2-13 UNC	
907.2	68.1	68.1	5/8-11 UNC	241.3
			3/4-10 UNC	
1,134.0	68.1	68.1	5/8-11 UNC	241.3
			3/4-10 UNC	
1,360.8	85.6	85.6	3/4-10 UNC	254.0
2,268.0	85.6	85.6e	3/4-10 UNC	320.5



Order Information

Single N	<i>l</i> lodule	Part # (C)	Price
		46599 (1/2-13 UNC)	\$1,435.00
500 lb	226.8 kg	46600 (5/8-11 UNC)	\$1,435.00
		46601 (3/4-10 UNC)	\$1,435.00
		46602 (1/2-13 UNC)	\$1,435.00
750 lb	340.2 kg	46603 (5/8-11 UNC)	\$1,435.00
		46604 (3/4-10 UNC)	\$1,435.00
		46605 (1/2-13 UNC)	\$1,435.00
1,000 lb	453.6 kg	46606 (5/8-11 UNC)	\$1,435.00
		46607 (3/4-10 UNC)	\$1,435.00
		46608 (1/2-13 UNC)	\$1,435.00
1,500 lb	680.4 kg	46609 (5/8-11 UNC)	\$1,435.00
		46610 (3/4-10 UNC)	\$1,435.00
		46611 (1/2-13 UNC)	\$1,435.00
2,000 lb	907.2 kg	46612 (5/8-11 UNC)	\$1,435.00
		46613 (3/4-10 UNC)	\$1,435.00
2,500 lb	1 124 Oka	46614 (5/8-11 UNC)	\$1,435.00
2,50010	1,134.0 kg	46615 (3/4-10 UNC)	\$1,435.00
3,000 lb	1,360.8 kg	46616 (3/4-10 UNC)	\$1,435.00
5,000 lb	2,268.0 kg	46617 (3/4-10 UNC)	\$2,135.00

3-Modu	le Kit	Part # (C)	Price
		46561 (1/2-13 UNC)	\$4,200.00
500 lb	226.8 kg	46562 (5/8-11 UNC)	\$4,200.00
		46563 (3/4-10 UNC)	\$4,200.00
		46564 (1/2-13 UNC)	\$4,200.00
750 lb	340.2 kg	46565 (5/8-11 UNC)	\$4,200.00
		46566 (3/4-10 UNC)	\$4,200.00
		46567 (1/2-13 UNC)	\$4,200.00
1,000 lb	453.6 kg	46568 (5/8-11 UNC)	\$4,200.00
		46569 (3/4-10 UNC)	\$4,200.00
		46570 (1/2-13 UNC)	\$4,200.00
1,500 lb	680.4 kg	46571 (5/8-11 UNC)	\$4,200.00
		46572 (3/4-10 UNC)	\$4,200.00
		46573 (1/2-13 UNC)	\$4,200.00
2,000 lb	907.2 kg	46574 (5/8-11 UNC)	\$4,200.00
		46575 (3/4-10 UNC)	\$4,200.00
2,500 lb	1,134.0 kg	46576 (5/8-11 UNC)	\$4,200.00
		46577 (3/4-10 UNC)	\$4,200.00
3,000 lb	1,360.8 kg	46578 (3/4-10 UNC)	\$4,200.00
5,000 lb	2,268.0 kg	46579 (3/4-10 UNC)	\$6,295.00

4-Modu	le Kit	Part # (C)	Price
		46580 (1/2-13 UNC)	\$5,600.00
500 lb	226.8 kg	46581 (5/8-11 UNC)	\$5,600.00
	-	46582 (3/4-10 UNC)	\$5,600.00
		46583 (1/2-13 UNC)	\$5,600.00
750 lb	340.2 kg	46584 (5/8-11 UNC)	\$5,600.00
		46585 (3/4-10 UNC)	\$5,600.00
		46586 (1/2-13 UNC)	\$5,600.00
1,000 lb	453.6 kg	46587 (5/8-11 UNC)	\$5,600.00
		46588 (3/4-10 UNC)	\$5,600.00
	680.4 kg	46589 (1/2-13 UNC)	\$5,600.00
1,500 lb		46590 (5/8-11 UNC)	\$5,600.00
·		46591 (3/4-10 UNC)	\$5,600.00
		46592 (1/2-13 UNC)	\$5,600.00
2,000 lb	907.2 kg	46593 (5/8-11 UNC)	\$5,600.00
		46594 (3/4-10 UNC)	\$5,600.00
0.50016	1,134.0 kg	46595 (5/8-11 UNC)	\$5,600.00
2,500 lb		46596 (3/4-10 UNC)	\$5,600.00
3,000 lb	1,360.8 kg	46597 (3/4-10 UNC)	\$5,600.00
5.000 lb	2.268.0 kg	46598 (3/4-10 UNC)	\$8,350.00
	,		1

^{*} Load rating is per module