MSI-Clamp On Load Cell



Standard Features

- ETD 150 construction
- Accommodates up to 3/4-inch wire rope size
- IP68
- Larger diameter clamp ons available call for pricing

Options


- Custom sizes available on request
- Pair with an SCT transmitter for basic safety functions

Part Number/Price

Part #	Description	Price
179080	Load Cell Assembly Clamp-On for 3/8 to 1/2 in wire rope	\$675.00
179082	Load Cell Assembly Clamp-On for 9/16 to 3/4 in wire rope	\$800.00
188816	Kit with SCT-2200 for 3/8 to 1/2 in wire rope	\$1,200.00
188817	Kit with SCT-2200 for 9/16 to 3/4 in wire rope	\$1,330.00
Larger diamet	er clamp ons available - call for pricing	

Dimensions

Cable Range	P/N	Α	В	С
3/8 - 1/2	179080	Cable + 1.70	6.00	2.00
9/16-3/4	179082	Cable + 1.67	6.00	2.00



Specifications

Accuracy: 3-5%

Material: 4340 steel, zinc plated

IP Rating: IP68

Cable Color Code: Red + Excitation

Black – Excitation Green + Signal White – Signal

Cable Length:

20 ft. (6m) integral cable with blunt end termination

CRANE SCALES