

## Specifications

### Print Method:

Okidata 320/420: 9-Pin (0.34 mm dia.) serial impact dot matrix  
Okidata 390: 24-Pin (0.20 mm dia.) serial impact dot matrix

### Graphics Resolution:

Okidata 320/420: 240 (H) x 216 (V) DPI maximum (Epson®/IBM®)  
Okidata 390: 360 (H) x 360 (V) DPI maximum (Epson/IBM AGM)

### Print Speed\*\* (cps):

Okidata 320: NLQ: 75; Utility: 300;  
High Speed Draft: 390; Super Speed Draft: 435  
Okidata 390: LQ: 105; Utility: 315; Super Speed Draft: 390 (15 cpi)  
Okidata 420: NLQ95; High Speed Draft: 5p 510;  
Utility: 570, Super 570

### Feed Rate:

5.0 ips

### Emulations:

Okidata 320: Epson EX-PPR II and OKI® Microline®  
Okidata 390: Epson ESC/P2, IBM ProPrinter® and IBM AGM  
Okidata 420: Epson Fx IMB Pro Point Micro

### Interface:

Okidata 320/390/420: IEEE 1284 bidirectional parallel; Windows® 95 plug and play compatible, USB  
Okidata 390: Centronics® and IEEE 1284 bidirectional parallel

### Compatibility:

Windows® XP, 2000, 98/95

### Receive Buffer:

Okidata 320: 28K  
Okidata 390: 23K  
Okidata420: 128K

### Code Pages:

Standard ASCII; Epson character set I and II; IBM character set I, I and All; Code Page 850, 860, 863, 865, 437; BRASCI and ABICOMP

### Resident Fonts:

Okidata 390: LQ: Courier, Letter Gothic, Orator, Prestige, Roman and Swiss/Bold; Utility: Gothic

### Scaleable Fonts:

Okidata 320/420: Courier, Gothic (22-216 pt. in one pt. increments)  
Okidata 390: Courier, Roman and Swiss™ (8-64 pt. in one pt. increments)

### Bar Codes:

Code 39, UPC A, UPC E, EAN 8, EAN 13, Interleaved 2 of 5, Code 128 (A, B, C), PostNet™

### Paper Input:

Single/multi-part, continuous, cut sheet, envelopes, card stock, labels  
Bottom feed with pull tractor option

### Number Of Copies:

Okidata 320: Six  
Okidata 390: Four  
Okidata 420: Six

### Tractor:

3.5 to 10.5 in wide (88.9-266.7 mm wide), rear push with zero tear and paper park (optional)

### Paper Thickness:

Rear feed: 0.014 in (0.35 mm) maximum;  
Bottom feed\*\*\*: 0.017 in (0.43 mm) maximum, expandable to 0.01 in (.78 mm)

### Paper Path:

Bottom, rear or top

### Paper Weight:

Cut sheet 16 to 24 lb (7.2 to 10.8 kg), Continuous 16 to 20 lb (7.2 to 9.1 kg)



Okidata 320 Turbo Microline

## Standard Features

- Vertical tabs
- Long-lasting, self-inking ribbon cartridge
- Bit image graphics for plotting charts, graphs and drawings
- Full ASCII character set
- Friction and adjustable pin feed paper handling

## Okidata 320/420 Turbo\*:

- Nine-pin, long-life print head (parallel input)
- Centronics®-compatible parallel interface
- Near letter-quality printing at 63 characters per second
- 80 columns with standard characters, 160 columns with condensed characters
- Front access panel for quick and easy control of type size, print quality and other frequently used printer functions

## Okidata 390 Turbo:

- 24-pin, long-life print head
- Supports Windows® 95/98
- Superior, professional quality printer
- Auto-tear accurately positions continuous forms for a clean tear at the perforation
- Three scaleable fonts  
\* Use with CBI

## Specifications Continued

### Electrical:

115 VAC, 230 VAC

### Power Consumption:

Okidata 320: Operating: 100 W  
Okidata 390: Operating: 43 W Idle: 10 W  
Okidata 420: 20,000 hours

### Reliability (MTBF):

10,000 hours (25% duty cycle, 35% page density)

### Print Head Life:

200 million characters

### Ribbon Type:

Black cartridge (2 million characters nominal life)

### Operating Temperature:

40° F to 104° F (4° C to 40° C) at 25% to 80% relative humidity

### Overall Size:

Okidata 320 and 390: (W x D x H): 15.7 x 13.6 x 4.6 in (398.8 x 345.4 x 116.8 mm)  
Okidata 420: 15.7 x 13.6 x 6.0 in

### Est. Ship Weight:

Okidata 320: 16 lb (7.2 kg)  
Okidata 390: 15 lb (6.8 kg)  
Okidata 420: 17 lb (7.7 kg)

### Warranty:

320/390: One-year limited warranty (includes print head)  
420: Three-year limited warranty

\*\* Print speeds apply to all pitches (10, 12, 17.1, and 20 cpi)

\*\*\* Requires optional pull tractor (part #41224)

# Okidata 320/390/420 Turbo

Microline Printers

## Part Number/Price

Part #	Description	Est. Weight	Price
126438	Okidata 320 Microline Turbo printer with RS-232 interface, 115 VAC	16 lb	\$960.00
41222	Okidata 320 Microline printer with parallel/USB interface, 115 VAC	16 lb	\$790.00
41223	Okidata 320 Microline printer with parallel/USB interface, 230 VAC	16 lb	\$790.00
75106	Okidata 390 Microline Turbo printer with parallel/USB interface, 115 VAC	15 lb	\$810.00
102959	Okidata 420 Microline Turbo printer with parallel/USB interface, 115 VAC	16 lb	\$825.00

## Options/Accessories

Part #	Description	Price
<b>Cables</b>		
15547	Blunt end, 25-Pin D-sub male RS-232 serial interface cable (Rice Lake indicators)	\$65.00
<b>320/420 Turbo Options and Accessories</b>		
41224	Pull tractor kit for bottom-fed continuous forms and push/pull operation	\$98.00
20239	RS-232 input board, older revisions	\$170.00
121454	RS-232 option board, 320 Rev 10	\$170.00
20664	Ribbon cartridge black, 320 and 390	\$8.00
132249	Ribbon cartridge for 420	\$8.00
21226	Protective dust cover	\$65.00
41363	Additional operating manual	\$35.00
75107	Cut sheet feeder	\$490.00
<b>390 Turbo Options and Accessories</b>		
75107	Cut sheet feeder	\$490.00
20239	RS-232 option board, older version	\$170.00
41224	Pull tractor kit for bottom-fed continuous forms and push/pull operation	\$98.00
20664	Ribbon cartridge black	\$8.00

*Standard unit has pins on roller for holes on paper*

*Interfaces to: Rice Lake indicators with a serial port screw terminal connection*