

# GoDEX® DT2x

Label Printer

PRINTERS



## Standard Features

- Auto language emulations GEPL, GZPL
- Free GoLabel design software for EZPL
- 203 dpi (8 dot/mm)
- Drop-in media loading
- USB or RS-232 interface
- Plain, gap label, black, mark or fanfold label
- Label length detection
- Direct thermal
- Model G500- direct thermal/thermal transfer
- 32 Bit CPU
- Serrated tear bar

## APPROVALS



## Specifications

### Print Speed:

Up to 7 ips

### Print Length:

Minimum: 0.16 in  
Maximum: 68 in

### Print Width:

2.12 in

### Media:

Continuous form, gap labeling, black mark sensing and punched sensing  
Label roll O.D. max: 5.0 in

### Core:

1 in, 1.5 in  
Thickness: 0.06 mm to 0.20 mm

### Printer Language:

GZPL or GEPL, EZ PL auto switch

### Resident Fonts:

11 resident alphanumeric fonts (included OCR A and B) are expandable eight times horizontally and vertically. All bit mapped fonts in eight orientations

### Bar Codes:

Code 39, Code 93, Code 128 (subset A, B, C), UCC/EAN - 128 K-Mart, UCC/EAN - 128, UPC A/E (add on 2 and 5), 2 of 5, EAN 8/13 (add on 2 and 5.)  
Codabar, Post Net, EAN 128, DUN 14, MaxiCode, HIBC, Plessey, Random Weight, Telepen, FIM, China Postal Code, RPS 128, PDF 417, Datamatrix code, QR Code

### Dimensions:

(L x H x W): 8.58 x 6.77 x 3.94 in  
(218 x 172 x 100 mm)

### Interfaces:

Baud rate 4800 to 115200; DB9  
USB port U2.0 (B-type)  
Ethernet (RJ-45)

### Memory:

8 MB flash

### Power:

Auto switching 100/240 VAC 50/60 Hz

### Environment:

Operation: 41° F to 104° F (5° C to 40° C)  
Storage: -4° F to 122° F (-20° C to 50° C)

### Humidity:

Operation: 30 to 85 % non-condensing, free air  
Storage: 10 to 90 % non-condensing, free air

### Approvals:

CE (EMC), FCC Class A, CB, CUL, CCC

### Warranty:

Two-year limited warranty

## Part Number/Price

Part #	Description	Est. Weight	Price
167515	DT2x 2 in direct thermal, time and date 10/240 VAC printer	2.65 lb	\$345.00
167626	Label peeler, black	—	\$39.00
167627	Cutter, black	—	\$200.00
107532	Print head	—	\$110.00
<b>Cables</b>			
41276	6 ft serial cable DB9 M to blunt end (Rice Lake indicators)	—	\$65.00
79074	USB-A (male) to USB-B (male) cable, 6 ft	—	\$30.00
64661	6 ft serial cable DB9 M to 8-Pin DIN	—	\$65.00
64660	6 ft serial cable DB9 M to DB9 male	—	\$65.00
Consult	Custom RS-232 serial cable	—	\$100.00

## Options/Accessories

Part #	Description	Price
38941	Cleaning pen for open print head printers 12/box	\$57.00
35664	Cleaning cards, (W x L) 4x 6 in for RL-42DT and RL-42TT	\$50.00
111085	Power supply, printers	\$158.00
15438	Power cord, detachable	\$17.75
193466	Real-time clock for DT4xW	\$20.00
<b>Label Stock/Ribbon</b>		
110347	Direct thermal, (W x L) 2.25 x 1.25 in, 5 in diameter with perf., 2,100/roll	\$12.80/roll
40332	Direct thermal, (W x L) 2.25 x 2 in, 5 in diameter with perf., 1,445/roll	\$14.25/roll
110348	Direct thermal, (W x L) 2.25 x 3 in, 5 in diameter with perf., 950/roll	\$13.50/roll
110349	Direct thermal, (W x L) 2.25 x 4 in, 5 in diameter with perf., 700/roll	\$10.80/roll
65617	Direct thermal, (W x L) 2.25 x 4.5 in, 5 in diameter with perf., 600/roll	\$14.60/roll
110346	Direct thermal, (W x L) 1.20 x 0.85 in, 5 in diameter with perf., 2710/roll	\$8.25/roll
47761	Direct thermal, (W x L) 2.5 x 121 ft, continuous 12 rolls/case	\$66.00/case

www.ricelake.com | Phone: 800-472-6703

RICELAKE