

Minebea Intec IS Series

Weighing Platforms



Standard Features

- The standard RS-485 interface is X-bus compatible. An RS-232C interface is optionally available. Power requirements range from 10.6 VDC to 30 VDC.
- At the touch of the unique ISO TEST key, the IS platform calibrates and adjusts itself automatically using a built-in calibration weight
- High internal resolution guarantees reliable weight readouts
- Weighing results: up to 50 times/second
- All scales come standard with stainless steel load plate (wrap-around design optional). High IP rating for ideal protection.
- Internal Calibration (ISEDE and ISIGG models only)

Accessories and Options

- A complete selection of options and accessories are available, including interfaces, cables and connectors, power supplies, mechanical accessories, software and mechanical security devices

Specifications

Indicator Connectivity:

Combics UV1

Models Sensing:

Force motor cell

Cable Length:

6 meters

Stability:

Weight stabilizes 1.5 second

Power Requirements:

10.6 VDC to 30 VDC supplied by external power
Supply, battery pack or Combics IS indicator

Weighing Design:

Electro magnetic

Indicators Options:

Combics UVI models

Construction:

Stainless steel platforms
Die-cast or galvanized base construction (model dependent)

Ingress Protection Rating:

BBD/DCP: IP54
EDE: IP65
IGG: IP67

Warranty:

Two-year limited warranty
Accessories: One-year limited warranty

Part Number/Price

RLWS PN	Minebea PN	Platform Size	# Load Cells	Capacity	Readability	Capacity	Readability	Est. Weight	Price
174127	ISBBP-06-H	4.5 in Ø	1	1.6 lb	0.00002	0.62 kg	0.001 g	19 lb	\$3,285.00
174128	ISBBP-3-H	7.1 in x 7.1 in	1	6.8 lb	0.00002	3.1 kg	0.01 g	19 lb	\$2,868.00
174129	ISBBP-6-H	7.1 in x 7.1 in	1	13.7 lb	0.00002	6.2 kg	0.01 g	19 lb	\$3,650.00
102003	ISDCS-16-H	15.8 in x 11.8 in	1	35 lb	0.0002	16 kg	0.1 g	41 lb	\$4,584.00
102004	ISDCS-35-H	15.8 in x 11.8 in	1	75 lb	0.0002	34 kg	0.1 g	41 lb	\$5,626.00
102005	ISEDE-64-SV1	15.8 in x 11.8 in	1	141 lb	0.002	64 kg	1 g	41 lb	\$5,470.00
102006	ISEDE-64-HV1	15.8 in x 11.8 in	1	141 lb	0.0002	64 kg	0.1 g	41 lb	\$7,504.00
102008	ISIGG-150-HV1	32 in x 24 in	1	330 lb	0.002	150 kg	1 g	185 lb	\$7,806.00
102009	ISIGG-300-HV1	32 in x 24 in	1	660 lb	0.005	300 kg	2 g	185 lb	\$7,806.00
Special Order									
102010	ISEDE-16-DS1	15.8 in x 11.8 in	1	35 lb	0.00002	16 kg	0.01 g	41 lb	Consult
102012	ISIGG-150-DS1	32 in x 24 in	1	330 lb	0.0002	150 kg	0.1 g	185 lb	\$8,377.00
102013	ISIGG-300-DS1	32 in x 24 in	1	660 lb	0.0005	300 kg	0.2 g	185 lb	\$8,826.00

Options/Accessories

RLWS PN	Minebea PN	Description	Price
Consult	-	Interface Mode (RS-485/422) required with Combics II indicators	Consult
Consult	-	DC power supply to weigh platform	Consult
Consult	YCC05_001M5	Cable, 25-Pin to 9-Pin D sub, cable for PC	Consult
32636	YRB06Z	External rechargeable battery pack - approx 29 hours of operation	\$755.00

Indicators

RLWS PN	Description	Comments	Price
115668	CAISL1-UV1	Combics 1 indicator for IS base, IP44	\$1,601.00
115670	CAISL2-UV1	Combics 2 indicator for IS base, IP44	\$1,863.00
Consult	CAISL3-UV1	Combics 3 indicator for IS base, IP44	\$2,121.00
115671	CAIS1-UV1	Combics 1 indicator for IS base, IP69K	\$1,757.00
115673	CAIS2-UV1	Combics 2 indicator for IS base, IP69K	\$2,123.00
115674	CAIS3-UV1	Combics 3 indicator for IS base, IP69K	\$2,508.00