

Minebea Intec Combics 1

Digital Weight Indicator



Application Note:

Combics 1 indicator is designed for use with both Combics, IF and IS series platforms. However, various accessories may differ and are application dependent.

Standard Features

- IP protection rating, IP44, IP69K
- Amber backlit LCD display, 0.8 in
- External calibration routine
- RS-232C
- On/Off, Zero, Tare, Print/Data Key
- Function keys for: Gross/net toggle; three-way unit toggle; 10X higher resolution toggle
- Automatic tare feature
- One scale connection

Part Number/Price

RLWS PN	Minebea PN	Description	Est. Weight	Price
102396	CAISL1-U	IP44 protection rated	7.5 lb	\$1,101.00
102398	CAIS1-U	IP69K protection rated	7.5 lb	\$1,458.00
115668	CAISL1-UV1	IP44, controller for IS base	7.5 lb	\$1,601.00
115671	CAIS1-UV1	IP69K, controller for IS base	7.5 lb	\$1,757.00

Options/Accessories

RLWS PN	Minebea PN	Description	Price
105607	YDH02CISUS	Wall mount bracket	\$77.00
171727	YDH12CWSUS	Bench mount bracket	\$77.00
156440	YDH01CWSUS	Post mount assembly for 10 x 10 in platforms, 13 in high	\$195.00
156441	YDH02CWSUS	Post mount assembly for 12 x 12 in platforms, 19 in high	\$210.00
156442	YDH03CWSUS	Post mount assembly for 18 x 18 in platforms, 29 in high	\$241.00
103049	YAS02MI	24 V industrial power supply	\$198.00
162640	YD002C-ETH	Ethernet TCP/IP	\$789.00
155826	YD002C-AO	Analog output, 0-20 mA, 4-20 mA, 0-10 V	\$789.00
Cables			
155804	YCC05-001M2	RS-232 9/25-Pin D-Sub female, 1.5 m, IP44	\$103.00
155805	YCC01-USBM2	RS-232 to USB connector, 2 m IP44	\$260.00
155806	YCC02-D25F6	RS-232 open to 25 D-Sub female	\$260.00
193048	YDC01SW	Dust cover pack of two	\$76.00

Specifications

Load Cell Connection:

4 or 6 wire

Excitation Voltage:

9V

Power Requirements:

120-240 VAC, 17 W/23 VA maximum

Housing:

AISI 304 stainless steel

Dimensions:

(W x D x H): 11.9 x 7.4 x 3.5 in

Operating Temperature:

14° F to 104° F (-10° C to 40° C)

Net Weight:

5 lb

Warranty:

Two-year limited warranty

Accessories: One-year limited warranty