

# 720i™ Series

Programmable Weight Indicator/Controller



## Standard Features

- LCD display size: panel mount (3.8 in x 1.2 in), universal (5.3 in x 1.5 in)
- Four softkeys
- Truck in/out, 1,000-ID memory (PCE software version)
- 32 setpoints, 26 configurable types (batch software version)
- Process control engine ProAction PCE define conditions and actions
- Data storage onboard, ProAction DBE user-defined
- Eight digital I/O (expandable)
- One option slot for pluggable options
- 20 auxiliary print formats
- Time & date
- Audit trail tracking and alibi storage
- Peak hold
- Rate of change
- Accumulator
- Multi-range/interval
- Local/remote
- Two full duplex serial ports
- One PS/2 keyboard port
- Header for fiber optic, Ethernet or USB
- Configurable with Revolution® software



Panel Mount



CPU Enclosure

## Specifications

### Power:

Line voltages: 100–240 VAC  
Frequency: 50–60 Hz  
DC voltages: 12–24 VDC  
Power consumption: 25 W

### Excitation Voltage:

10 VDC, 16 x 350Ω or 32 x 700Ω load cells

### Analog Signal Input Range:

-10 mV to +45 mV

### Analog Signal Sensitivity:

0.3 μV/graduation minimum at 7.5 Hz  
1.0 μV/graduation recommended

### A/D Sample Rate:

7.5 to 960 Hz, software selectable

### Resolution:

Internal: 8 million counts/8,000,000 23 bit  
Display: 1,000,000

### System Linearity / PI Rating:

±0.01% full scale

### Digital I/O:

Eight channels on CPU board;  
optional 24-channel I/O

### Communication Ports:

Two ports on CPU board support up to 115,200 bps  
Port 2: Full duplex RS-232 with handshaking  
Port 4: Full duplex RS-232, simplex 20mA  
Optional dual-channel serial expansion boards  
Channel A: RS-232, RS-485, 20 mA  
Channel B: RS-232, 20 mA

### Display:

Panel Mount: 3.8 in x 1.2 in (96 mm x 30 mm)  
Universal: 5.3 in x 1.5 in (133 mm x 39 mm)  
240 x 64 pixel, Transflective LCD with adjustable contrast

### Keys/Buttons:

Ten-key (panel mount) membrane panel  
22-key (universal) membrane panel tactile feel  
Optional keyboard connection supported

### Temperature Range:

Certified: 14°F to 104°F (-10°C to 40°C)  
Operating: 14°F to 122°F (-10°C to 50°C)

### Weight:

Universal enclosure: 9.5 lb (4.3 kg)  
Panel Mount enclosure: 8.5 lb (3.9 kg)

### Rating/Material:

NEMA Type 4X/IP66, stainless steel

### Warranty:

Two-year limited warranty

### EMC Immunity:

EN 50082 Part 2 IEC EN 61000-4-2, 3, 4, 5, 6, 8,  
and 11

### Approvals:

NTEP CC 08-022, Class III/IIL 10,000d  
Measurement Canada AM-5677C  
Class III/IILHD 10,000d  
CE Marked  
UL/cUL Listed (universal)  
UL/cUL Recognized (panel mount)

## Approvals



Measurement  
Canada  
Approved



# 720i™ Series

Programmable Weight Indicator/Controller

## Part Number/Price

Part #	Description	Est. Weight	Price
<b>PCE Software</b>			
101230 †	720i Universal, 115 VAC	12 lb	\$1,325.00
103459 ††	720i Universal, 115–230VAC, CE	12 lb	\$1,325.00
107708*	720i Universal, 12–24VDC	12 lb	\$1,425.00
101229**	720i Panel Mount, 115–230VAC	12 lb	\$1,325.00
119116**	720i Panel Mount, 115–230VAC, CE	12 lb	\$1,325.00
107710*	720i Panel Mount, 12–24VDC	12 lb	\$1,425.00
<b>Batch Software</b>			
115447 †	720i Universal, 115 VAC	12 lb	\$1,325.00
115448 ††	720i Universal, 115–230VAC, CE	12 lb	\$1,325.00
115449**	720i Panel Mount, 115–230VAC	12 lb	\$1,325.00

\*DC/DC converter installed option, not UL approved

\*\*Power cord sold separately



† US plug (NA) - Type B




†† Euro Plug - Type E

## Options/Accessories

Part #	Description	Price
<b>Option Cards</b>		
67601	Digital I/O, 24-channel	\$285.00
67602	Analog output: selectable 0-10 V, 0-20 mA	\$310.00
67604	Serial, dual channel	\$335.00
93245	USB Port (PC connection only-replaces serial port 2)	\$175.00
<b>Network Cards</b>		
77142	Ethernet TCP/IP Port (replaces serial port 2)	\$400.00
71986	Ethernet TCP/IP module (installed in option slot)	\$400.00
108671	Wireless LAN Card 802.11 A/B (replaces serial port 2)	\$570.00
87803	EtherNet/IP®	\$800.00
68539	Remote I/O interface	\$675.00
68540	Profibus® DP interface	\$675.00
68541	DeviceNet™ interface	\$675.00
<b>Hardware</b>		
15436	Power cord for panel mount NEMA Type 5-15 plug	\$17.00
105382	Power cord for panel mount CEE 7/7 plug	\$17.00
19369	Start/stop switch box	\$395.00
83569	Clear protective overlay (package of five)	\$75.00
118975	Panel mount kit, for universal	\$175.00
101923	Remote relay box, does not include relay	\$235.00
<b>Manuals &amp; Software</b>		
103121	Installation manual	\$25.00
104033	720i toolkit CD	\$35.00
107622	720i ProAction Simulator CD	\$295.00
<b>Primary Component Parts</b>		
106788	CPU board assembly with PCE firmware	\$825.00
195388	CPU board assembly with batching firmware	\$825.00
101244	LCD Display (panel mount) transfective	\$150.00
102888	LCD Display (universal) transfective	\$150.00
101239	Display board (includes display for panel mount)	\$400.00
102887	Display board (w/o display for universal)	\$300.00
67613	AC power supply 100-240 nominal, 25 watt	\$150.00
132791	DC/DC power supply 12-24VDC nominal, 25 watt	\$195.00
101256	Switch membrane for panel mount	\$65.00
101257	Switch membrane for universal	\$65.00

To have your option factory installed, please specify when placing your order.




### 720i Panel Mount Display Dimensions

A	7.36 in (187 mm)	D	2.45 in (62 mm)	G	6.12 in (155 mm)
B	1.60 in (41 mm)	E	3.88 in (99 mm)		
C	0.59 in (15 mm)	F	0.62 in (16 mm)		

### 720i Panel Mount CPU Enclosure

(L x W x H): 12.75 x 6.05 x 2.14 in (324 x 154 x 5 mm)



### 720i Universal Dimensions

A	10.50 in (267 mm)	D	0.44 in (11 mm)	G	5.25 in (133 mm)
B	7.25 in (184 mm)	E	3.51 in (89 mm)		
C	9.66 in (245 mm)	F	2.31 in (59 mm)		

INDICATORS / CONTROLLERS

www.ricelake.com | Phone: 800-472-6703

RICE LAKE