

VALVE CENTERS CHART

FOR FLAT GAUGES ILLUSTRATED ON PAGES 18 AND 19

- The center-to-center dimensions indicated in the charts are the minimum distances obtainable between valve centers for the corresponding gauge and valves.
- Charts apply to standard Rigid gauge connection 1/2" NPT Female.
- For optional 3/4" connection, consult Ernst Flow Industries for corresponding valve center dimensions.

NOTE: For Steel Valves that incorporate Threaded Union Gauge Connections (Models EFI 323, 324, 325, 326, 423, 424, 425, 426, 67-H, 67-L) in either the standard 1/2" or optional 3/4" NPT Female, consult Ernst Flow Industries for corresponding valve center dimensions.

Gauge Type and Model			Number of Sections	VISIBLE GLASS (Dimensions in Inches)	Distance Between Valve Centers (Dimensions in Inches) Models 331,332, 333,334,335, 336,433,434, 435,436
Reflex	Transparent				
EFI S	EFI ST	EFI WT			
EFI S-1100J	EFI ST-1200J	EFI WT-10J	1	3-3/4	8-3/8
EFI S-1101J	EFI ST-1201J	EFI WT-11J	1	4-3/4	9-3/8
EFI S-11002	EFI ST-1202J	EFI WT-12J	1	5-3/4	10-3/8
EFI S-1103J	EFI ST-1203J	EFI WT-13J	1	6-3/4	11-3/8
EFI S-1104J	EFI ST-1204J	EFI WT-14J	1	7-7/8	12-1/2
EFI S-1105J	EFI ST-1205J	EFI WT-15J	1	9-1/8	13-3/4
EFI S-1106J	EFI ST-1206J	EFI WT-16J	1	10-1/4	14-7/8
EFI S-1107J	EFI ST-1207J	EFI WT-17J	1	11-7/8	16-1/2
EFI S-1108J	EFI ST-1208J	EFI WT-18J	1	12-5/8	17-1/4
EFI S-1123J	EFI ST-1223J	EFI WT-23J	2	15	19-5/8
EFI S-1124J	EFI ST-1224J	EFI WT-24J	2	17-1/4	21-7/8
EFI S-1125J	EFI ST-1225J	EFI WT-25J	2	19-3/4	24-3/8
EFI S-1126J	EFI ST-1226J	EFI WT-26J	2	22	26-5/8
EFI S-1127J	EFI ST-1227J	EFI WT-27J	2	25-1/4	29-7/8
EFI S-1128J	EFI ST-1228J	EFI WT-28J	2	26-3/4	31-3/8
EFI S-1145J	EFI ST-1245J	EFI WT-35J	3	30-3/8	35
EFI S-1146J	EFI ST-1246J	EFI WT-36J	3	33-3/4	38-3/8
EFI S-1147J	EFI ST-1247J	EFI WT-37J	3	38-5/8	43-1/4
EFI S-1148J	EFI ST-1248J	EFI WT-38J	3	40-7/8	45-1/2
EFI S-1166J	EFI ST-1266J	EFI WT-46J	4	45-1/2	50-1/4
EFI S-1167J	EFI ST-1267J	EFI WT-47J	4	52	56-5/8
EFI S-1168J	EFI ST-1268J	EFI WT-48J	4	55	59-5/8
EFI S-56J	EFI ST-56J	EFI WT-56J	5	57-1/4	61-7/8
EFI S-57J	EFI ST-57J	EFI WT-57J	5	65-3/8	70
EFI S-58J	EFI ST-58J	EFI WT-58J	5	69-1/8	73-3/4
EFI S-67J	EFI ST-67J	EFI WT-67J	6	78-3/4	83-3/8
EFI S-68J	EFI ST-68J	EFI WT-68J	6	83-1/4	87-7/8
EFI S-77J	EFI ST-77J	EFI WT-77J	7	92-1/8	96-3/4
EFI S-78J	EFI ST-78J	EFI WT-78J	7	97-3/8	102
EFI S-87J	EFI ST-87J	EFI WT-87J	8	105-1/2	110-1/8
EFI S-88J	EFI ST-88J	EFI WT-88J	8	111-1/2	116-1/8
EFI S-97J	EFI ST-97J	EFI WT-97J	9	118-7/8	123-1/2
EFI S-98J	EFI ST-98J	EFI WT-98J	9	125-5/8	130-1/4

ORDERING GUIDELINES

We want to process your orders as quickly as possible.

To ensure your order is being processed promptly and efficiently, please specify the following:

1. Quantity.
2. EFI Model.
3. Size.
4. Material. (It is especially important to specify metal desired, when ordering products constructed of metal.)
5. Give a brief description of the Ernst Flow Industries products desired and provide a page number.