

CARBON STEEL GAUGES (OFFSET PATTERN DESIGN)

CARBON STEEL GAUGE VALVE WITH STAINLESS STEEL TRIM

AUTOMATIC

*For Steam Pressures up to 300 PSI @ 422°F

- For Liquid Level Pressures up to:
600 PSI @ 100°F
345 PSI @ 400°F
- Graphite washer for:
5/8" glass - 39/64" x 1-1/16" x 3/8"
3/4" glass - 47/64 x 1-1/8" x 3/8"
- Rods 2-1/2" shorter than centers
- Glass 1-3/8" shorter than centers

Also available in Stainless Steel construction.

- 1/2" NPT Vent and Drain

MODEL		Size of NPT Connection	Size of Glass O.D.
Hand Wheel	Lever		
EFI 203J	EFI 204J	1/2"	5/8"
EFI 205J	EFI 206J	3/4"	3/4"

NOTE: Important...Specify if valves are to be used for steam service. Steam and Liquid Level pressure ratings stated are for tubular glass use only.



WARNING: For use with PROCESS SATURATED STEAM APPLICATIONS ONLY.

Carbon Steel Gauge Valves ARE NOT TO BE USED WITH SUPERHEATED STEAM.

CARBON STEEL GAUGE VALVE WITH STAINLESS STEEL TRIM

AUTOMATIC

*For Steam Pressures up to 300 PSI @ 422°F

- For Liquid Level Pressures up to:
600 PSI @ 100°F
345 PSI @ 400°F
- Graphite washer for:
5/8" glass - 39/64" x 1-1/16" x 3/8"
3/4" glass - 47/64 x 1-1/8" x 3/8"
- Rods 2-1/2" shorter than centers
- Glass 1-3/8" shorter than centers

Also available in Stainless Steel construction.

- 1/2" NPT Vent and Drain

MODEL		Size of NPT Connection	Size of Glass O.D.
Hand Wheel	Lever		
EFI 243J	EFI 244J	1/2"	5/8"
EFI 245J	EFI 246J	3/4"	3/4"

★ Operating pressures and temperatures are subject to the limitations of the tubular gauge glass and washer composition...consult with Ernst Flow Industries for gauge glass ratings.



WARNING: For use with PROCESS SATURATED STEAM APPLICATIONS ONLY.

Carbon Steel Gauge Valves ARE NOT TO BE USED WITH SUPERHEATED STEAM.

NOTE: Important...Specify if valves are to be used for steam service. Steam and Liquid Level pressure ratings stated are for tubular glass use only.