



Be Right™



5500 Clark DO Sensors

Replaceable Membrane Cartridge

Model 5500-series dissolved oxygen oxygen sensors feature a replaceable cartridge, simplifying the delicate and time-consuming task of installing a new membrane. Each cartridge assembly includes a pre-installed,

semi-permeable membrane, electrolyte, and electrodes.

Rugged, Foul-Resistant Membrane

An extremely durable 50 micron thick hydrophobic membrane ensures that the D.O. sensor resists fouling and withstands the harsh environments found in wastewater treatment plants.

Complete Encapsulation

Fully-encapsulated construction protects the sensor's built-in electronics from moisture and humidity problems, extending the working life of the sensor.

Versatile Mounting Styles

The handrail and flotation unique stainless steel swivel/pivot/pipe clamp assembly, enabling easy sensor positioning and removal from the process. The flotation hardware has a ball float assembly that continually bobs up and down to gently scrub the sensor membrane. The submersion hardware enables submerging the sensor to a desired depth in the basin.

Part Number	Tagging	Cable Length	Mounting	Connector	USD Price
276G1200					Contact Hach
5500A1020-001					Contact Hach
276G1206					Contact Hach
5540D0A	None	15	Submersion	Metal M.S. plug	Contact Hach
60A2053					Contact Hach
276M1210					Contact Hach
5H0675					Contact Hach
5500F1008-003					Contact Hach
5540D0A0A33N	None	33	Submersion	Metal M.S. plug	Contact Hach
276G1221-115					Contact Hach
76A9902					Contact Hach
5540D0C	None	15	Submersion	Plastic M.S. plug	Contact Hach

Part Number	Tagging	Cable Length	Mounting	Connector	USD Price
5540D0A0A75N	None	75	Submersion	Metal M.S. plug	Contact Hach
1000F3293-007					Contact Hach
MH276J00F					Contact Hach
MH378W4PZ					Contact Hach
276G1230					Contact Hach
76G9912					Contact Hach
1H1201					Contact Hach
5550D0A	None	15	Union	Metal M.S. plug	Contact Hach