LARGE IC CUSHION

PAPER ROLL SPECIAL



PAPER, HANDLED

- ▶ 12000 lb. Capacity
- ► Enhanced Dust & Debris Filtration
- ► Specialized Counterweight
- ► 20% More Fuel Efficient Than Previous Model



8FGC55U-PRS

PAPER ROLL HANDLING, PERFECTED

THE TOYOTA PAPER ROLL SPECIAL FORKLIFT. The product:

heavy, awkward, easily damaged. The environment: dusty, dirty, did we mention dusty? Paper handling presents exacting demands. The Paper Roll Special meets them, safely and efficiently. Equipped to stack and maneuver heavy paper rolls, it's the perfect solution for paper mills, printing plants, newspaper production and similar applications. Paperwork? Done.

PAPER ROLL SPECIAL ADVANTAGES

➤ SYSTEM OF ACTIVE STABILITY™ (SAS)

automatically detects potentially unsafe conditions and engages additional safety features for increased operator protection and reduced product and forklift damage

- ► CLAMP RELEASE INTERLOCK option helps prevent accidental release of clamp
- ► AUTOMATIC CLAMP LEVELING positions clamp vertical to paper roll, improving efficiency and productivity and limiting product damage
- ► POWERFUL 3.7 LITER, 4-CYLINDER TOYOTA-BUILT ENGINE is designed to increase productivity and fuel efficiency, particularly in a 24/7 paper mill
- ► SHORTENED WHEELBASE, LOAD DISTANCE & RIGHT-ANGLE STACKING RADIUS for greater maneuverability
- ► COMPACT COUNTERWEIGHT for additional maneuverability



- ► LARGE RADIATOR & COOLING FAN handle damp, humid paper- and pulp-processing environment
- ► ENGINE & RADIATOR FILTRATION SYSTEMS are designed to keep out excess dust and debris common in paper-handling applications





WHEELBASE LOAD CENTER **CAPACITY** 12000 LBS. 70.5 IN. 24 IN. **INDUSTRIES** Paper STANDARD FEATURES DURABILITY • Control Area Network (CAN-bus) • Moisture-resistant electric connectors • Anti-restart ignition key switch · Stamped steel engine hood communication High cooling capacity radiator • Wide Visible Full-Free Lift Three Low-maintenance battery Radiator screen Stage Mast (FSV) • Large-capacity engine cooling fan • External hydraulic oil cooler • Fully-stamped steel side panels • 8" cyclone air cleaner Full-floating front axle • Plate-iron front fenders **SUPPORT** System of Active Stability[™] (SAS) Key lowering interlock • Key off/headlight off system • Operator Presence Sensing System (OPSS) Electric horn Speed control • Bolt-on overhead guard · Neutral start safety switch **PERFORMANCE** • EPA/CARB-certified engine LCD Multi-Function Display - includes: - Engine oil pressure warning light • Toyota 3.7 liter, 4-cylinder, OHV gasoline - Data log, fuel, and operation information - OPSS activation light engine (1FS) w/ QR Code output - Parking brake indicator · Distributorless ignition system - SAS/OPSS warning light - Master warning, wheel, direction, and • Treaded cushion tires (front & rear) • Alternator with built-in regulator (60A) mast tilt indicators · Automatic clamp leveling • Automatic transmission with oil cooler - Various hour meters • UL-approved model type "LP" - Engine coolant temperature gauge · Electric shift control • Full-floating powertrain - Fuel gauge (gasoline only) • Hydraulic system tuned for clamping LED headlights - Check engine light attachments **ERGONOMICS** Dash-mounted instrument display • 12"-long dual operator assist grips • Oversized cup holder • 11.8"-dia., 2-spoke steering wheel · Heavy-duty non-slip rubber floor mat · Non-cinching seatbelt • Load-sensing power steering Load-sensing power steering Low, wide entry steps Integrated headlight & turn signal lever

- · Cowl-mounted hydraulic control levers with rubber boot covers
- Vinyl 4-way adjustable full-suspension seat
- Double action parking brake (hand)

SERVICEABILITY

- · Easy access no tools required floorboard
- · Engine hood assist damper with lock device
- Air cleaner discharge valve

- Easy-lift engine hood with wide 75° opening Easy access to common service items such as filters & dipsticks
- Engine protection system

OPTIONAL EQUIPMENT*

- Intelli-Shift
- Clamp release interlock
- Mini-lever controls with ErgoShift
- Synchronized steering
- EZ Pedal foot directional control
- Combination brake & inching pedal
- Steering wheel with knob
- Hydraulic accumulators 1 or 2 quarts
- · LED front combination lights
- Strobe lights
- LED rear combination lights
- LED rear work light
- · LED reverse-activated rear work light
- Cloth 4-way adjustable full-suspension seat
- Swivel seat

- Orange seatbelt
- Box fin radiator
- Pre-cleaner for air intake
- Rearview mirrors
- 12-Volt power supply
- Rear assist grip with horn button
- Back up alarms
- 5-way hydraulics

^{*} Please contact your local, authorized Toyota Dealer for a complete list of available options.

TRUCK SPECIFICATIONS

MODEL NUMBER

GENERAL DATA					8FGC55U-PRS
Load Capacity				lb (kg)	12000 (5500)
Load Center				in (mm)	24 (600)
Power Type				()	LPG
Operator Position					Seated Rider
Tire Type Front / Re					Cushion / Cushion
Wheels (x = driven)			Front / Rear		2x/2
EXTERIOR DIMENSIONS					
					8FGC55U-PRS
Maximum Fork Height (top of forks)				in (mm)	N/A
Free-Lift (top of fo	orks)			in (mm)	N/A
Fork Size (TxWxL)				in (mm)	No Forks
Fork Spread Max. / Min. (outer edge to edge)				in (mm)	46.1 (1170) / 11.8 (300)
Tilt Range (forward / backward)				deg	5/6
Length to Fork Face				in (mm)	N/A
Overall Width				in (mm)	55.9 (1420)
Mast Lowered Height				in (mm)	86.6 (2200)
Mast Extended Height (top of load backrest)				in (mm)	174.6 (4435)
Overhead Guard Height				in (mm)	83.5 (2120)
Turning Radius (inside / outside)				in (mm)	93.5 (2380)
Load Distance				in (mm)	N/A
Basic Right-Angle	s Stacking	Aisle Widt	h	in (mm)	_
PERFORMANCE	DATA -				8FGC55U-PRS
PERFURIVIANCE				1.4.4.	
Speeds Drawbar Pull	Maximum Travel (forward / reverse)		Full Load	mph (km/h)	13.0 (21.0) / 13.0 (21.0)
	(IUIWalu	/ reverse)	No Load	mph (km/h)	13.0 (21.0) / 13.0 (21.0)
	Lifting		Full Load	fpm (mm/sec)	85 (430)
	3		No Load	fpm (mm/sec)	87 (440)
	Lowering Maximum		Full Load	fpm (mm/sec)	102 (520)
			No Load	fpm (mm/sec)	93 (470)
			Full Load	lb (kg)	9900 (4500)
			No Load	lb (kg)	3300 (1500)
Gradeability ¹	1 mph (1.5 km/h)		Full Load	%	25
	Maximum		Full Load	%	34
			No Load	%	18
TRUCK WEIGHTS	c				8FGC55U-PRS
	9			" (1)	
Total Weight				lb (kg)	17220 (7810)
Weight	Full Load	oad (front / rear)			
Distribution No Loa			')	lb (kg)	25140 (11460) / 4080 (1850)
	No Load	(front / rear	,	lb (kg)	25140 (11460) / 4080 (1850) 5800 (2630) / 11420 (5180)
TIRES	No Load	(front / rear	,		
TIRES		, ,	·)		5800 (2630) / 11420 (5180) 8FGC55U-PRS
		(front / rear (front / rear	r)		5800 (2630) / 11420 (5180) 8FGC55U-PRS 2/2
		, ,	r) Front		5800 (2630) / 11420 (5180) 8FGC55U-PRS 2 / 2 22 x 12 x 16
Tires	Number	, ,	r)	lb (kg)	5800 (2630) / 11420 (5180) 8FGC55U-PRS 2 / 2 22 x 12 x 16 18 x 8 x 12-1/8
Tires Wheelbase	Number	, ,	r) Front	lb (kg)	5800 (2630) / 11420 (5180) 8FGC55U-PRS 2 / 2 22 x 12 x 16 18 x 8 x 12-1/8 70.5 (1790)
Tires Wheelbase Tread Width (fron	Number Size	(front / real	Front Rear	Ib (kg) in (mm) in (mm)	5800 (2630) / 11420 (5180) 8FGC55U-PRS 2 / 2 22 x 12 x 16 18 x 8 x 12-1/8 70.5 (1790) 43.9 (1115) / 43.5 (1105)
Tires Wheelbase Tread Width (fron Underclearance	Number Size nt / rear) Minimum	(front / read	r) Front Rear	in (mm) in (mm) in (mm)	5800 (2630) / 11420 (5180) 8FGC55U-PRS 2 / 2 22 x 12 x 16 18 x 8 x 12-1/8 70.5 (1790) 43.9 (1115) / 43.5 (1105) 3.3 (85)
Tires Wheelbase Tread Width (fron Underclearance (full load)	Number Size nt / rear) Minimum Center o	(front / real	r) Front Rear	Ib (kg) in (mm) in (mm)	5800 (2630) / 11420 (5180) 8FGC55U-PRS 2 / 2 22 x 12 x 16 18 x 8 x 12-1/8 70.5 (1790) 43.9 (1115) / 43.5 (1105) 3.3 (85) 5.7 (145)
Tires Wheelbase Tread Width (fron Underclearance	Number Size nt / rear) Minimum Center o	(front / read	r) Front Rear	in (mm) in (mm) in (mm)	5800 (2630) / 11420 (5180) 8FGC55U-PRS 2 / 2 22 x 12 x 16 18 x 8 x 12-1/8 70.5 (1790) 43.9 (1115) / 43.5 (1105) 3.3 (85)
Tires Wheelbase Tread Width (fron Underclearance (full load)	Number Size nt / rear) Minimum Center of Service ((front / real	r) Front Rear	in (mm) in (mm) in (mm)	5800 (2630) / 11420 (5180) 8FGC55U-PRS 2 / 2 22 x 12 x 16 18 x 8 x 12-1/8 70.5 (1790) 43.9 (1115) / 43.5 (1105) 3.3 (85) 5.7 (145)
Tires Wheelbase Tread Width (fron Underclearance (full load) Brake	Number Size nt / rear) Minimum Center o Service ((front / real	r) Front Rear	in (mm) in (mm) in (mm)	5800 (2630) / 11420 (5180) 8FGC55U-PRS 2 / 2 22 x 12 x 16 18 x 8 x 12-1/8 70.5 (1790) 43.9 (1115) / 43.5 (1105) 3.3 (85) 5.7 (145) Hydraulic / Hand
Tires Wheelbase Tread Width (fron Underclearance (full load) Brake	Number Size nt / rear) Minimum Center o Service ((front / real	r) Front Rear	in (mm) in (mm) in (mm) in (mm)	5800 (2630) / 11420 (5180) 8FGC55U-PRS 2 / 2 22 x 12 x 16 18 x 8 x 12-1/8 70.5 (1790) 43.9 (1115) / 43.5 (1105) 3.3 (85) 5.7 (145) Hydraulic / Hand 8FGC55U-PRS
Tires Wheelbase Tread Width (fron Underclearance (full load) Brake	Number Size nt / rear) Minimum Center o Service (n with Load f Wheelbas (foot) / Parl	Front Rear Rear	in (mm) in (mm) in (mm) in (mm) V/Ah	5800 (2630) / 11420 (5180) 8FGC55U-PRS 2 / 2 22 x 12 x 16 18 x 8 x 12-1/8 70.5 (1790) 43.9 (1115) / 43.5 (1105) 3.3 (85) 5.7 (145) Hydraulic / Hand 8FGC55U-PRS 12 / 48
Tires Wheelbase Tread Width (fron Underclearance (full load) Brake	Number Size at / rear) Minimum Center of Service (ating)	n with Load f Wheelbas foot) / Parl	Front Rear Rear	in (mm) in (mm) in (mm) in (mm) V/Ah	5800 (2630) / 11420 (5180) 8FGC55U-PRS 2 / 2 22 x 12 x 16 18 x 8 x 12-1/8 70.5 (1790) 43.9 (1115) / 43.5 (1105) 3.3 (85) 5.7 (145) Hydraulic / Hand 8FGC55U-PRS 12 / 48 TOYOTA 1FS 89 @ 2550
Tires Wheelbase Tread Width (fron Underclearance (full load) Brake POWER SYSTEM Battery (5-hour ra	Number Size at / rear) Minimum Center of Service (ating)	n with Load f Wheelbas (foot) / Parl Make / Moc	Front Rear Rear	in (mm) in (mm) in (mm) in (mm) V/Ah SAE HP (kW)	5800 (2630) / 11420 (5180) 8FGC55U-PRS 2 / 2 22 x 12 x 16 18 x 8 x 12-1/8 70.5 (1790) 43.9 (1115) / 43.5 (1105) 3.3 (85) 5.7 (145) Hydraulic / Hand 8FGC55U-PRS 12 / 48 TOYOTA 1FS 89 @ 2550 (66 @ 2550)
Tires Wheelbase Tread Width (fron Underclearance (full load) Brake POWER SYSTEM Battery (5-hour ra	Number Size nt / rear) Minimum Center o Service (n with Load f Wheelbas (foot) / Parl Make / Moc	r) Front Rear Rear Relel Repower	in (mm) in (mm) in (mm) in (mm) V/Ah SAE HP (kW) SAE ft-lb	5800 (2630) / 11420 (5180) 8FGC55U-PRS 2 / 2 22 x 12 x 16 18 x 8 x 12-1/8 70.5 (1790) 43.9 (1115) / 43.5 (1105) 3.3 (85) 5.7 (145) Hydraulic / Hand 8FGC55U-PRS 12 / 48 TOYOTA 1FS 89 @ 2550 (66 @ 2550) 210 @ 1200 - 1400
Tires Wheelbase Tread Width (fron Underclearance (full load) Brake POWER SYSTEM Battery (5-hour ra	Number Size nt / rear) Minimum Center o Service (ating)	n with Load f Wheelbas (foot) / Parl Make / Moc Rated Hors @ rpm	Front Rear Rear lel lel epower	in (mm) in (mm) in (mm) in (mm) V/Ah SAE HP (kW)	5800 (2630) / 11420 (5180) 8FGC55U-PRS 2 / 2 22 x 12 x 16 18 x 8 x 12-1/8 70.5 (1790) 43.9 (1115) / 43.5 (1105) 3.3 (85) 5.7 (145) Hydraulic / Hand 8FGC55U-PRS 12 / 48 TOYOTA 1FS 89 @ 2550 (66 @ 2550) 210 @ 1200 - 1400 (290 @ 1200 - 1400)
Tires Wheelbase Tread Width (fron Underclearance (full load) Brake POWER SYSTEM Battery (5-hour ra	Number Size nt / rear) Minimum Center o Service (ating)	n with Load f Wheelbas ffoot) / Parl Make / Moc Rated Hors @ rpm Rated Torqu	Front Rear Rear lel lel lepower Cyllinders	in (mm) in (mm) in (mm) in (mm) V/Ah SAE HP (kW) SAE ft-lb (N-m)	5800 (2630) / 11420 (5180) 8FGC55U-PRS 2 / 2 22 x 12 x 16 18 x 8 x 12-1/8 70.5 (1790) 43.9 (1115) / 43.5 (1105) 3.3 (85) 5.7 (145) Hydraulic / Hand 8FGC55U-PRS 12 / 48 TOYOTA 1FS 89 @ 2550 (66 @ 2550) 210 @ 1200 - 1400 (290 @ 1200 - 1400)
Tires Wheelbase Tread Width (fron Underclearance (full load) Brake POWER SYSTEM Battery (5-hour ra	Number Size at / rear) Minimum Center o Service (ating)	n with Load f Wheelbas foot) / Parl Make / Moc Rated Hors a rpm Rated Torqu Number of I	Front Rear Rear lel lel lepower Cylinders lacement	in (mm) in (mm) in (mm) in (mm) V/Ah SAE HP (kW) SAE ft-lb (N-m)	5800 (2630) / 11420 (5180) 8FGC55U-PRS 2 / 2 22 x 12 x 16 18 x 8 x 12-1/8 70.5 (1790) 43.9 (1115) / 43.5 (1105) 3.3 (85) 5.7 (145) Hydraulic / Hand 8FGC55U-PRS 12 / 48 TOYOTA 1FS 89 @ 2550 (66 @ 2550) 210 @ 1200 - 1400 (290 @ 1200 - 1400)
Tires Wheelbase Tread Width (fron Underclearance (full load) Brake POWER SYSTEM Battery (5-hour ra	Number Size at / rear) Minimum Center o Service (ating)	n with Load f Wheelbas ffoot) / Parl Make / Moc Rated Hors @ rpm Rated Torqu	Front Rear Rear lel lel lepower Cylinders lacement	in (mm) in (mm) in (mm) in (mm) V/Ah SAE HP (kW) SAE ft-lb (N-m)	5800 (2630) / 11420 (5180) 8FGC55U-PRS 2 / 2 22 x 12 x 16 18 x 8 x 12-1/8 70.5 (1790) 43.9 (1115) / 43.5 (1105) 3.3 (85) 5.7 (145) Hydraulic / Hand 8FGC55U-PRS 12 / 48 TOYOTA 1FS 89 @ 2550 (66 @ 2550) 210 @ 1200 - 1400 (290 @ 1200 - 1400)
Tires Wheelbase Tread Width (fron Underclearance (full load) Brake POWER SYSTEM Battery (5-hour ra	Number Size at / rear) Minimum Center o Service (ating) F	n with Load f Wheelbas foot) / Parl Make / Moc Rated Hors a rpm Rated Torqu Number of I	Front Rear Rear lel lel lepower Cylinders lacement	in (mm) in (mm) in (mm) in (mm) V/Ah SAE HP (kW) SAE ft-lb (N-m)	5800 (2630) / 11420 (5180) 8FGC55U-PRS 2 / 2 22 x 12 x 16 18 x 8 x 12-1/8 70.5 (1790) 43.9 (1115) / 43.5 (1105) 3.3 (85) 5.7 (145) Hydraulic / Hand 8FGC55U-PRS 12 / 48 TOYOTA 1FS 89 @ 2550 (66 @ 2550) 210 @ 1200 - 1400 (290 @ 1200 - 1400)
Tires Wheelbase Tread Width (fron Underclearance (full load) Brake POWER SYSTEM Battery (5-hour ra	Number Size at / rear) Minimum Center o Service (ating) F F F	n with Load f Wheelbas foot) / Parl Make / Moc Rated Hors or rpm Rated Torqu Number of I Piston Disp Fuel Tank C	Front Rear Rear lel lel lepower Cylinders lacement	in (mm) in (mm) in (mm) in (mm) V / Ah SAE HP (kW) SAE ft-lb (N-m) cu in (cc) US gal (liter)	5800 (2630) / 11420 (5180) 8FGC55U-PRS 2 / 2 22 x 12 x 16 18 x 8 x 12-1/8 70.5 (1790) 43.9 (1115) / 43.5 (1105) 3.3 (85) 5.7 (145) Hydraulic / Hand 8FGC55U-PRS 12 / 48 TOYOTA 1FS 89 @ 2550 (66 @ 2550) 210 @ 1200 - 1400 (290 @ 1200 - 1400) 4 224 (3685) —
Tires Wheelbase Tread Width (fron Underclearance (full load) Brake POWER SYSTEM Battery (5-hour ra	Number Size nt / rear) Minimum Center o Service (ating) F F F F F S ic Number	n with Load f Wheelbas foot) / Parl Make / Moc Rated Hors rpm Rated Torqu Number of I Piston Disp Fuel Tank C Fype Speeds (for	Front Rear Rear lel lel epower Cylinders lacement apacity	in (mm) in (mm) in (mm) in (mm) V / Ah SAE HP (kW) SAE ft-lb (N-m) cu in (cc) US gal (liter)	5800 (2630) / 11420 (5180) 8FGC55U-PRS 2 / 2 22 × 12 × 16 18 × 8 × 12-1/8 70.5 (1790) 43.9 (1115) / 43.5 (1105) 3.3 (85) 5.7 (145) Hydraulic / Hand 8FGC55U-PRS 12 / 48 TOYOTA 1FS 89 @ 2550 (66 @ 2550) 210 @ 1200 - 1400 (290 @ 1200 - 1400) 4 224 (3685) — Automatic

Computed values. Performance of LPG fuel system may be less than performance of standard model shown. Values taken at Hydraulic Control Valve. Does not take in to consideration losses through mast plumbing (hosing, fittings, QDs, etc.).







"I'M HERE TO MAKE SURE YOUR FORKLIFTS DON'T TAKE VACATION DAYS."

Butch - 360 Technician, ProLift, Cincinnati, Ohio



HELP IS ALWAYS HERE WITH TOYOTA 360 SUPPORT.

The industry's best and most comprehensive dealer network quickly delivers Toyota Certified Technicians to your work site. These specially-trained technicians can also help assess your warehouse and facility needs to recommend the right equipment for the job. And with the largest fleet of used and rental forklifts, Toyota 360 keeps your business running at full speed.

ToyotaForklift.com/360-Support



YOUR BUSINESS IS RIDING ON IT.

Some product features described herein are optional. Please consult your dealer for specifications. Details of specifications and equipment are based on information available at time of printing and may change without notice.

