



[HOME](#) » [COMMERCIAL CONSTRUCTION](#) » [NEOPRENE / ELASTOMERIC FLOOR MOUNTED NON-SEISMIC](#) » [FABRI-FLEX REINFORCED DUCK & NEOPRENE PADS](#)



NEOPRENE / ELASTOMERIC FLOOR MOUNTED NON-SEISMIC

## **FABRI-FLEX REINFORCED DUCK & NEOPRENE PADS**

VMC Group Fabri-Flex (Fabriflex) isolation pads with 1000 psi loading capability for excellent high frequency sound attenuations under extremely heavy load applications.

Fabri-Flex Pads consist of multiple layers of high quality, cotton duck fabric thoroughly impregnated and bonded together by a specially formulated elastomeric compound. Standard thickness ranges from 1/8" to 1" and the pads are cut to size requirements.

Fabri-Flex Pads are also available in a washer design. Manufactured of the same material, the washers are

designed to eliminate metal-to-metal contact between steel bolting and steel bearing plates.

## FEATURES & BENEFITS

- 1,000 psi loading capabilities
- Multiple layered, cotton duck fabric thoroughly impregnated with an elastomeric compound for durability
- Standard thickness ranges from 1/8" to 1"
- Optional washer design

## APPLICATIONS

- Air handling units
- Fans
- Pumps
- Chillers
- Air compressors
- HVAC equipment
- Power generation
- Electrical transformers
- Motors

## DOWNLOADS

---

### Spec Sheets

[Spec Type 1 Elastomeric Pads](#)

### Submittal Drawings

#### Fabri-Flex

[Model Fabri-Flex reinforced duck isolation pad.pdf](#)

[Model NDB 50-2000 lbs. Elastomeric square inch isolation pad.pdf](#)

[Model NR 20-4050 lbs. Elastomeric 0.375 inch thick isolation pad.pdf](#)

[Model NRC 20-4860 lbs. Elastomeric square inch isolation pad.pdf](#)

[Model SP-NR 20-4050 lbs. Elastomeric isolation pad bonded to steel](#)

[plate style A thru E.pdf](#)

[Model SP-NRC 20-4860 lbs. Elastomeric isolation pad bonded to steel plate style A thru E.pdf](#)

### **Grommets**

[Model Elastomeric Grommet Vibration Isolators.pdf](#)

---

## **RELATED SERVICES**

---

### **Engineering**

The engineers we employ hold the highest industry-recognized credentials in structural analysis, elastomer development and system dynamics.

### **Certification**

We are the first ISO accredited PCA ISO-17065, third-party certification body for special seismic certification of non-structural building components and their mounting configurations by the ICC's International Accreditation Service.

### **Test & Measurement**

We are the only ISO 17025:2005 Accredited Seismic Simulation Test Laboratory with a triaxial shake table owned and operated by California licensed Structural engineers.

### **Testing Services Update**

DCL now offers Nuclear Qualification and Testing services.

In partnership with [Greenberry Industrial](#), we now offer testing services that meet the requirements of ASME NQA-1.

[Call for more information.](#)

---

## **RELATED PRODUCTS**

---



[VLM Leveling Isolator](#)



[R Single Deflection Isolators](#)