

Orbisphere 410 Controller

Applications

- Food and Beverage
- Industrial Water
- Pure Water Applications
- Power (non-nuclear)



Precise, Powerful Process Monitoring

The Orbisphere 410 offers precise, process monitoring capability. Designed to complement the Orbisphere high quality oxygen and ozone sensors these instruments provide accurate, repeatable trace level measurements and an impressive level of data management. These process monitoring instruments are designed for applications in the food & beverage, power generation, electronics, life sciences, chemical and water treatment industries.

Easy to use, intuitive software using clear, full color touch-screen

All functions of Orbisphere 410 instruments are accessed through the color touch-screen. This screen acts as display and keyboard.

Internal diagnostics and reminders for maintenance and calibration

To ensure continuous high performance and simplify maintenance, Orbisphere 410 instruments offer a number of diagnostic features: A notification that calibration is due ensures QC procedural compliance, a notification that a sensor service is due ensures optimal preventative maintenance planning. The sensor service diagnostics minimises downtime, and system alarms transmitted through analog output provide continuous status indication.

Easy to use and reliable

Orbisphere 410 instruments are designed for ease of use. After simple installation, the system is measuring your process in minutes. Simple menus allow you to rapidly create a specific configuration for the instrument. The main measurement window continuously displays real time process readings, graphed sensor trends (user selectable from last 1 minute to last 1 hour), alarm limits, temperature and event occurrence.

Multiple communication options including USB and Profibus

Digital communication uses industry standard protocols including Profibus and USB in addition to traditional analog outputs and alarm relays. These may all be configured in terms of function, content and behaviour.

Data storage

Data storage of up to 10000 measurements, last 1000 operator actions and details of last 50 calibrations.

Technical Data*

Enclosure Construction	Wall (pipe) mount: stainless steel Panel mount: aluminum	Compliance Certifications	EMC: EN61326-1:2006 CE: EN61010-1:2010
Enclosure Rating	Wall (pipe) mount: IP65, NEMA 4x Panel mount: IP65	Data Storage	Rolling buffer or store once mode for up to 1000 measurements and 1000 operator actions Holds calibration records for last 50 calibrations
Measurements	Resolution, accuracy and response time are determined by sensor	Password Protection	5 levels of authorized access to configuration and data management
Sensor	Orbisphere 311xx, A1100, M1100, K1100, C1100, 314xx	Operating Temperature Range	-5 - 50 °C
Units	Gas concentration: Configurable for gas or liquid phase with multiple unit options Pressure: External and barometric pressure with multiple unit options Temperature: Sample temperature with unit options (K, °C, °F)	Operating Conditions	0 - 95 % non-condensing relative humidity
Interference correction	Chlorinity correction Salinity correction CO ₂ insensitivity H ₂ S insensitivity	Display	Color TFT touch-screen display
Communication	RS485 Profibus DP (optional) Ethernet USB-client to download data from a computer USB-host to download data with a USB memory stick	User Interface	Touch-screen panel displays: concentration, trend graph, diagnostics, alarm status, historical data
Analog Outputs	3 smart 0/4-20 mA (500 ohms), programmable as linear or tri-linear, configurable to send diagnostics information	Power	Universal 100/240 VAC @ 50/60 Hz, 25 VA 10-36 VDC, 25 W
Relays	3 measurement alarm relays (2A to 30 VAC or 0.5 A to 50 VDC); configurable to send diagnostics information 1 system alarm relay (2 A to 30 VAC or 0.5 A to 50 VDC)	Dimensions (H x W x D)	Wall dimensions: 230.5 mm x 250 mm x 160 mm (9.1 in x 9.8 in x 6.3 in) Panel dimensions: 156 mm x 220 mm x 253.5 mm (6.14 in x 8.86 in x 9.84 in)
		Weight	Wall (pipe) mount: 3.8 kg Panel mount: 2.9 kg

*Subject to change without notice.

Several controller configurations depending on parameter/sensor, mounting, communications, and power options are available. Please contact Hach for more details.

Hach World Headquarters: Loveland, Colorado USA

United States: 800-227-4224 tel 970-669-2932 fax orders@hach.com

Outside United States: 970-669-3050 tel 970-461-3939 fax int@hach.com

hach.com

Printed in U.S.A.

©Hach Company, 2017. All rights reserved.

In the interest of improving and updating its equipment, Hach Company reserves the right to alter specifications to equipment at any time.



Be Right™