

Combics 2

Complete Scale



Shown with optional post mount assembly

Application Note:

Counting, checkweighing, differential weighing, percentage weighing, gross-net-tare, sorting, net-total, animal weighing, averaging, totalizing

Standard Features

- Amber backlit LCD display, 0.8 in, 13 segment
- External calibration routine
- RS-232C
- Numeric keypad (with two IDs) for entering identifier codes and preset tares
- Info key for quick and easy display of tare input and ID codes
- Date/time fully integrated
- Three built-in LED checkweighing lights
- Bar graph weighing range indicator
- Optional barcode scanner for preset tare, reference weight and ID entry
- Stored customer specific data records
- Two scale connections, analog or digital
- 10 ft cable

Part Number/Price

RLWS PN	Minebea PN	Dimensions	Capacity	Readability	Est. Weight	Price
Mild Steel with CAISL2-U						
156409	CAW2P1U-10CC-I	10 x 10 in	15 lb (6 kg)	0.0005 lb (0.0002 kg)	20 lb	\$2,020.00
156414	CAW2P1U-50DD-I	12 x 12 in	60 lb (30 kg)	0.002 lb (0.001 kg)	24 lb	\$2,051.00
156420	CAW2P1U-100EE-I	18 x 18 in	150 lb (60 kg)	0.005 lb (0.002 kg)	65 lb	\$2,355.00
156423	CAW2P1U-250GG-I	24 x 24 in	300 lb (150 kg)	0.01 lb (0.005 kg)	120 lb	\$3,225.00
Stainless Steel with CAIS2-U						
156424	CAW2S1U-10CC-I	10 x 10 in	15 lb (6 kg)	0.0005 lb (0.0002 kg)	22 lb	\$2,506.00
156425	CAW2S1U-50DD-I	12 x 12 in	60 lb (30 kg)	0.002 lb (0.001 kg)	30 lb	\$2,637.00
156426	CAW2S1U-100EE-I	18 x 18 in	150 lb (60 kg)	0.005 lb (0.002 kg)	68 lb	\$2,794.00
156427	CAW2S4UR-250GG-I	24 x 24 in	300 lb (150 kg)	0.01 lb (0.005 kg)	127 lb	\$6,117.00

CAW2P are an IP65 mild steel base with an IP44 indicator

CAW2S are an IP67 stainless steel base with an IP69K indicator

Options/Accessories

RLWS PN	Minebea PN	Description	Price
156440	YDH01CWSUS	Post mount assembly for 10 x 10 in platforms, 13 in high	\$200.00
156441	YDH02CWSUS	Post mount assembly for 12 x 12 in platforms, 19 in high	\$217.00
156442	YDH03CWSUS	Post mount assembly for 18 x 18 in platforms, 29 in high	\$250.00
171727	YDH12CWSUS	Bench mount bracket	\$80.00
105607	YDH02CISUS	Tilttable wall mount bracket	\$80.00
Consult	69CW0126	Power supply	Consult

Specifications

Supply Voltage:
9 V

Power Requirements:
120-240 VAC, 17 W / 23 VA maximum

Indicator Housing:
AISI 304 stainless steel

Indicator Dimensions:
(W x D x H): 11.9 x 7.4 x 3.5 in
(302.3 x 188 x 89 mm)

Operating Temperature:
14° F to 104° F (-10° C to 40° C)

Warranty:
Two-year limited warranty
Accessories: one-year limited warranty