## MINEBEA INTEC Combics 3 Digital Weight Indicators

PRECISION INDUSTRIAL WEIGHING

Combics 2 and Combics 3 indicators are designed for use with both Combics, IF and IS series platforms. However, various accessories may differ and are application dependent.

Applications Software Pre-installed:

Counting, checkweighing, differential weighing, percentage weighing, gross-net-tare, sorting, net-total, animal weighing

Custom Applications Packages:

Single component batching BASIC

Single component batching PRO

## **Standard Features**

- IP protection rating (IP44, IP69K)
- · Amber backlit LCD display
- On/Off Zero, Tare, Print/Data Keys
- · Function keys for: Gross/net toggle; three-way unit toggle; 10X higher resolution toggle
- · Keypad with two IDs for entering identifier codes and preset tare
- Info key for quick and easy display of tare input and ID codes
- Date/time fully integrated
- GMP/GLP printable record
- Platform toggling and four function keys
- Three built-in LED checkweighing lights
- Bar graph weighing range indicator
- · Application data and totalization memory stored in battery-backed RAM
- Optional barcode scanner for preset tare, reference weight and ID entry
- Stored customer-specific data records
- · Key for toggling between weighing applications, and five soft keys with text-supported user guidance
- · Input functions for entering up to four alphanumeric ID texts

## Part Number/Price

<b>RLWS PN</b>	Minebea PN	Description	Est. Weight	Price
102405	CAISL3-U	IP44 protection rated	7.5 lb	\$1,859.00
Consult	CAISL3-UV1	IP44, controller for IS base	7.5 lb	\$2,207.00
102407	CAIS3-U	IP69K protection rated	7.5 lb	\$2,228.00
115674	CAIS3-UV1	IP69K, controller for IS base	7.5 lb	\$2,572.00

# **Options/Accessories**

	-		
<b>RLWS PN</b>	Minebea PN	Description	Price
105607	YDH02CISUS	Wall mount bracket	\$80.00
171727	YDH12CWSUS	Bench mount bracket	\$80.00
156440	YDH01CWSUS	Post mount assembly for 10 x 10 in platforms, 13 in high	\$200.00
156441	YDH02CWSUS	Post mount assembly for 12 x 12 in platforms, 19 in high	\$217.00
156442	YDH03CWSUS	Post mount assembly for 18 x 18 in platforms, 29 in high	\$250.00
103049	YAS02MI	2 V industrial power supply	\$201.00
155826	YD002C-A0	Analog output, 0-20 mA, 4-20 mA, 0-10 V	\$801.00
162640	YD002C-ETH	Ethernet TCP-IP	\$801.00
193049	YDC01CI	Dust cover pack of two	\$67.00
Cables			
155804	YCC05-001M2	RS-232 9/25-Pin D-Sub female, 1.5 m, IP44	\$104.00
155805	YCC01-USBM2	RS-232 to USB connector, 2 m IP44	\$160.00
155806	YCC02-D25F6	RS-232 open to 25 D-Sub female	\$264.00



### **Specifications**

Load Cell Connection: 4 or 6 wire

Supply Voltage:

Power Requirements: 120-240 VAC, 17 W/23 VA maximum

Housing: AISI 304 stainless steel

Dimensions:

(W x D x H): 11.9 x 7.4 x 3.5 in

Operating Temperature: 14° F to 104° F (-10° C to 40° C)

Net Weight: 5 lb

#### Warranty:

Two-year limited warranty Accessories: One-year limited warranty