

LaserLight2™

Four-inch, Six-inch, Four-inch Stop/Go Remote Display



Standard Features


- Available with a 4-in (100 mm) or 6-in (150 mm) display
- Six high-intensity red digits (double-row discrete LED)
- Time and date displayed when scale is empty
- Auto Learn mode of communication protocols
- Hold displayed weight (demand input)
- Software selectable standstill mode for no updates while in motion
- Durable weathertight IP66 enclosure
- Adjustable daylight/night intensity
- Non-glare contrast filtered lens
- Mirror (reverse image) function
- RS-232, 20 mA and RS-485 communications
- Auto sensing 115/230 VAC power supply
- PEMs for VESA flat-wall mount or side-mounting flange
- Polyethylene breather vent inhibits internal moisture buildup
- Red, green and arrow lights in stop/go version

APPROVALS*



*See Specific Part Numbers

Dimensions			
22-inch Enclosure (Four-inch Model)			
A	22.28 in (565 mm)	D	9.80 in (250 mm)
B	10.96 in (280 mm)	E	23.00 in (584 mm)
C	3.28 in (85 mm)	F	6.00 in (152 mm) 3/8 in bolt
31-inch Enclosure (Six-inch and Stop/Go Models)			
A	30.63 in (780 mm)	D	12.77 in (325 mm)
B	13.94 in (355 mm)	E	31.00 in (787 mm)
C	3.73 in (95 mm)	F	7.75 in (197 mm) 3/8 in bolt



Specifications

Display:

6-digit, 7-segment discrete oval red LED lamps
 Contrast enhanced optical filtering lens
 1- or 2-place decimal or comma indication
 4 annunciators for GR, NT, lb, kg
 4-inch red, green ball/arrow in Stop/Go model

Maximum Viewing Distance:

4 in: 250 ft (75 m)
 6 in: 300 ft (100 m)

Input Interface:

RS-232, RS-485, 20 mA current loop (active or passive, switch selectable)

Output Interface:

Independently configurable echo out port or RS-232

Input Data Format:

Baud Rate: 1200, 2400, 4800, 9600 and 19200
 self-learning or software selectable

Character Format:

7 or 8 data bits; even, odd, or no parity; 1 or 2 stop bits, self-learning or software selectable

Update:

Continuous or out-of-motion only; software selectable

Power Consumption:

4 in: 21 watt
 6 in: 27 watt

Time:

Software enable/disable, 12- or 24-hour format

Date:

Software enable/disable, US or ISO format

Rating/Material:

IP66 weather tight, mild steel, powder coated

Dimensions:

4-inch (L x H): 22.28 in x 9.8 in
 6-inch (L x H): 30.63 in x 12.77 in
 Stop/Go (L x H): 30.63 in x 12.77 in
 (flanges add 2.00 in width)

Weight:

4 in: 20 lb (9 kg)
 6 in: 25 lb (11 kg)

Operating Temperature Range:

-40°F to 120°F (-40°C to 49°C)

Warranty:

Two-year limited warranty

Approvals:

UL/cUL on specific part numbers

Part Number/Price

Part #	Description	Est. Weight	Price
Flange Mounted (included)			
167091	LaserLight2 remote display 4-inch (100 mm) includes PN 175305	20lb	\$1,600.00
179521*	LaserLight2 remote display 4-inch (100 mm) marked UL/cUL includes PN 175305	20lb	\$1,800.00
175286	LaserLight2 remote display 4-inch (100 mm) stainless steel includes PN 179910	20lb	\$1,950.00
167092	LaserLight2 remote display 6-inch (150 mm) includes PN 175306	25lb	\$2,100.00
179523*	LaserLight2 remote display 6-inch (150 mm) marked UL/cUL includes PN 175306	25lb	\$2,300.00
167093	LaserLight2 remote display Stop/Go 4-inch (100 mm) includes PN 175306	25lb	\$2,100.00
179525*	LaserLight2 remote display Stop/Go 4-inch (100 mm) marked UL/cUL includes PN 175306	25lb	\$2,300.00
187120	LaserLight2 remote display Stop/Go 4-inch (100 mm) stainless steel includes PN 187124	25lb	\$2,500.00
VESA Mounted (included)			
175860	LaserLight2 remote display 4-inch (100 mm) includes PN 175213	20lb	\$1,650.00
179522*	LaserLight2 remote display 4-inch (100 mm) marked UL/cUL includes PN 175213	20lb	\$1,850.00
175861	LaserLight2 remote display 6-inch (150 mm) includes PN 175213	25lb	\$2,150.00
179524*	LaserLight2 remote display 6-inch (150 mm) marked UL/cUL includes PN 175213	25lb	\$2,350.00
175862	LaserLight2 remote display Stop/Go 4-inch (100 mm) includes PN 175213	25lb	\$2,150.00
179526*	LaserLight2 remote display Stop/Go 4-inch (100 mm) marked UL/cUL includes PN 175213	25lb	\$2,350.00

*UL/cUL on specific models

Options/Accessories

Part #	Description	Price
175052	Wireless interface, pair of ConnexLink Radios and mount	\$795.00
Consult	LaserLight2 green display (modified LED boards)	Consult
175213	Mount bracket, VESA flat-wall option (included with VESA mounted remote)	\$80.00
175305	Mount bracket, 4-inch flange option (included with flange mounted remote)	\$25.00
175306	Mount bracket, 6-inch flange option (included with flange mounted remote)	\$25.00
179910	Mount bracket, 4-inch stainless steel flange option (included with flange mounted stainless steel remote)	\$29.00
187124	Mount bracket, 6-inch stainless steel flange option (included with flange mounted stainless steel remote)	\$40.00
75856	Pole mount kit, 4-inch flange option (24-inch wide frame for 4-8 inch dia. pole)	\$225.00
77775	Pole mount kit, 6-inch and 4-inch stop/go flange option (32-inch wide frame for 4-8 inch dia. pole)	\$225.00
177865	Pole mount kit, VESA flat-wall option mount for 2-6 inch pole	\$75.00
178790	Offset kit (right or left flag mount) used with universal pole mount (requires PN 177865)	\$60.00
181224	Visor for 22 inch enclosure (not required for weather protection)	\$150.00
181801	Visor for 31 inch enclosure (not required for weather protection)	\$150.00

