


Flared Fitting Pressure Snubbers



All AN and MS Type fittings are available as snubbers




| Coupling Flare x Flare (similar to AN815) | | | | | |
|---|-----------|--------------|--------|---------|--------|
| Description | Model No. | Hex (inches) | Length | Threads | Weight |
| ¼" Flare (7/16"-20 NF-3) | AC-1 | 11/16 | 1 ¼ | 7/16-20 | ½ oz. |
| ⅜" Flare (9/16"-18 NF-3) | AC-6 | 13/16 | 1 3/8 | 9/16-18 | 1 oz. |
| ½" Flare (¾"-16 NF-3) | AC-8 | 1 | 1 9/16 | ¾-16 | 2 oz. |



| Coupling Flared x NPT (Similar to AN816) | | | | | |
|--|-----------|--------------|-----------|---------|--------|
| Description | Model No. | Tubing (O.D) | NPT Pipe | Length | weight |
| ¼" Flare x 1/8" NPT Female | 12-FR-4 | ¼" | ⅛" Female | 1.3/16" | 1 oz. |
| 5/16" Flare x 1/8" NPT Female | 12-FR-5 | 5/16" | ⅛" Female | 1 3/16" | 1 oz. |
| ¼" Flare x ¼" NPT Female | 25-FR-4 | ¼" | ¼" Female | 1 ⅜" | 1 oz. |
| 5/16" Flare x ¼" NPT Female | 25-FR-5 | 5/16" | ¼" Female | 1 7/16" | 1 oz. |
| 3/8" Flare x ¼" NPT Female | 25-FR-6 | ⅜" | ¼" Female | 1 7/16" | 1 oz. |
| ¼" Flare x ⅛" Male | 12-MR-4 | ¼" | ⅛" Male | 1 ½" | |
| 5/16" Flare x ⅛" Male | 12-MR-5 | 5/16" | ⅛" Male | 1 3/16" | 2 oz. |
| ¼" Flare x ¼" Male | 25-MR-4 | ¼" | ¼" Male | 1 ⅜" | |
| 5/16" Flare x ¼" Male | 25-MR-5 | 5/16" | ¼" Male | 1 5/16" | 2 oz. |
| 3/8" Flare x ¼" Male | 25-MR-6 | ⅜" | ¼" Male | 1 7/16" | |
| ¼" Flare x ½" Male | 50-MR-4 | ¼" | ½" Male | | 3 oz. |
| 5/16" Flare x ½" Male | 50-MR-5 | 5/16" | ½" Male | | 3 oz. |
| 3/8" Flare x ½" Male | 50-MR-6 | ⅜" | ½" Male | | 3 oz. |



| Flared Tube Reducer (similar to AN919) | | | | | | |
|--|--------------|--------|--------------|------------|------------|------------|
| Description | Model Number | Weight | Hex (inches) | Length | Thread (S) | Thread (L) |
| ¼" Flare (7/16"-20 NF-3) x ⅜" Flare (5/16"-20 NF-3) | ARC-1 | 1 oz. | 11/16 | 1 ¼ | 5/16"-24 | 7/16"-20 |
| ⅜" Flare (9/16"-18 NF-3) x ¼" Flare (7/16"-20 NF-3) | 1ARC-6 | 1 oz. | 13/16 | 1 13/32 | 7/16"-20 | 9/16"-18 |
| ½" Flare (¾"-16 NF-3) x ¼" Flare (7/16"-20 NF-3) | 1ARC-10 | 2 oz. | 1 | 1 17/32 | 7/16"-20 | 3/4"-16 |



| | |
|---|---|
| Flare Tube Bushing Gasket Seal x Flare See Flareless Snubbers (chemiquip.com) | Flared tube Tee Contact for details |
|---|---|

| | |
|---|--|
| Flared tube Elbow Contact for details | Flared tube Bulkhead union Contact for details |
|---|--|

Housing materials

- 303 Stainless Steel
- 316 Stainless Steel
- Plated Carbon steel

| Add suffix to model no. to indicate desired porosity | |
|--|--|
| Suffix | Porosity |
| C | Highly Viscos Fluids over 500 S.S.U. |
| D | Oil 225 S.S.U. to 500 S.S.U. |
| E | Water & Light Oils 30 to 225 S.S.U. |
| F | Vapor and Low Viscosity Fluids under 30 S.S.U. |
| G | Air or other Gases |
| HX | Pulsating Gas |
| HXX | Extreme Gas Pulsation |

The products illustrated in this catalog are not limited to the standard design shown.