

Floor Access Doors

BILCO's floor access door safety products help workers do their job safely by protecting them while they are working. Products meet OSHA fall protection standards and make fixed ladder access safer and easier.



Fall Protection Grating System Features

- Provides a permanent means of fall protection under access doors
- Exceeds OSHA fall protection requirements
- Aluminum grating with a safety-yellow powder coat paint finish for added durability
- Equipped with a stainless steel automatic hold-open device that securely locks the panel in the full open position
- Stainless steel hardware for corrosion resistance
- Supplied with a padlock hasp for added security
- Backed by a 25-year manufacturer's warranty

LadderUP® Features

- Adjustable mounting hardware accommodates virtually any ladder rung size or spacing
- Telescoping design is spring balanced for ease of operation
- Automatically locks in the fully raised position to provide the user with a firm and steady hand-hold
- Handy release lever allows the post to be easily lowered to its retracted position
- Available in four levels of corrosion resistance to provide many years of trouble free, dependable service

Log on to www.BILCO.com to find a sales representative near you.



Fall Protection Grating System

Fall Protection Grating System allows workers to safely inspect pumps and monitor underground areas. System permanently mounts under access door covers and are available as either factory-installed or as field-installable kits for all standard-sized Bilco Type J, JD, J-AL and J-DAL models. Grating system features aluminum construction with a safety yellow powder coat paint finish and stainless steel hardware.



BILCO LadderUp® Safety Post

LadderUP® Safety Posts provide easier, safer ladder access through roof hatches, floor access doors and manholes. This telescoping post permanently mounts to the top two rungs of any fixed ladder, providing a positive hand-hold and enabling the user to enter or exit an opening in an upright and balanced position.

| MODEL# | MATERIAL/FINISH | WEIGHT | |
|--------|---|--------|-----|
| | | lbs. | kg. |
| LU-1 | Steel, yellow powder coat | 24 | 11 |
| LU-2 | Steel, hot dip galvanized | 24 | 11 |
| LU-3 | Type 304 Stainless Steel, sand blast finish | 24 | 11 |
| LU-4 | Aluminum, mill finish | 14 | 7 |