

Part Numbers/Price

Part #	Description	Price
119687	Weigh out kiosk with 920i® HMI and thermal kiosk printer, 24 x 24 x 12 in painted mild steel enclosure, A/D not included	\$5,435.00

Options/Accessories

Part #	Description	Price
21159	Internal transient protection	\$245.00
23146	Traffic light	\$775.00
119691	Vandal-proof 12-key keypad	\$445.00
176452	HID smart card reader	\$550.00
119692	88 key, panel mount Qwerty style keyboard	\$780.00
119693	200 watt heater	\$550.00
119761	Ethernet unmanaged switch, five port	\$298.00
119689	Kiosk option, A/D single-channel, includes DIN rail and terminals	\$345.00
119690	Kiosk option, A/D dual-channel, includes DIN rail and terminals	\$510.00
119946	Single port Ethernet server	\$435.00
120040	Dual port Ethernet server	\$605.00
33490	Relay rack four-channel Opto 22 style with screws	\$80.00
Consult	22 mm Allen Bradley push buttons with legend plates	\$150.00
75850	SURVIVOR® LaserLight® Series remote display, 4 in	\$1,500.00
75852	SURVIVOR® LaserLight® Series remote display, 6 in	\$1,950.00

Replacement Parts

Part #	Description	Price
105445	Paper 6 in OD, one ply thermal 80 mm (3.1 in) 710 ft/roll	\$25.00
105446	Paper 8 in OD, one ply thermal 80 mm (3.1 in) 1268 ft/roll	\$27.00
54215	3.15 amp 250V Slo Blo 5 x 20 mm kiosk power input fuse	\$4.00
88792	Power supply, IDEC 12VDC	\$130.00
160025	Power supply, IDEC 12VDC - 15W	\$175.00
88793	Power supply, IDEC 24VDC - 30W	\$215.00
72682	Network protection, surge	\$40.00
69201	RS-232 protection, TP232	\$175.00
181230	Serial kiosk printer kit (includes printer, bracket assembly, power supply and cables)	\$1,555.00
191359	Ethernet kiosk printer kit (includes printer, bracket assembly, power supply and cables)	\$1,600.00

Printer Kiosk

Thermal-transfer Printer Kiosk



Basic printer kiosk with optional RFID card reader and optional number keypad



Basic printer kiosk
PN 92971



Basic printer kiosk with optional RFID card reader

Standard Features

Printer Kiosk with Ethernet Intercom

- Digital Acoustics Ethernet TCP/IP intercom substation

Thermal-transfer Printer Kiosk

- Painted mild steel enclosure
- Slide door access to ticket
- Zinc-plated 3/4-inch NPT conduit hubs
- Additional options available upon request

Note: Printer, thermal transfer ribbon and card stock sold separately

Specifications

Line Voltages:
115 or 230 VAC

Frequency:
50 or 60 Hz

Power Consumption:
0.5 amps (depending on options)

Fusing:
6 amp circuit breaker

Humidity:
0-95% relative humidity

Rating/Material:
NEMA Type 1
IP10

Printer Serial Ports:
RS-232
Ethernet (optional)

Storage Temperature:
14°F to 158°F (-10°C to 70°C)

Current Supported Riser Plates:

- Zebra® 140XIIIPlus
- Zebra 105SL
- Zebra R110Xi
- Zebra Z4Mplus
- Zebra 2746e
- Honeywell 4206
- Honeywell I-4212
- Intermec/Honeywell 3400e
- Intermec/Honeywell 4440

Warranty:
Two-year limited warranty

