

Part Number/Price

Part #	Model #	Description	Price
107232	TC-620	620 g x 0.01 g	\$737.00
107233	TC-1200	1,200 g x 0.1 g	\$675.00
107234	TC-4200	4,200 g x 0.1 g	\$737.00
107235	TC-6200	6,200 g x 0.1 g	\$795.00

Options/Accessories

Part #	Description	Price
107236	Rechargeable battery TC-620, TC-1200, 32 hr	\$105.00
107237	Rechargeable battery TC-4200, TC-6200, 32 hr	\$105.00
107238	RS-232 option with DIN-5-Pin connector (not compatible with battery option) (TC-620, TC-1200)	\$130.00
107239	RS-232 option with DIN-5-Pin connection (not compatible with battery option) (TC-4200, TC-6200)	\$130.00
107240	In-use dust cover, 620 g to 1,200 g	\$27.00
107250	In-use dust cover, 4,200 g to 6,200 g	\$27.00
109236	Underweigh hook TC-620, TC-1200	\$27.00
109292	Underweigh hook TC-4200, TC-6200	\$27.00
42566	120VAC adapter/12VDC	\$68.00
42168	230VAC adapter	\$74.00
107243	Additional operating manual	\$16.00
75351	WinWedge® software	\$325.00
115303	Five-pin DIN to DB9F RS-232 cable	\$98.00
115148	RS-232 manual	\$6.00



Standard Features

- External weight calibration
- Large, 16.5 mm-high backlit liquid crystal display (LCD)
- Selectable modes: Weight, Unit, Count and Percentage
- 12 units of measurement
- Mono-metal tuning fork sensor (MMTS) provides quick response and stability
- 20-step bar graph display
- 115 VAC adapter included (230 VAC optional)
- One part in 620,000 resolution
- RS-232 bidirectional
- Plastic housing on models <1,000 g, plastic top and die cast bottom on models >1,000 g

Options

- Rechargeable battery
- Under-hook weighing

Specifications

	TP-220 [^]	TP-820	TP-3200	TP-8200	TP-12K
Part #	107244	107245	107246	107247	107248
List Price	\$1,050.00	\$1,050.00	\$1,190.00	\$1,050.00	\$1,210.00
Capacity	220 g	820 g	3,200 g	8,200 g	12,000 g
Resolution	0.001 g	0.01 g	0.01 g	0.1 g	0.1 g
Operating Modes	Counting, Percentage, Limit Function (checkweighing)				
Repeatability	1 division				
Linearity	1 division				
Operating Temperature	41° F to 95° F (5° C to 35° C)				
Pan Size	Ø 4.6 in (116.8 mm)	6.6 in x 5.5 in (167.6 x 139.7 mm)	7 in x 6.2 in (177.8 x 157.5 mm)		
Dimensions	9.2 x 7.1 x 6.6 in (including windshield) (235 x 182 x 170 mm)	9.2 x 7.1 x 2.9 in (235 x 182 x 75 mm)	10.1 x 7.5 x 3.4 in (265 x 192 x 87 mm)		
RS-232 Specifications	Baud rate - 1200/2400/2800/9600; Data bits - 8, Connector - DIN 5-Pin				
Est. Ship Weight	2.9 lb (1.3 kg)			6.2 lb (2.8 kg)	
Calibration Weight	200 g	800 g	3,000 g	8,000 g	12,000 g
Power	120VAC adapter				
Battery Option	Nickel Cadmium battery, 12-hour run time, 24-hour charge time				
Warranty	Five-year Limited Warranty				
Return Policy	Rice Lake Standard Policy				

[^]Weighing Chamber